

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODE								MATION						
YEAI		EST GROUP		VEHICLE CLASS(ES)					ATEGORY		FUEL TYPE			
2025	5 SK	MXV01.6J13		PC					ELECTRIC HICLE		GASOLINE			
	USEFUL	LIFE (miles)		VEHICLE EMISSION CATEGORY					INTERIM / IN	IEDIATE IN-USE STD				
EXI	I/ORVR	EVAP			FTP SFTF				FTP	SFTP				
1!	50000	150000		LEV3	SULEV30 LEV 3 COMPOSITE			MPOSITE	PM		*			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD STATUS			ENGINE DISPLACEMENT			
DFI, WR-HO2S, HO2S, WU-TWC, TWC, TC, CAC, EGR, EGRC								FULL	ALL MODELS					
*						PARTIAL		*		1.6				
*			*					PARTIAL WITH *						
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
	SKMXR01	.37J1G		LEV 3	OPTION2	PC			C	HCT				
		·		E	EMISSION CI	REDIT	INFC	RMATION	·					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS			
	N N							N N						
				NMOG	AND FLEET	AVE	RAGE		TION					
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	IO/NMHC RATIO	PC+101/0-3/501						(-)				
*	*	1.10		*	0	.030		0.030 *						

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 26th day of February 2024.

Folin U. Lang

Robin U. Lang, Chief *O* Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/I	-	-	O mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CER	T STD
FTP@50K	*		*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10		0.010	0.030	0.3	1.0	*	*	*	4	0.00	0 0.001
50°F @4K	GASOLINE- TIER3 E10		0.016	0.060	0.1	1.0	*	*	*	8		
				FUEL TYP	E		NN	IOG+N	Ox (g/mi)		CO (g/	/mi)
			I		E		CE	RT	STD	CER	Т	STD
HWFET @ 50I				*			*	*		*		
HWFET @ UL			GASOI	INE-TIEF	R3 E10		0.0	06	0.030			
20°F @ 50K		COLD	CO E10 R	EGULAR G	ASOLINE	(TIER3)				0.2	2	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			Эг	P E.	λΠΑL		133101	ISTANDA	1803/	AND	CERTIFIC		VELS				
						l	JS06				SC03		C	OMPOS	ITE		
	FUEL TY	PE			OG+N g/mi)		CO (g/mi)	Pl (mg			DG+NOx g/mi)	CO (g/mi)	NMOG+NC (g/mi))x C (g/i	-	PM (mg/mi)	
@ 4K	*	* C		*			*				*	*					
•			STD				*			*		*					
			CERT		*		* 5		*		*	0.009	0.	3	*		
@ UL	GASOLIN TIER3 E		SID		*		*	6		*		*	0.050	4.	2	*	
			BIN										0.030				
		WH	OLE VE	IICL	E EV/	APORA	TIVE E	MISSION	STAN	DAR	DS AND C	ERTIFICA	TION LEVE	ELS			
						W	IOLE VEHICLE EVAPORATIVE TESTING										
	ORATIVE			FUEL TYPE		3DHS (g/		g/test) @ UL		2Dł	IS (g/test)	@ UL	F	RL (g/mi) @ L		UL	
					CER	T S	STD	FEL	CER	RL	STD	FEL	CE	RT		STD	
SKMXI	SKMXR0137J1G		ASOLINE LEV3 E1		0.214 0		. 300	*	0.24	42	0.300	*	0.	0.00 C		0.05	
(ORVR / FUI	EL C	ONLY / C	ANIS	STER	BLEED	EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIFICA	ATION L	EVE	LS	
									FU	EL C	NLY EVA	P & CANIS	TER BLEE	D			
	ORATIVE			g/gallon) @ UL			FUE	~ =		HS RIG TEST g/test) @ UL			RIG TEST t) @ UL				
		FU	EL TYPE	C	ERT	STD			CEI	RT	STD	CERT	STD	CERT	•	STD	
SKMX	R0137J1G		SOLINE- ER3 E10	0	.03	0.20		OLINE- 73 E10	*		*	*	*			0.020	

CALIFORNIA

KIA CORPORATION

Executive Order: A-314-0453 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
SKMXR0137J1G	SKMXR0137J1G-MQH	0.00	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2025 MODEL YEAR: VEHICLE MODELS INFORMATION

Γ	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
	KIA	SORENTO HYBRID AWD	PC	1.6	AMS 6	SKMXR0137J1G	1	F
	KIA	SORENTO HYBRID FWD	PC	1.6	AMS 6	SKMXR0137J1G	1	F