

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRO	UP II	NFOR	MATION					
MODI YEA		TEST	T GROUP		VEHICLE CLASS(ES)					ATEGORY		FUEL TYPE		
202	5 SMBXT02.0HY1 LDT3, LDT4									ELECTRIC HICLE		GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION								CATE	MEDIATE IN-USE STD					
EXH/ORVR EVAP					FTP SF				ТР	FTP		SFTP		
1	50000		150000		LEV3	SULEV30	LEV	3 C	MPOSITE	PM		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							L		OBD S	D STATUS		ENGINE DISPLACEMENT (L)		
1	DFI, TC, CAC, WR-HO2S, HO2S, TWC(2)								FULL	*				
*	*								ARTIAL	*		2.0		
*	* *								FINES					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							Y EVAP EMISSION STD VEHICLE CLASS			ę	SPECIAL FEATURES		
	SMBXR	0170	LNF	LE	V З ОРТІ	ON2 WITH 1	FEL		LI	от3		*		
					E	EMISSION CI	REDI	T INFO	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							ZEV				OPTIONAL EXH. STD FOR WORK TRUCKS		
		N				N			N N					
					NMOG	AND FLEET	AVE	RAG		TION				
NMOG RAF	G CH4 FTP RAF NMOG/NMHC RATIO RATIO (g/mi)						0-375							
*	*		1.10		* 0.030 0.030 *							*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II system of the listed vehicle models has been determined to have five deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of seventy-five dollars (\$75) per vehicle for the third through fifth deficiencies in the listed test group that are produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the California Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2025 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$47,363 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this $\frac{10 \text{ th}}{10 \text{ th}}$ day of May 2024.

Adrin U. Lang

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

				i+NOx mi)		O mi)		Ox mi)	HC (mg	-		PM g/mi)
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*		*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10 PREM		0.026	0.030	0.4	1.0	*	*	*	4	0.000	0.001
50°F @4K		*	*	*	*	*	*	*	*	*		
								IOG+NO	x (g/mi)		CO (g/n	ni)
	FUEL TYPE							RT	STD		Т	STD
HWFET @	HWFET @ 50K			*			*	*				
HWFET @ UL		GASOLINE-TIER3 E10 PREM						15	0.030			
20°F @ 50K		50K COLD CO E10 PREMIUM GASOLINE (TIER3) 0.5							5	12.5		
			SETP EXH	AUST EM	ISSION ST					IS		

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			SF	I P EX	(HAU:	SIEMI	SSION	STANDA	ARDS	AND	CERTIFIC	ATION LE	VELS					
						ι	IS06				SC03			CC	OMPOS	SITE		
	FUEL TY	PE)G+N(g/mi)		CO (g/mi)	Pl (mg/			DG+NOx g/mi)	CO (g/mi)		IMOG+NOx (g/mi)		:O ′mi)	PM (mg/mi)	
@4K *		CERT		*			*				*	*						
-			STD	*			*				*	*						
	@ UL GASOLINE- PREM		CERT		*		* 2		2	*		*	0.023		1	.0	*	
@ UL			STD	*			* 6		5	* *		*	0.050		4.2		*	
			BIN										0.	050				
WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																		
	WF							OLE VEHICLE EVAPORATIVE TESTING										
	EVAPORATIVE FAMILY		FUEL TYPE		30	DHS (g/	g/test) @ UL			2DHS (g/test)		@ UL		RL (g/mi) @ l		UL		
					CERT	ERT STD		FEL	CEF	CERT STD		FEL		CEF	RT	STD		
SMBXR0170LNF		_	ASOLINE IER3 E1 PREM		0.32	8 0.	500	0.450	0.3	30	0.500	0.45	0.450		0.02		0.05	
C	DRVR / FUE	EL C	ONLY / C	ANIS	TER E	BLEED	EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERT	FIFICA	TION L	.EVE	LS	
									FU	JEL C	ONLY EVA	P & CANIS	STER	BLEEI	D			
	EVAPORATIVE FAMILY		ORVR (g/gal		allon) @ UL					HS RIG TEST g/test) @ UL		2DHS RIG (g/test) @				D CANISTER (g/test) @ 4K		
		FU	EL TYPE	CE	RT	STD			CE	RT	STD	CERT	S	TD	CER	Т	STD	
SMBXR0170LNF		-	SOLINE- ER3 E10		01	0.20	LEV	OLINE- 3 E10 REM	*	,	*	*		*	0.017		0.020	

CALIFORNIA AIR RESOURCES BOARD

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
SMBXR0170LNF	SMBXR0170LNF-LNF	*	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2025 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
MERCEDES-BENZ	GLE 350	LDT3	2.0	A9	SMBXR0170LNF	1	\$
MERCEDES-BENZ	GLE 350 4MATIC	LDT4	2.0	A9	SMBXR0170LNF	1	\$