

Executive Order: A-003-0876

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRO	UP IN	IFORI	MATION					
MOD YEA		TEST GROUP			VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
202	25	SMBXD02.0HD3			MDV5			I	DEDICATED SINGLE FUEL VEHICLE			DIESEL		
USEFUL LIFE (miles)					VEHICLE EMISSION CATEG				GORY INTERIM / INTE			RMEDIATE IN-USE STD		
EXH/ORVR EVAP					FTP S			SF	FTP FTP			SFTP		
150000 *				LEV3	SULEV230 LEV3 (HOT14 (LA92), FTP TEST			35 UC *			*			
SF	SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD STATUS			ENGINE DISPLACEMENT (L)		
1			C(2), CAC, EGR, HP-EGI PM:	RC, L				FULL	*					
*		*							PARTIAL *			2.0		
*	* *							1	TIAL WITH FINES	ALL MODELS				
			Е	VAPO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMILY	'INFORMATIO	١			
EVAP / ORVR FAMILY EVAPORATIVE STD CATE						GORY	,	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
*					*				*			*		
			•			EMISSION CI	REDIT	INFO	RMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY  NMOG CREDIT FOR NON ZERO-EVAP						ON-P	ZEV	NMOG CREDIT FOR DOF			OPTIONAL EXH. STD FOR WORK TRUCKS			
N N								N			N			
NMOG AND FLEET AVERAGE INFORMATION														
NMO(			FTP NMOG/NMHO RATIO	: 1	CHO/NMHC RATIO NMOG+NOX FLE LDT (3751 LVW-8 + MDPV (g/			500 G\	) GVW) MDV (8501-10000 G			MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*		*		*		*		*			*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-003-0876

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

#### BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have three (3) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of twenty five dollars (\$25) per vehicle for the third deficiency in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2025 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$47,363 per violation per vehicle pursuant to HSC Section 43154.

### BE IT FURTHER RESOLVED:

The fuel-fired heater incorporated in the listed vehicle models must not operate at ambient temperature above 40 °F (13 CCR Section 1961.2(a)(13) [Emission Standard for a Fuel-Fired Heater]).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 23rd day of May 2024.

Robin U. Lang, Chief

**Emissions Certification and Compliance Division** 

Robin U. Lang

Executive Order: A-003-0876

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

# **ATTACHMENT**

	EXHA	\US	ΓAND	EVAI	POR	ATIV	E EMIS	SION	STA	NDARI	DS AN	D CER	TIFIC	CATION	LEV	'ELS	<b>)</b>	
		EXH	AUST E	MISSI	ON ST	ΓAND.	ARDS A	ND CE	RTIFIC	ATION I	EVELS	(FTP, F	WFET	Г, 50°F, 2	0°F)			
	FUEL TY			nonoxid djustme PRVR [g	4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon noxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity istment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; VR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 0 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP													
				NMHC+NOx (g/mi)		Эx	CO (g/mi)			NOx (g/mi)			HCH (mg/i			PM (g/mi)		
					5	STD	CERT	S	TD	CERT	STD	CE	RT	STD	CERT		STD	
FTP@5	TP@50K		*			*	*		*	*	*		*	*	4		*	
FTP@L			EL-EPA 0.		0	.230	0.4		. 2	*	*	*		6	0.0	001	0.010	
50°F @	4K	*	*			*	*		*	*	*	*		*				
				FUEL TYPE							NMHC+NOx (g/n				CO (g/mi)			
												ST	ט	CERT		STD		
HWFE	Г @ 50K				*						*	*						
HWFET @ UL					DIESEL-EPA					0.	052	0.23						
20°F	@ 50K				*								*		*			
SFTP EXHAUST EMISSION STANDARDS AND CERTI										ERTIFIC	CATION	LEVE	LS					
				US06						SC03 NMHC+NOx CO			COMPOSITE					
	FUEL TY		YPE		NMHC+NOx (g/mi)		CO (g/mi)				IMHC+NOx (g/mi)			NMHC+NOx (g/mi)		CO /mi)	PM (mg/mi)	
@ 4K	*	ST		*			*				*	*						
					*		*		*		*	*		0.000				
e	D.T.D.G.T.T	IESEL-EPA ST			*		*		*		*			0.028		1.0	7	
@ UL	DIESEL										•	*		*	4	1.0		
					= E\/^	POP	ATIVE E	MISSIO	N STA	NDAPD	S AND	PEDTIE	CATIC	ON LEVE				
		441	IOLL V		~		HOLE V							2.4 LL VE				
	ORATIVI MILY			L TYPE		3DHS (g/test) @ U					2DHS (g/test) @			RL (g/n		mi) @ UL		
						Т	STD	FEL	CE	RT	STD	FEL		CERT			STD	
	*	*			*	* *		*		*	*	* *		*		*		
C	ORVR / F	UEL	ONLY /	CANIS	TER I	BLEE	D EVAP	ORATI\						RTIFICA		LEVE	LS	
			0D: /=											R BLEE				
	ORATIVI MILY			R (g/gallon) @		UL	L FUEL			OHS RIG TEST g/test) @ UL		2DHS RIG (g/test) @		_			D CANISTER (g/test) @ 4K	
'		FU	JEL TYI	PE CE	ERT STD		FUE	_ 1176		ERT	STD	CER		STD CE			STD	
	*	*		* *		*	*			*	*	*		* :		* *		
	EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)																	
EVAF	PORATIV	Æ FA	MILY		LEAK	FAM	ILY			CER	Т				STD			
		*					*					*						



Executive Order: A-003-0876

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: .DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV; medium-duty vehicle; MDV4; MDV 8501-10000#GVWR; MDV5; MDV 10001-14000#GVWR; MDPV; mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia: NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission: AM: automated manual transmission: AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

# 2025 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
MERCEDES-BENZ	SPRINTER 3500 XD	MDV5	2.0	A9	*	1	\$
MERCEDES-BENZ	SPRINTER 3500 XD AWD	MDV5	2.0	A9	*	1	\$
MERCEDES-BENZ	SPRINTER 4500	MDV5	2.0	A9	*	1	\$