

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO		NFOR	MATION						
MOD YEA		EST GROUP		VEHICLE CLASS(ES)					ATEGORY		FUEL TYPE			
202	5 SI	BMXJ04.4S68		LDT4, PC					ELECTRIC HICLE		GASOLINE			
	USEFU	L LIFE (miles)		VEHICLE EMISSION CATEGORY					INTERIM / INTERMEDIATE IN-USE STD					
EX	H/ORVR	EVAP		FTP		SF	SFTP FTP			SFTP				
1	50000	15000	0	LEV3	ULEV70	LEV	3 CC	MPOSITE	*		*			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	STATUS		ENGINE DISPLACEMENT (L)			
1 2WU-TWC, 2TWC, 2WR-HO2S, 2HO2S, DFI, 2TC, 2CAC								FULL	*					
*			*				Р	ARTIAL	*		4.4			
*							TIAL WITH	ALL MODELS						
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							(SSION STD E CLASS	S	PECIAL FEATURES			
	SBMXR0	180G05	LI	EV 3 OPTI	ON2 WITH	FEL	PC			*				
				E	EMISSION CI	REDIT	r info	ORMATION						
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						ON-P	NMOG CREDIT FOR DOR			2	OPTIONAL EXH. STD FOR WORK TRUCKS			
N N								N N						
				NMOG	AND FLEET		RAGE		TION					
NMOG CH4 FTP RAF RAF NMOG/NMHC RATIO					NMOG+NOX FLEET ST PC+LDT (0-3750 LVW (g/mi)									
*	*	1.10		*	0	.030			0.030		*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicle model 760i xDrive Sedan has been determined to have two (2) deficiencies and the vehicle models ALPINA XB7, X5 M60i xDrive, X6 M60i xDrive, and X7 M60i xDrive have been determined to have three (3) deficiencies. The listed vehicle models with two (2) deficiencies are approved subject to the manufacturer paying a fine of fifty dollars (\$50) per vehicle for the first and second deficiency in the listed test group that is produced and delivered for sale in California. The listed vehicle models with three (3) deficiencies are approved subject to the manufacturer paying a fine of fifty dollars (\$50) per vehicle for the second and third deficiency in the listed test group that is produced and delivered and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the California Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2025 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$47,363 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-008-0613 dated March 18, 2024.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 29th day of May 2024.

Robin U. Lang

Robin U. Lang, Chief *O* Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/	i+NOx mi)	-	O mi)		Ox mi)		HCHO (mg/mi)			M mi)
			CERT	STD	CERT S		CERT	STD	CER	г ѕт	D CI	ERT	STD
FTP@50K	*		*	*	*	*	*	*	*	*		*	*
FTP@UL	GASOLINE- TIER3 E10		0.035	0.070	0.4	1.7	*	*	*	4	0.	001	0.003
50°F @4K		SOLINE- R3 E10	0.032	0.140	0.3	1.7	*	*	*	16	;		
								IOG+N		СО	(g/mi))	
				FUEL TYP	CE	CERT		STD CE		CERT			
HWFET @) 50K			*			*	*					
HWFET @	2) UL		GASOI	0.0	05	0.070							
20°F @ 50K		COLD	CO E10 R	EGULAR G	ASOLINE	(TIER3)					0.7		10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			361		1031		33101	I STANDA	ARD3	AND	CERTIFIC		VELS				
						ι	JS06				SC03		C	OMPOS	ΤE		
	FUEL TY	PE		NMOG+ (g/m			CO (g/mi)	Pl (mg/			DG+NOx g/mi)	CO (g/mi)	NMOG+NO (g/mi))x C((g/r	-	PM (mg/mi)	
@ 4K	* _		CERT	*		*					*	*					
•			STD	*		*				*		*					
			CERT	*	*		* 2		2	*		*	0.031	0.	7	*	
@ UL	GASOLIN TIER3 E	SID		*	*		* 6		5		*	*	0.050	4.	4.2	*	
			BIN										0.070				
		WHC		IICLE E	VAPC	RA	TIVE E	MISSION	STAN	IDAR	DS AND C	ERTIFICA	TION LEVE	LS			
					WHOLE VEHICLE EVAPORATIVE TESTING												
	EVAPORATIVE FAMILY		FUEL TYPE		E 3DHS ((g/test) @ UL			2DHS (g/test)			F	RL (g/mi) @ l		UL	
				CERT		S	TD FEL		CEF	CERT STD		FEL	CE	RT	STD		
SBMXI	SBMXR0180G05		ASOLINE LER3 E1		0.184 0		.300 0.500		0.2	56	0.300	0.50	0.	0.01		0.05	
C	ORVR / FUI	EL O	NLY / C	ANISTE	R BLI	EED	EVAP	ORATIVE	EMIS	SION	I STANDA	RDS AND	CERTIFICA	TION LI	EVE	LS	
				FUEL ONLY EVAP & CANISTER BLEED													
	ORATIVE	ORVR (g/gallon) @ UL			-		-	DHS RIG TEST (g/test) @ UL		-	RIG TEST t) @ UL			CANISTER test) @ 4K	
		FUE	EL TYPE	CERT	S	٢D			CE	RT	STD	CERT	STD	CERT		STD	
SBMX	R0180G05		SOLINE- ER3 E10	0.05	0.	20		OLINE- R3 E10	*	r	*	*	*	0.011		0.020	



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
SBMXR0180G05	SBMXR0180G05-001	0.01	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2025 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS ENGINE (L) TRANS TYPE		EVAPORATIVE FAMILY	EXH ECS	OBD	
BMW	7601 XDRIVE SEDAN	PC	4.4	SA8	SBMXR0180G05	1	\$
BMW	ALPINA XB7	LDT4	4.4	SA8	SBMXR0180G05	1	\$
BMW	X5 M601 XDRIVE	LDT4	4.4	SA8	SBMXR0180G05	1	\$
BMW	X6 M601 XDRIVE	LDT4	4.4	SA8	SBMXR0180G05	1	\$
BMW	X7 M601 XDRIVE	LDT4	4.4	SA8	SBMXR0180G05	1	\$