

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION														
MODE YEA		EST GROUP		VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY		FUEL TYPE			
202	5 51	SMXJ02.0F6X		L	DT2, PC			-	SINGLE FUEL HICLE	GASOLINE				
	USEFU	L LIFE (miles)		VEH	ICLE EMISS	ION C	ATE	GORY	INTERIM / IN	/ INTERMEDIATE IN-USE STD				
EXI	I/ORVR	EVAP		FTP		SFTP FTP				SFTP				
1!	50000	150000	)	LEV3	SULEV30	LEV	3 CC	MPOSITE	*		*			
SPI	ECIAL F	EATURES & EX			ON CONTRO	L		OBD S	TATUS	ENGINE DISPLACEME				
1	WU-TW	C, TWC, WR-H	02S, CAG		FI, MFI, TO	FULL SOME MODELS								
*			*				Р	ARTIAL	SOME MODELS	2.0				
*			*					TIAL WITH	*	1				
		E	VAPO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	(INFORMATIO	1				
EVA	\P / OR\	R FAMILY	EVA	PORATIVE	E STD CATE	GORY	EVAP EMISSION ST VEHICLE CLASS			SPECIAL FEATURES				
	SBMXR0	120011	LI	EV 3 OPTI	ION2 WITH	FEL		I	PC		*			
				E	EMISSION CI	REDIT	INFC	ORMATION						
	REDIT F	DX FLEET AVE. DR EXTENDED RRANTY			EDIT FOR N ZERO-EVAP	ON-P	ZEV	NMOG CREDIT FOR DOP			OPTIONAL EXH. STD FOR WORK TRUCKS			
	N N								N		N			
				NMOG	AND FLEET		RAGE		TION					
NMOG RAF	NMOG/NMHC PC+LDL (0-3				0-375					NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)				
*	*	1.10		*	0	.030			0.030		*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV). Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-008-0622 dated March 22, 2024.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 10th day of May 2024.

Polin U. Lang

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/I	-	C (g/I	O mi)	N( (g/	Ox mi)		HO /mi)	-	M /mi)	
			CERT	STD	CERT STD C		CERT	STD	CERT	STD	CERT	STD	
FTP@50K		*	*	*	*	*	*	*	*	*	*	*	
FTP@UL		OLINE- R3 E10	0.017	0.030	0.4	1.0	*	*	*	4	0.000	0.003	
50°F @4K		OLINE- R3 E10	0.014	0.060	0.3	1.0	*	*	*	8			
					-		NN	NMOG+NOx (g/mi)			CO (g/mi)		
	FUEL TYPE				CE	RT	STD	CER	Т	STD			
HWFET @ 50K			*		*								
HWFET @ UL			GASOI	INE-TIEF	R3 E10		0.0	09	0.030				
20°F @ 50K		COLD	CO E10 R	EGULAR G	ASOLINE	(TIER3)				0.4		10.0	

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			эг	P E	лпаu		133101	ISTANDA	ARDS A		CERTIFIC		VELS			
						l	JS06				SC03		C	OMPOSI	TE	
	FUEL TY	PE			DG+N g/mi)		CO (g/mi)	Pl (mg/			DG+NOx g/mi)	CO (g/mi)	NMOG+NC (g/mi)	)x CC (g/n		PM (mg/mi)
@ 4K	*		CERT	*		*					*	*				
•			STD		*	*				*		*				
			CERT		*		*	0	)		*	*	0.014	0.	4	*
@ UL	GASOLIN TIER3 E		STD		*		*	6	5		*	*	0.050	4.3	2	*
			BIN										0.050			
	WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS															
						W	HOLE \	/EHICLE	EVAPO	ORAI	TIVE TEST	ING				
	ORATIVE	FII		E	3DHS (g		g/test) @ UL		2DHS (g/test)		@ UL	F	RL (g/mi) (		@ UL	
					CER	RT S	STD	FEL	CER	R	STD	FEL	CE	RT	Ś	STD
SBMXI	R0120U11		ASOLINE IER3 E1		0.19	91 0	. 300	0.300	0.18	39	0.300	0.300	0.	01	0	. 05
(	ORVR / FUI	EL C	ONLY/C	ANIS	STER	BLEED	EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIFICA	TION LE	VEI	S
									FU	EL C	ONLY EVA	P & CANIS	TER BLEE	D		
	ORATIVE	(	ORVR (g	/gall	on) @	0 UL	FUE	L TYPE			IG TEST ) @ UL		tig test () @ UL			NISTER st) @ 4K
		FU	EL TYPE	CI	ERT	STD			CEF	RT	STD	CERT	STD	CERT		STD
SBMX	R0120U11		SOLINE- ER3 E10	0	.10	0.20		OLINE- R3 E10	*		*	*	*	0.015		0.020



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
SBMXR0120U11	SBMXR0120U11-01	0.01	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2025 MODEL YEAR: VEHICLE MODELS INFORMATION

MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
COOPER HARDTOP 2 DOOR	PC	2.0	AMS7	SBMXR0120U11	1	F
COOPER S HARDTOP 2 DOOR	PC	2.0	AMS7	SBMXR0120U11	1	P
COOPER S HARDTOP 4 DOOR	PC	2.0	AMS7	SBMXR0120U11	1	F
COUNTRYMAN S ALL4	LDT2	2.0	AMS7	SBMXR0120U11	1	P
	COOPER HARDTOP 2 DOOR COOPER S HARDTOP 2 DOOR COOPER S HARDTOP 4 DOOR	COOPER HARDTOP 2 DOOR PC   COOPER S HARDTOP 2 DOOR PC   COOPER S HARDTOP 4 DOOR PC	COOPER HARDTOP 2 DOORPC2.0COOPER S HARDTOP 2 DOORPC2.0COOPER S HARDTOP 4 DOORPC2.0	COOPER HARDTOP 2 DOORPC2.0AMS7COOPER S HARDTOP 2 DOORPC2.0AMS7COOPER S HARDTOP 4 DOORPC2.0AMS7	MODELVEH CLASSENGINE (L)TRANS TYPEFAMILYCOOPER HARDTOP 2 DOORPC2.0AMS7SBMXR0120U11COOPER S HARDTOP 2 DOORPC2.0AMS7SBMXR0120U11COOPER S HARDTOP 4 DOORPC2.0AMS7SBMXR0120U11	MODELVEH CLASSENGINE (L)TRANS TYPEFAMILYECSCOOPER HARDTOP 2 DOORPC2.0AMS7SBMXR0120U111COOPER S HARDTOP 2 DOORPC2.0AMS7SBMXR0120U111COOPER S HARDTOP 4 DOORPC2.0AMS7SBMXR0120U111