

TOYOTA MOTOR CORPORATION

Executive Order: A-014-1215

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MODE		TEST GROUP			VEHICLE CLASS(ES)				ATEGORY		FUEL TYPE		
2025	ST	YXV02.4H33		PC					ELECTRIC HICLE		GASOLINE		
	USEFUL	. LIFE (miles)		VEH	IICLE EMISS	CATEC	ORY	INTERIM / IN	TERM	ERMEDIATE IN-USE STD			
EXH/ORVR EVAP				FTP			SF	ТР	FTP		SFTP		
15	150000 150000			LEV3	SULEV30 LEV 3 COMP			MPOSITE	*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTRO SYSTEMS							OBD STATUS			ENGINE DISPLACEMENT (L)			
1	DFI,	SFI, WR-HO2	S(2)	, TWC(2)	?), TC, CAC			FULL	ALL MODELS				
*	* PARTIAL *								2.4				
*	* PARTIAL WITH * FINES												
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							,	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
:	STYXR01	65J72	V 3 OPTION2 WITH FEL				PC			*			
EMISSION CREDIT INFORMATION													
	EDIT FO	X FLEET AVE. OR EXTENDED RRANTY			MOG CREDIT FOR NON-PZEV ZERO-EVAP			NMOG C	REDIT FOR DO	~	OPTIONAL EXH. STD FOR WORK TRUCKS		
N N							N			N			
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	CH4 RAF	NMCG/NMUC DCTI DT /0 3760											
*	*	1.10		*	0	.030			0.030		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



TOYOTA MOTOR CORPORATION

Executive Order: A-014-1215

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this /8th day of March 2024.

Robin U. Lang, Chief

Emissions Certification and Compliance Division

Tolin U. Lang

TOYOTA MOTOR **CORPORATION**

Executive Order: A-014-1215 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																		
EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)																		
		FUEL TYPE			CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP													
					IOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)			HCH (mg/i		PM (g/mi)			
					CER.	Т	STD	CER	T ST	D	CERT	STD	CERT		STD CE		RT	STD
FTP@5	TP@50K *			*		*	*	*		*	*	*		*			*	
	FTP@UL GASOLINE- TIER3 E10		1 (0.023	37 0	.030	0.16			*	*	*			4 0.00		0.003	
50°F @4	50°F @4K *			*		*	*	*		*	*	*			*			
					FUEL TYPE								Ox (g/mi)				(g/mi)	
HWFE1	Г@5	50K					*				C	ERT *	STD *		CERT			STD
HWFE		-			GA	SOLIN	E-TIEF	R3 E10			0.	0078	78 0.030					
20°F @ 50K CO			LD CO	E10	PREM	IUM GA	ASOLINE (TIER3)							0.33		10.0		
				S	FTP E	EXHAU	IST EM	ISSION	STAND	ARDS	AND C	ERTIFIC	CATION LE	EVEL	.S			
							US06					SC03			COMPOSITE			
	FUEL T		YPE		NN	NMOG+NOx (g/mi)		CO (g/mi)	_	M /mi)	NMOG+NOx (g/mi)		CO (g/mi)			Ox CO (g/mi)		PM (mg/mi)
@ 4K	K *		CER			*		*				*	*					
		ST		STD		*		*				*						
		CI		CERT		*		*	0	. 5	*		*	0.0183		0.19		*
@ UL	@ UL GASOL		S 11			*		*	* 6			*	*		0.050		. 2	*
				BIN										0.040				
			WH	OLE VI	EHIC	LE EV							CERTIFICA	ATIO	N LEVEL	.S		
EVAPORATIVE .				IIEI TY	/DE	WHOLE VEHICLE EVAP					ORATIVE TESTING 2DHS (g/test) @ UL				RL (g/mi) @ UL			
FAMILY		[FUEL TYPE			CERT ST		FEL	CE			, <u> </u>	FEL		т	STD		
STYXR0165J72			ASOLII IER3 I	LINE- 3 E10 0.15			.300	0.300	0.1		0.300		0.300		0.007		0.05	
ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																		
										F	UEL O	NLY EVA	P & CANI	STE	R BLEED			
EVAPORATIVE FAMILY		ORVR (g/gal			llon) @	on) @ UL				HS RIG TEST g/test) @ UL			2DHS RIG (g/test) @			BLEED CANISTER EST (g/test) @ 4K		
		FU	EL TYF	PE	CERT	STD	CEI				CERT		STD	CERT		STD		
STYXR0165J72		5J72		SOLINI ER3 E:		10 00310 2		*		*	*	*		*	*		*	



TOYOTA MOTOR CORPORATION

Executive Order: A-014-1215

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
STYXR0165J72	STYXR0165J72-001	*	0.02						

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV; medium-duty vehicle; MDV4; MDV 8501-10000#GVWR; MDV5; MDV 10001-14000#GVWR; MDPV; mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIŔ/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2025 MODEL YEAR: VEHICLE MODELS INFORMATION **EVAPORATIVE EXH VEH CLASS ENGINE (L)** TRANS TYPE MAKE MODEL OBD **FAMILY ECS** TOYOTA TOYOTA CROWN AWD PC 2.4 scv6 STYXR0165J72 F 1