

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRC	UP II	NFOR	MATION					
MODE YEAF	-	EST GROUP		VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY		FUEL TYPE		
2025	5 SI	3MXV02.0M48			PC			-	SINGLE FUEL HICLE	GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISSION							CATE	GORY INTERIM / INTERMEDIATE IN-USE STD					
EXH	i/orvr	EVAP			FTP		SF	ТР	FTP		SFTP		
150000 150000					ULEV125	LEV	3 C	OMPOSITE	*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS	EN	ENGINE DISPLACEMENT (L)		
1	Т	WC, WR-HO2S,	HO2S	S, DFI,	TC, CAC			FULL	ALL MODELS				
*			*				F	PARTIAL	*		2.0		
*						PAF	TIAL WITH	*					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR								SSION STD E CLASS	SPECIAL FEATURES			
5	SBMXR0	150G30	LE	V 3 OPTI	ION2 WITH	FEL		I	2C	*			
				I	EMISSION CI	REDI	T INFO	ORMATION					
	EDIT F	DX FLEET AVE. OR EXTENDED RRANTY	I		EDIT FOR N ZERO-EVAP	ON-P	ZEV	NMOG C	REDIT FOR DOF	,	OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N		N		
				NMOG	AND FLEE	AVE	RAG		TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO		O/NMHC RATIO				V) LDT	+NOX FLEET S1 (3751 LVW-8500 R) + MDPV (g/mi		D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	0	.030			0.030		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this //t/c day of July 2024.

Tolin U. Lang

Robin U. Lang, Chief *O* Emissions Certification and Compliance Division



FUEL TYPE

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG+NOx (g/mi) CO (g/mi) CO   CERT STD CERT STD C			Ox mi)		HCHO (mg/mi)		PM g/mi)		
					CERT	STD	CERT	STD	CERT	STD		
FTP@50K	K *		*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10		0.047	0.125	0.6	2.1	*	*	*	4	0.001	0.003
50°F @4K		SOLINE- R3 E10	0.034	0.250	0.6	2.1	*	*	*	16		
				FUEL TYP	E		NN	NMOG+NOx (g/mi)			CO (g/m	ni)
			l	FUELITP	E		CE	RT	STD	CER	Т	STD
HWFET @ 50K		*						•	*			
HWFET @ UL			GASOI	LINE-TIER	R3 E10		0.0	)25	0.125			
20°F @ 50K		COLD	CO E10 R	EGULAR G	ASOLINE	(TIER3)				1.0	)	10.0

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			551	PEX	HAU	21 EIN	12210IN	I STANDA	ARDS	AND	CERTIFIC	ATION LE	VELS		
						ι	JS06				SC03		C	OMPOSITE	
	FUEL TY	PE			G+N g/mi)	Ox	CO (g/mi)	Pl (mg/			DG+NOx g/mi)	CO (g/mi)	NMOG+NC (g/mi)	x CO (g/mi)	PM (mg/mi)
@ 4K	*		CERT	*			*				*	*			
_			STD				*				*	*			
			CERT		*		*	0			*	*	0.052	0.8	*
@ UL	GASOLIN TIER3 E		STD		*		*	6	;		*	*	0.050	4.2	*
			BIN										0.120		
		WHC	DLE VEF	IICLE	E EVA	PORA	TIVE E	MISSION	STAN	DAR	DS AND C	ERTIFICA	TION LEVE	LS	
						W	IOLE V	/EHICLE	EVAP	ORAI	TIVE TEST	ING			
	ORATIVE AMILY	FL	JEL TYP	E	31	DHS (g	/test) @	DL 🔋		2DH	IS (g/test)	@ UL	F	RL (g/mi) @	≬UL
					CER	T S	TD	FEL	CEF	RL	STD	FEL	CE	RT	STD
SBMXI	R0150G30	-	ASOLINE IER3 E1			0.	0.01 0.05								
(	ORVR / FUI	EL O	NLY / C/	ANIS'	TER	BLEED	EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIFICA	TION LEV	ELS
									FU	IEL C	NLY EVA	P & CANIS	STER BLEE	D	
	ORATIVE	C	DRVR (g/	gallo	on) @	UL	FUE	L TYPE	-	-	IG TEST ) @ UL		RIG TEST t) @ UL		ANISTER est) @ 4K
		FUE	EL TYPE	CE	RT	STD			CE	RT	STD	CERT	STD	CERT	STD
SBMX	R0150G30		OLINE- R3 E10	0.	04	0.20		OLINE- R3 E10	*		*	*	*	0.004	0.020



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
SBMXR0150G30	SBMXR0150G30-001	0.00	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2025 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
BMW	2301 COUPE	PC	2.0	SA8	SBMXR0150G30	1	F
BMW	2301 XDRIVE COUPE	PC	2.0	SA8	SBMXR0150G30	1	F