

FCA US LLC.

Executive Order: A-009-1670

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| NODEL TEST GROUP VEHICLE CLASS(ES) FUEL CATEGORY FUEL TYPE | | TEST GROUP INFORMATION | | | | | | | | | | | |
|--|---|------------------------|----------------|------|-----------|-------------|-------|---------------|-----------|--------------------|------|-------------------|--|
| USEFUL LIFE (miles) | | | EST GROUP | | VEHIC | LE CLASS(E | S) | | FUEL C | ATEGORY | | FUEL TYPE | |
| STP | 202 | 5 SC | CRXD03.65V1 | | | MDV4 | |] | | | | GASOLINE | |
| 150000 | | USEFU | L LIFE (miles) | | VEH | IICLE EMISS | ION C | ATEC | ORY | INTERIM / IN | TERM | EDIATE IN-USE STD | |
| 150000 | EXI | 1/ORVR | EVAP | | | FTP | | SF | TP | FTP | | SFTP | |
| SYSTEMS | 1! | 50000 | 150000 |) | LEV3 | ULEV250 | US0 | 6, SC | 03, FTP | * | | * | |
| | SPI | CIAL F | | | | ON CONTRO | L | | OBD S | TATUS | EN | | |
| * * * * * * * * * * * * * * * * * * * | 1 | | EGRC, 2HO2S | (2), | SFI, 2TW | C, EGR | | | FULL | ALL MODELS | | | |
| FINES | * | | | * | | | | P. | ARTIAL | * | 3.6 | | |
| EVAP / ORVR FAMILY EVAPORATIVE STD CATEGORY SCRXF0180TP0 LEV 3 OPTION2 WITH FEL MDV4 * EMISSION CREDIT INFORMATION NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG AND FLEET AVERAGE INFORMATION NMOG CREDIT FOR DOR NMOG AND FLEET AVERAGE INFORMATION NMOG CH4 RAF NMOG/NMHC RATIO NMOG/NMHC RATIO NMOG+NOX FLEET STD NMOG+NOX FLEET STD NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi) NMOG CH4 RAF NMOG/NMHC RATIO | * | | | * | | | | | | * | | | |
| SCRXF0180TP0 LEV 3 OPTION2 WITH FEL MDV4 * EMISSION CREDIT INFORMATION NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON-PZEV ZERO-EVAP NMOG AND FLEET AVERAGE INFORMATION NMOG AND FLEET AVERAGE INFORMATION NMOG CREDIT FOR DOR OPTIONAL EXH. STD FOR WORK TRUCKS N N N N N N NMOG CREDIT FOR DOR OPTIONAL EXH. STD FOR WORK TRUCKS NMOG AND FLEET AVERAGE INFORMATION NMOG CH4 RAF NMOG/NMHC RATIO NMOG+NOX FLEET STD NMOG+NOX FLEET STD NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi) MDV (10,001-14,000 GVWR) (g/mi) | | | E | VAPO | RATIVE & | REFUELING | (EVA | P/OR | VR) FAMIL | INFORMATION | | | |
| EMISSION CREDIT INFORMATION NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY N N N N N N N NMOG AND FLEET AVERAGE INFORMATION NMOG CREDIT FOR DOR OPTIONAL EXH. STD FOR WORK TRUCKS N N N N N N N N N N N N N N N N N N N | EVA | AP / OR\ | R FAMILY | EVA | PORATIVE | STD CATE | GORY | , | | | SP | ECIAL FEATURES | |
| NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON-PZEV ZERO-EVAP NMOG CREDIT FOR DOR FOR WORK TRUCKS N NMOG AND FLEET AVERAGE INFORMATION NMOG CHARTIO NMOG-NOX FLEET STD MDV (8501-10000 GVWR) (g/mi) NMOG-NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi) | | SCRXF0 | 180TP0 | Ll | EV 3 OPTI | ON2 WITH | FEL | MDV4 * | | | | * | |
| CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON-PZEV ZERO-EVAP NMOG CREDIT FOR DOR NMOG CREDIT FOR DOR NMOG CREDIT FOR DOR NMOG WORK TRUCKS N NMOG AND FLEET AVERAGE INFORMATION NMOG CREDIT FOR DOR NMOG WORK TRUCKS NMOG AND FLEET AVERAGE INFORMATION NMOG CREDIT FOR DOR NMOG WORK TRUCKS NMOG AND FLEET AVERAGE INFORMATION NMOG CREDIT FOR DOR NMOG WORK TRUCKS NMOG AND FLEET AVERAGE INFORMATION NMOG CREDIT FOR DOR NMOG WORK TRUCKS NMOG AND FLEET AVERAGE INFORMATION NMOG CREDIT FOR DOR NMOG WORK TRUCKS NMOG AND FLEET AVERAGE INFORMATION NMOG CREDIT FOR DOR NMOG WORK TRUCKS | | | | | | EMISSION CI | REDIT | INFC | RMATION | • | | | |
| NMOG AND FLEET AVERAGE INFORMATION NMOG CH4 RAF NMOG/NMHC RATIO NMOG/NMHC RATIO NMOG+NOX FLEET STD NMOG+NOX FLEET STD MDV (8501-10000 GVWR) (g/mi) NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi) | | REDIT F | OR EXTENDED | | | | ON-P | ZEV | NMOG C | REDIT FOR DOP | | | |
| NMOG RAF RAF RATIO NMOG/NMHC RATIO NMOG+NOX FLEET STD LDT (3751 LVW-8500 GVW) + MDPV (g/mi) NMOG+NOX FLEET STD MDV (8501-10000 GVWR) (g/mi) NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR | N N | | | | | | | | | N | | N | |
| NMOG CH4 RAF NMOG/NMHC RATIO LDT (3751 LVW-8500 GVW) MDV (8501-10000 GVWR) MDV (10,001-14,000 GVWR) (g/mi) MDV (10,001-14,000 GVWR) (g/mi) | | | | | NMOG | AND FLEET | AVE | RAGE | INFORMA | TION | | | |
| * * 1.10 * * * * | NMOG CH4 NMOG/NMHC HCHO/NMHC LDT (3751 LVW- | | | | VW-8 | 500 G | | 501-10000 GVW | | MDV (10,001-14,000 | | | |
| | * | * | 1.10 | | * | | * | | | * | | * | |

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



FCA US LLC.

Executive Order: A-009-1670

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

him Yacorbian for

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 28th day of June 2024.

Robin U. Lang, Chief

Emissions Certification and Compliance Division



ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION | EVELS (FTP. HWEFT, 50°F, 20°F)

| EXTINOUT EMISSION STANDARDS AND SERVIN ISATISM ELVELS (1 11, 1111 E1, 55 1, 25 1) |
|--|
| CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon |
| monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity |
| adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; |
| 00/07/10/ 11 11 11 11 11 11 11 11 11 11 11 |

FUEL TYPE

adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

| | | NMOG+NOx (g/mi) | | | | NOx (g/mi) | | HCHO (mg/mi) | | PM (g/mi) | |
|----------|-----------------------|--------------------|-------|------|-----|---------------|-----|-----------------|-----|--------------|-------|
| | | CERT | STD | CERT | STD | CERT | STD | CERT | STD | CERT | STD |
| FTP@50K | * | * | * | * | * | * | * | * | * | * | * |
| FTP@UL | GASOLINE- LEV3 E10 | 0.0295 | 0.250 | 0.41 | 6.4 | * | * | * | 6 | 0.0003 | 0.008 |
| 50°F @4K | GASOLINE- LEV3 E10 | 0.0421 | 0.500 | 0.44 | 6.4 | * | * | * | 32 | | |

| | FUEL TYPE | NMOG+N | Ox (g/mi) | CO (g/mi) | | |
|-------------|-------------------|--------|-----------|-----------|-----|--|
| | FUELTIFE | CERT | STD | CERT | STD | |
| HWFET @ 50K | * | * | * | | | |
| HWFET @ UL | GASOLINE-LEV3 E10 | 0.0140 | 0.250 | | | |
| 20°F @ 50K | * | | | * | * | |

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

| | | | | US06 | | SC03 | 3 | COM | IPOSITE | |
|------|-----------------------|------|--------------------|--------------|---------------|--------------------|--------------|--------------------|----------------|---------------|
| | FUEL TYPE | | NMOG+NOx (g/mi) | CO (g/mi) | PM (mg/mi) | NMOG+NOx (g/mi) | CO (g/mi) | NMOG+NOx (g/mi) | CO (g/mi) | PM (mg/mi) |
| @ 4K | * | CERT | * | * | | * | * | | | |
| | | STD | * | * | | * | * | | | |
| | | CERT | * | * | * | * | * | 0.0359 | 13.09 | 0.9 |
| @ UL | GASOLINE- LEV3 E10 | STD | * | * | * | * | * | 0.800 | 22.0 | 10 |
| | | BIN | | | | | | * | | |

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

| | FUEL TYPE | | WHOLE \ | | | | | | |
|--------------------|-----------------------|--------|--------------|-------|--------|---------------|----------------|-------|------|
| EVAPORATIVE FAMILY | | 3DH | S (g/test) @ | D UL | 2DI | HS (g/test) (| RL (g/mi) @ UL | | |
| | | CERT | STD | FEL | CERT | STD | FEL | CERT | STD |
| SCRXF0180TP0 | GASOLINE- LEV3 E10 | 0.2494 | 0.600 | 0.550 | 0.1383 | 0.600 | 0.550 | 0.000 | 0.05 |

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

| | | | | FUEL ONLY EVAP & CANISTER BLEED | | | | | | | | |
|--------------------|-----------------------|-------|------|---------------------------------|--------------------------------|-----|--------------------------------|-----|--------------------------------------|-------|--|--|
| EVAPORATIVE FAMILY | ORVR (g/gallon) @ UL | | | FUEL TYPE | 3DHS RIG TEST (g/test) @ UL | | 2DHS RIG TEST (g/test) @ UL | | BLEED CANISTER TEST (g/test) @ 4K | | | |
| | FUEL TYPE | CERT | STD | | CERT | STD | CERT | STD | CERT | STD | | |
| SCRXF0180TP0 | GASOLINE- LEV3 E10 | 0.052 | 0.20 | GASOLINE- LEV3 E10 | * | * | * | * | 0.0081 | 0.030 | | |



FCA US LLC.

Executive Order: A-009-1670

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

| EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES) | | | | | | | | |
|---|------------------|------|------|--|--|--|--|--|
| EVAPORATIVE FAMILY | LEAK FAMILY | CERT | STD | | | | | |
| SCRXF0180TP0 | SCRXF0180TP0-LF1 | * | 0.02 | | | | | |

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV; medium-duty vehicle; MDV4; MDV 8501-10000#GVWR; MDV5; MDV 10001-14000#GVWR; MDPV; mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIŔ/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2025 MODEL YEAR: VEHICLE MODELS INFORMATION

| MAKE | MODEL | VEH CLASS | ENGINE (L) | TRANS TYPE | EVAPORATIVE FAMILY | EXH ECS | OBD |
|------|-------------------------------|-----------|------------|------------|--------------------|------------|-----|
| RAM | PROMASTER 3500 CAB CHASSIS | MDV4 | 3.6 | A9 | SCRXF0180TP0 | 1 | F |