

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION														
MODE		TEST GROUP VEHICLE CLA					S)	FUEL CATEGORY				FUEL TYPE		
2025	5 5	SGMXT06.2375 LDT4							DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION							ATE	GORY	IEDIATE IN-USE STD					
EXH/ORVR EVAP FTP					FTP		SF	ТР	FTP	SFTP				
15	50000		150000		LEV3	ULEV50	LEV	'3 CO	MPOSITE	*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS	EN	ENGINE DISPLACEMENT (L)			
1		Ι	OFI, 2WR-H	HO2S, 2TWC, 2HO2S					FULL	ALL MODELS				
*				*				Р	ARTIAL	*		6.2		
*				*					TIAL WITH FINES	*	_			
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						GORY	,	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
:	SGMXR	0173	50D	LE	V 3 OPTI	ON2 WITH H	FEL		LDT4			HCT		
					E	EMISSION CR	REDIT	INFC	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							ZEV	NMOG CREDIT FOR DOP			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N				N				N				
					NMOG	AND FLEET	AVE	RAGE		TION				
NMOG RAF	CH4 RAF		FTP MOG/NMHC RATIO		O/NMHC ATIO	C NMOG+NOX FLE PC+LDT (0-375 (g/mi)) LDT	+NOX FLEET ST (3751 LVW-8500 R) + MDPV (g/mi		D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*		1.10		*	0	.030			0.030		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 24 th day of June 2024.

Colin U. Lang

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

				G+NOx mi)	-	O mi)		Ox mi)	HC (mg			PM g/mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K	*		*	*	*	*	*	*	*	*	*	*	
FTP@UL	GASOLINE- TIER3 E10		0.032	0.050	0.5	1.7	*	*	*	4	0.002	0.003	
50°F @4K		*	*	*	*	*	*	*	*	*			
			• •		-		NN	NMOG+NOx (g/mi)			CO (g/mi)		
				FUEL TYP	E		CE	RT	STD	CER	Т	STD	
HWFET @ 50K			*					r	*				
HWFET @	@ UL		GASOLINE-TIER3 E10						0.050				
20°F @ 50K		COLD	CO E10 R	EGULAR G	ASOLINE	(TIER3)				1.6	5	12.5	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			SFT	P EXHAI	JST EN	ISSION	I STAND	ARDS	AND	CERTIFIC	ATION LE	VELS		
				US06						SC03		С	OMPOSI	ſE
	FUEL TY	PE	I	NMOG+N (g/mi)	-	CO (g/mi)	Pl (mg			DG+NOx g/mi)	CO (g/mi)	NMOG+NC (g/mi)	x CO (g/m	
@ 4K	*		ERT	*		*				*	*			
_		5	STD	*		*				*	*			
		С	ERT	*		*	1	-		*	*	0.022	0.6	5 *
@ UL	GASOLIN TIER3 E		STD	*		*	e	5		*	*	0.050	4.2	2 *
		I	BIN									0.070		
		WHOI	LE VEH	ICLE EV	APORA	TIVE E	MISSION	STAN	DAR	DS AND C	ERTIFICA	TION LEVE	LS	
					WHOLE VEHICLE EVAPORATIVE TESTING									
	ORATIVE	FUEL TYPE		PE 3DHS (g/		(g/test) @ UL		2DHS (g/test)		@ UL	F	RL (g/mi) @ UL		
				CEF	श्म	STD	FEL	CEF	RT	STD	FEL	CE	RT	STD
SGMXR	R017350D		SOLINE ER3 E1(0 1	98 0	. 500	0.500	0.2	00	0.500	0.500	0.	0.00 0.	
C	DRVR / FUR	EL ON	ILY / CA	NISTER	BLEED) EVAP	ORATIVE	EMIS	SION	I STANDA	RDS AND	CERTIFICA	TION LE	VELS
								FU	JEL C	ONLY EVA	P & CANIS	STER BLEE	D	
	ORATIVE MILY	OF	RVR (g/	gallon) (DUL	FUE	L TYPE			IG TEST) @ UL		RIG TEST t) @ UL		CANISTER /test) @ 4K
		FUEL	L TYPE	CERT	STD			CE	RT	STD	CERT	STD	CERT	STD
SGMXF	R017350D	GASOLINE		0.02	0.20		OLINE- R3 E10	*	•	*	*	*	0.008	0.020



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)								
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD					
SGMXR017350D	SGMXR017350D-LK1	*	0.02					

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2025 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
CHEVROLET	SILVERADO 4WD	LDT4	6.2	A10	SGMXR017350D	1	F
CHEVROLET	SILVERADO 4WD MUD TERRAIN TIRES	LDT4	6.2	A10	SGMXR017350D	1	F
CHEVROLET	SILVERADO 4WD ZR2	LDT4	6.2	A10	SGMXR017350D	1	F
GMC	SIERRA 4WD	LDT4	6.2	A10	SGMXR017350D	1	F
GMC	SIERRA 4WD AT4X	LDT4	6.2	A10	SGMXR017350D	1	F
GMC	SIERRA 4WD MUD TERRAIN TIRES	LDT4	6.2	A10	SGMXR017350D	1	F