

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRO	UP IN	NFOR	MATION					
MODE YEA		TES	T GROUP		VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY		FUEL TYPE		
202	5 5	SHNX	T03.53TC		LD	T2, LDT3			DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISS							ION C	ATE	GORY	INTERIM / IN	TER	ERMEDIATE IN-USE STD		
EXH/ORVR EVAP						FTP		SF	тр	FTP		SFTP		
1	50000		150000		LEV3	ULEV70	LEV	73 CC	MPOSITE	*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTRO SYSTEMS							L		OBD S	STATUS		ENGINE DISPLACEMENT (L)		
1	2WU-TWC, TWC, 2WR-HO2S, 2HO2S, EGR, DFI								FULL	ALL MODELS				
*	*							F	PARTIAL	*		3.5		
*	*							PAF	RTIAL WITH FINES	*				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							,	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
	SHNXR	.0150	BAA		LEV 3	OPTION2			LI)Т2		*		
					E	EMISSION CI	REDIT	[INF	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						ON-P	ZEV	NMOG CREDIT FOR DOP			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N				N				N		N		
					NMOG	AND FLEET	AVE	RAG	E INFORMA	TION				
NMOG RAF		CH4 RAF RATIO FTP HCHO/NMHC RATIO NMOG+NOX FL PC+LDT (0-37 (g/mi)				0-375		V) LDT	+NOX FLEET S (3751 LVW-850(R) + MDPV (g/m)	NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*		1.10		0.05	0	.030			0.030		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 2/st day of June 2024.

Polin U. Lang

Robin U. Lang, Chief *U* Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

				S+NOx mi)		O mi)		Ox mi)	HC (mg	-	(PM (g/mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	r std	
FTP@50K		*	*	*	*	*	*	*	*	*	*	*	
FTP@UL	GASOLINE- LEV3 E10		0.032	0.070	0.1	1.7	*	*	1	4	0.000	0 0.003	
50°F @4K		*	*	*	*	*	*	*	*	*			
								/IOG+N	Ox (g/mi)		CO (g/mi)		
				FUEL TYP	E		CE	RT	STD	CER	Т	STD	
HWFET @ 50K		*						,	*				
HWFET @	@ UL	GASOLINE-LEV3 E10						010	0.070				
20°F @	20°F @ 50K		CO E10 R	EGULAR G	ASOLINE	(TIER3)				1.0)	12.5	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			SFT	P EXHAL	JST EN	ISSION	STAND	ARDS A	AND	CERTIFIC	ATION LE	VELS			
						US06				SC03		C	OMPOSI	TE	
	FUEL TYI	PE		NMOG+N (g/mi)	-	CO (g/mi)	Pl (mg			DG+NOx g/mi)	CO (g/mi)	NMOG+NC (g/mi)		-	PM ng/mi)
@ 4K	*		CERT	*	*		*			*	*				
		\$	STD	*	*					*	*				
		С	CERT * * 1 * * 0.027		0.	3	*								
@ UL	GASOLIN LEV3 E1		STD	*		*	e	5		*	*	0.050	4.	2	*
			BIN									0.080			
		wно	LE VEH		APORA	TIVE E	MISSION	STAN	DAR	DS AND C	ERTIFICA	TION LEVE	ELS		
				WHOLE VEHICLE EVAPORATIVE TESTING											
	ORATIVE	FUI	EL TYP	Ξ 3	DHS (g	/test) @	0 UL		2Dł	IS (g/test)	@ UL	F	RL (g/mi)	g/mi) @ UL	
				CEF	RL :	STD	FEL	CER	T	STD	FEL	CE	RT	CO (g/mi) (m 0.3 4.2 /mi) @ UL STE 0.0! N LEVELS EED CANIS T (g/test) (c RT S	D
SHNXR	R0150BAA		SOLINE V3 E10	0 1	06 0	. 400	*	0.12	23	0.400	*	0.	00	0.0)5
C)rvr / fue	EL ON	NLY / CA	NISTER	BLEED) EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIFICA	ATION LE	VELS	
								FU	EL C	NLY EVA	P & CANIS	TER BLEE	D		
EVAPORATIVE FAMILY		O	ORVR (g/ga		ı/gallon) @ UL		FUEL TYPE		3DHS RIG TE (g/test) @ l			t) @ UL		ED CANISTER T (g/test) @ 4K	
		FUEI	L TYPE	CERT	STD]		CEF	RT	STD	CERT	STD	CERT	S	TD
SHNXR	R0150BAA		OLINE- R3 E10	0.01	0.20		OLINE- 3 E10	*		*	*	*	0.012	0.	020



HONDA MOTOR CO., LTD.

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
SHNXR0150BAA	SHNXR0150BAA-A00	*	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2025 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
HONDA	PASSPORT AWD	LDT2	3.5	SA9	SHNXR0150BAA	1	F
HONDA	RIDGELINE AWD	LDT3	3.5	SA9	SHNXR0150BAA	1	F
HONDA	RIDGELINE AWD TRAILSPORT	LDT3	3.5	SA9	SHNXR0150BAA	1	F