

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRO	UP II	NFOR	MATION					
MODE YEA		TEST GI	ROUP		VEHIC	LE CLASS(E	S)		FUEL C	EL CATEGORY FUEL TYPE				
202	5 S	STKXT03	3.3DHA		LD	T3, LDT4				ELECTRIC HICLE		GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION								CATE	EGORY INTERIM / INTERMEDIATE IN-USE \$					
EXI	H/ORVF	र	EVAP			FTP		SF	ТР	FTP		SFTP		
1	50000		150000		LEV3	ULEV50	LEV	3 CC	MPOSITE	*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							L		OBD S	TATUS	E	ENGINE DISPLACEMENT (L)		
1	TWC, CAC, TC, DFI, EGRC, HO2S, WR-HO2S, EGR								FULL	ALL MODELS				
*	*								ARTIAL	*		3.3		
*				*				1	RTIAL WITH *					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							(		SSION STD E CLASS	S	SPECIAL FEATURES		
	STKXRO	)132GDQ	2	LE.	V З ОРТІ	ON2 WITH I	FEL		LI	LDT3 HCT				
					E	EMISSION CI	REDI	T INFO	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							ZEV	NMOG C	REDIT FOR DOI	ર	OPTIONAL EXH. STD FOR WORK TRUCKS		
		N				N				N N				
					NMOG	AND FLEET	AVE	RAGE		TION				
NMOG RAF					O/NMHC ATIO	NMOG+NO PC+LDT (i (g			) LDT	+NOX FLEET S (3751 LVW-8500 R) + MDPV (g/m	_	NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1	L.10		*	0	.030			0.030		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-016-0503 dated November 20, 2023.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 3/st day of May 2024.

Rolin U. Lang

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

## EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/I	i+NOx mi)	C (g/I	-		Ox mi)		CHO g/mi)	()	PM g/mi)	
			CERT	STD	CERT	STD	CERT	CERT STD		STD	CERT	STD	
FTP@50K	*		*	*	*	*	*	*	*	*	*	*	
FTP@UL	GASOLINE- LEV3 E10		0.034	0.050	0.4	1.7	*	*	*	4	0.002	0.003	
50°F @4K		SOLINE- V3 E10	0.055	0.100	1.1	1.7	*	*	*	16			
					F		NN	IOG+N	Ox (g/mi)		CO (g/mi)		
				FUEL TYP	E		CE	RT	STD	CER	т	STD	
HWFET @ 50				*			*	*					
HWFET @ U			GASO	LINE-LEV	3 E10		0.0	002	0.050				
20°F @ 50K		COLD	CO E10 R	EGULAR G	ASOLINE	(TIER3)				1.0	5	12.5	

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			361	P C/			133101	1 STANDA	ARDS P		CERTIFIC		VELO					
						l	JS06				SC03		C	OMPOSI	ΤE			
	FUEL TY	PE			)G+N g/mi)		CO (g/mi)	Pl (mg/			DG+NOx g/mi)	CO (g/mi)	NMOG+NO (g/mi)	)x CC (g/n	-	PM (mg/mi)		
@ 4K	*	* CERT			*		*				*	*						
•			STD	*			*			*		*						
	@ UL GASOLINE- LEV3 E10		CERT		*		*	2	2		*	*	0.030	0.	3	*		
@ UL			STD	*			* 6		;	*		*	0.050	4.3	2	*		
			BIN										0.070					
	WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																	
WHOLE VEHICLE EVAPORATIVE TESTING																		
	EVAPORATIVE FAMILY		FUEL TYP		UEL TYPE				g/test) @ UL		2DHS (g/test)		@ UL	F	RL (g/mi) @		UL	
					STD	FEL			CER	Т	STD	FEL	CE	RT	;	STD		
STKXR0132GDQ		-	ASOLINE EV3 E1		0.21	L5 0	. 500	0.500	*		0.500	0.500	0.	0.00 0.05				
(	ORVR / FUI	EL O	NLY / C	ANIS	TER	BLEED	EVAP	ORATIVE	EMISS	SION	STANDA	RDS AND	CERTIFICA	TION LE	VE	LS		
									FUI	EL C	NLY EVA	P & CANIS	TER BLEE	D				
EVAPORATIVI FAMILY		C	ORVR (g	RVR (g/gallon) @ UL			~ =			HS RIG TEST g/test) @ UL			tig test () @ UL					
		FU	EL TYPE	CE	RT	STD			CER	RL	STD	CERT	STD			STD		
STKX	R0132GDQ		SOLINE- ER3 E10	0.	. 02	0.20		OLINE- 73 E10	*		*	*	*	0.007		0.020		



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
STKXR0132GDQ	STKXR0132GDQ-001	*	0.02						

\*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR.0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2025 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
MAZDA	MAZDA CX-70 4WD	LDT3	3.3	SA8	STKXR0132GDQ	1	F
MAZDA	MAZDA CX-90 4WD	LDT4	3.3	SA8	STKXR0132GDQ	1	F