

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	OUP IN	IFOR	MATION					
MODE		EST GROUP		VEHIC	LE CLASS(E	S)	FUEL CATEGORY				FUEL TYPE		
202	025 SMBXD02.0HD3 MDV5						DEDICATED SINGLE FUEL VEHICLE				DIESEL		
USEFUL LIFE (miles) VEHICLE EMISSION							ATE	GORY	INTERIM / IN	TERM	ERMEDIATE IN-USE STD		
EXH/ORVR EVAP FTP						SFTP			FTP		SFTP		
1	50000	*	LEV3	SULEV230 SULEV230 SULEV230 SULEV230 SULEV230 (LA92), SC03, FTP TEST CYCLE			435 UC , SC03,	*		*			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS	EN	ENGINE DISPLACEMENT (L)		
1 1	DFI, TC(2), CAC, OC, SCRC+DPF+SCRC, SCRC, 1 FFH, HP-EGR, HP-EGRC, LP-EGR, LP-EGRC, RDQS, PMS, NOXS(3)							FULL	*				
*	*							ARTIAL	* 2.0		2.0		
*			*				PAR	TIAL WITH	ALL MODELS				
		E	VAPC	ORATIVE &	REFUELING	i (EVA	P/OR	VR) FAMILY	INFORMATION				
EVA	AP / ORV	R FAMILY	EVA	PORATIVE	E STD CATE	GORY	C EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
	*				*		*				*		
					EMISSION C	REDIT	INFO	ORMATION	·				
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						PZEV NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS			
	N N						N			N			
				NMOG	AND FLEE	Γ AVE	RAGI	E INFORMA	ΓΙΟΝ	•			
NMOG CH4 FTP RAF RAF RAF RATIO FTP RATIO HCHO/NMHC RATIO NMOG+NOX FL LDT (3751 LVW-8 RATIO + MDPV (g						VW-85	500 G	600 GVW) MDV (8501-10000 GVWR) MDV			MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	*		*		*	* *				*		
Soo th		mont for Voh	iclo M	Indole Eve	porativo Ea	mily	Engir		mont Emission	Con	trol Systems Phase-		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have three (3) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of twenty five dollars (\$25) per vehicle for the third deficiency in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2025 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$47,363 per violation per vehicle pursuant to HSC Section 43154.

BE IT FURTHER RESOLVED:

The fuel-fired heater incorporated in the listed vehicle models must not operate at ambient temperature above 40 °F (13 CCR Section 1961.2(a)(13) [Emission Standard for a Fuel-Fired Heater]).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-003-0876 dated May 23, 2024.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 16th day of July 2024.

him Yacoukian for

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

*

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMHC+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HO /mi)	PM (g/mi)		
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CE	RT	STD
FTP@50K		*	*	*	*	*	*	*	*	*	*		*
FTP@UL	DIE	SEL-EPA	0.053	0.230	0.3	4.2	*	*	*	6	0.0	01	0.010
50°F @4K		*	*	*	*	*	*	*	*	*			
					NN	/HC+NC	CO (g/mi)						
	FUEL TYPE				CE	RT	STD	CER	Т		STD		
HWFET @ 50K		*						*					
HWFET @ UL		DIESEL-EPA						26	0.230				
20°F @ 50K				*					*			*	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

				US06		SC0	3	COMPOSITE					
	FUEL TYPE		NMHC+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMHC+NOx (g/mi)	CO (g/mi)	NMHC+NOx (g/mi)	CO (g/mi)	PM (mg/mi)			
@ 4K	4K *	CERT	*	*		*	*						
•		STD	*	*		*	*						
		CERT	*	*	*	*	*	0.028	0.3	0			
@ UL	DIESEL-EPA	STD	*	*	*	*	*	0.350	4.0	7			
		BIN						*					

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
			W	HOLE V									
EVAPORATIVE FAMILY	FUEL TYPE	E 3	DHS (g	/test) @	UL	2DI		RL (g/mi) @ UL					
		CER	RT S	STD	FEL	CERT	STD	FEL	CE	RT	STD		
*	*	*	*		*	*	*	*	1	*	*		
ORVR / FUI	ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS												
			FUEL ONLY EVAP & CANISTER							R BLEED			
EVAPORATIVE	ORVR (g/	ORVR (g/gallon) @ UL					3DHS RIG TEST		G TEST	BLEED CANISTER			
FAMILY				FUEL TYPE		(g/test) @ UL		(g/test)@UL	TEST (g/	test) @ 4K		
	FUEL TYPE	CERT	STD			CERT	STD	CERT	STD	CERT	STD		
*	* * * *		*		*	*	*	*	*	*			
	EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)												
EVAPORATIVE	FAMILY	LEA	K FAMI	Y CERT						STD			

*

*

*

CALIFORNIA

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: .DT<6000#GVWR;3751-5750#LVW; LDT3: LDT 6001-8500#GVWR;3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR;5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission: AM: automated manual transmission: AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2025 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
MERCEDES-BENZ	SPRINTER 3500 XD	MDV5	2.0	A9	*	1	\$
MERCEDES-BENZ	SPRINTER 3500 XD AWD	MDV5	2.0	А9	*	1	\$
MERCEDES-BENZ	SPRINTER 4500	MDV5	2.0	A9	*	1	\$