

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRC	UP I	NFOR	MATION					
MODE YEA		TEST GROUP		VEHIC	LE CLASS(E	S) FUEL CATEO			ATEGORY		FUEL TYPE		
202	5 S	NSXT02.0RMD		LDT1	DEDICATED SIN VEHICL					GASOLINE			
	VEF	ICLE EMISS	SSION CATEGORY INTERIM / IN				TERMEDIATE IN-USE STD						
EXI	H/ORVR	EVAP		FTP		SFTP FTP				SFTP			
1	150000 150000			LEV3	SULEV30	LEV	3 C	OMPOSITE	*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD STATUS			ENGINE DISPLACEMENT (L)		
1	TWC(2), HO2S, WR-HO2S, EGR, EGRC, DFI							FULL	SOME MODELS				
*	*							PARTIAL	SOME MODELS		2.0		
*		*						RTIAL WITH FINES	*				
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						Y	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
	SNSXR0	099PDA	LE	IV 3 OPTI	ION2 WITH	FEL		LDT1			*		
				I	EMISSION CI	REDI	T INFO	ORMATION	·				
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY										OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N	N			
				NMOG	AND FLEET		RAG	E INFORMA	TION				
NMOG RAF	CH4 RAF					0-375							
*	*	1.10		*	0	.030		0.030			*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>3rd</u> day of June 2024.

Robin U. Lang

Robin U. Lang, Chief *O* Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG+NOx (g/mi)		C (g/i	-		NOx (g/mi)		HCHO (mg/mi)		PM /mi)
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K		*	*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- LEV3 E10		0.012	0.030	0.3	1.0	*	*	*	4	0.0005	0.003
50°F @4K	GASOLINE- LEV3 E10		0.014	0.060	0.1	1.0	*	*	*	8		
				-		NN	NMOG+NOx (g/mi)			CO (g/mi)		
		FUEL TYPE						RT	STD	CER	Т	STD
HWFET @ 50K		*					*		*			
HWFET @ UL		GASOLINE-LEV3 E10						05	0.030			
20°F @ 50K		COLD	CO E10 R	EGULAR G	ASOLINE	(TIER3)				0.6	5	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			5611			122101	I STANDA	ARD2 /	AND	CERTIFIC	ATION LE	VELS			
					US06					SC03		C	OMPOSIT	E	
	FUEL TY	PE	١	NMOG+N (g/mi)		CO (g/mi)	Pl (mg/			DG+NOx g/mi)	CO (g/mi)	NMOG+NO (g/mi)	x CO (g/mi	PM (mg/mi)	
@ 4K	*	СІ	ERT	*		-		,		*	*	,		, (3 ,	
e		s	STD			*				*	*				
		CI	ERT	*		*	3	5		*	*	0.013	1.7	*	
@ UL	GASOLIN LEV3 E1	S	STD	*		*	6	;		*	*	0.050	4.2	*	
		E	BIN									0.040			
		WHOL	E VEH	CLE EV	APORA	TIVE E	MISSION	STAN	DAR	DS AND C	ERTIFICA	TION LEVE	LS		
					W	HOLE \	/EHICLE	EVAPO	ORAT	IVE TEST	ING				
	ORATIVE AMILY	FUE	EL TYPE	= 3	DHS (g	/test) @	DUL		2DH	IS (g/test)	@ UL	F	RL (g/mi) ((g/mi) @ UL	
				CEF	RT S	STD	FEL	CER	R	STD	FEL	CE	RT	STD	
SNSXI	ROO99PDA		OLINE- V3 E10	0 1	58 0	. 300	0.300	0.18	88	0.300	0.30	0.0	000	0.05	
C	ORVR / FUI	EL ONI	LY / CA	NISTER	BLEED) EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIFICA	TION LE	/ELS	
								FU	EL C	NLY EVA	P & CANIS	TER BLEE	D		
	ORATIVE AMILY	OR	ORVR (g/gallor		llon) @ UL		-		HS RIG TEST g/test) @ UL			RIG TEST t) @ UL			
		FUEL	. TYPE	CERT	STD]		CE	RT	STD	CERT	STD	CERT	STD	
SNSXE	ROO99PDA		LINE- 3 E10	0.13	0.20		OLINE- 73 E10	*		*	*	*	0.008	0.020	



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
SNSXR0099PDA	SNSXR0099PDA-001	*	0.02						

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2025 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
NISSAN	KICKS	LDT1	2.0	CV1	SNSXR0099PDA	1	P
NISSAN	KICKS AWD	LDT1	2.0	CV1	SNSXR0099PDA	1	F