

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GF	ROUP IN	NFOI	RMATION						
MODE YEAF	- T	EST GROUP		VEHICLE CLASS(ES)			FUEL	FUEL CATEGORY			FUEL TYPE			
2025	SK	MXT01.6P2T		1.022					PLUG-IN HYBRID ELECTRIC VEHICLE			GASOLINE		
	USEFUL LIFE (miles) VEHICLE EMISSION CATEGORY INTERIM / INTERMEDIATE IN-							MEDIATE IN-USE STD						
EX⊦	I/ORVR	RVR EVAP FTP SFTP FTP						SFTP						
15	60000	150000		LEV3	SULEV30	LEV	3 0	COMPOSITE	2	*		*		
SPE	CIAL FE	ATURES & EXH SYS	IAUST TEMS	EMISSI	ON CONTR	OL		OBD	ST	ATUS	ENGINE DISPLACEMENT (L)			
1	DFI, WR-HO2S, HO2S, WU-TWC, TWC, TC, CAC, EGR, EGRC							FULL	FULL ALL MODELS					
*	*							PARTIAL		*	1.6			
*	*							RTIAL WIT FINES	н	*				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVA	P / ORV	R FAMILY	EVAP	ORATIVE	E STD CAT	EGORY	(			SION STD CLASS	S	PECIAL FEATURES		
5	SKMXR0106P2G LEV 3 OPTION2							LDT2				HCT		
		·			EMISSION	CREDIT	Γ INF	ORMATIO	N	·				
ALLOWANCE FOR TEST GROUP AVE. CRED TZEV EXTENDED W					IT FOR NON-PZE			V ZERO-	ZERO-		OR OPTIONAL EXH. STD FOR WORK TRUCKS			
ALL MODELS N							N			N		N		
			•	NMOG	AND FLE	ET AVE	RAG		IAT	ION				
NMOG RAF				(0-375										
*	*	1.10		*		0.030		0.030 *						

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>16th</u> day of April 2024.

Jolin U. Lang

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

#### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)		
			CERT	STD	CERT	STD	CERT	STD	CE	RL	STD	CEF	RT	STD
FTP@50K		*	*	*	*	*	*	*	*		*	*		*
FTP@UL		SOLINE- R3 E10	0.013	0.030	0.1	1.0	*	*	*		4	0.0	01	0.003
50°F @4K		SOLINE- R3 E10	0.014	0.060	0.1	1.0	*	*	*		8			
					E		NN	NMOG+NOx (g/mi)				CO (g/mi)		
	FUEL TYPE					CE	RT	STD		CER	Т		STD	
HWFET @ 50K		*							*					
HWFET @ UL			0.0	07	0.03	0								
20°F @ 50K		COLD	CO E10 R	EGULAR G	ASOLINE	(TIER3)					0.3	;	1	L2.5

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			351		ΠΑU		2210IN	STANDA	ARD3		CERTIFIC	ATION LE	VELS			
											SC03		COMPOSITE			
	FUEL TYPE			NMO	G+NC	Эх	СО	PI	N	NMC	OG+NOx	СО	NMOG+NC	)x C	0	PM
				(g	/mi)		(g/mi)	(mg	/mi)	(	g/mi)	(g/mi)	(g/mi)	(g/	mi)	(mg/mi)
@ 4K	@4K *		CERT	*			*			*		*				
-			STD	*			*			*		*				
			CERT		*		* 1		-	*		*	0.012	0	.1	*
@ UL	UL GASOLINE- TIER3 E10		SID		*		*	e	6		*	*	0.050	4	. 2	*
			BIN										0.030			
	WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS															
						WH	IOLE V	EHICLE	EVAP	ORA	TIVE TEST	ING				
	EVAPORATIVE FAMILY		FUEL TYPE		PE 3DHS (g		(g/test) @ UL			2DHS (g/test) @ UL			F	RL (g/m	(g/mi) @ UL	
				(	CERT STD		TD	FEL	CERT		STD	FEL	CE	RT	RT STD	
SKMXF	SKMXR0106P2G		ASOLINE LEV3 E1(		0.25	80.	400	*	0.1	97	0.400	*	0.	00	0.05	
C	DRVR / FUE	EL C	ONLY / C	ANIST	FER E	BLEED	EVAPO	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIFICA	TION L	EVE	LS
								FUEL ONLY EVAP & CANISTER BLEED								
	ORATIVE	(	ORVR (g/gallon) @ UL			UL			_	3DHS RIG TEST (g/test) @ UL		_	lig test ) @ UL		EED CANISTER ST (g/test) @ 4k	
		FU	EL TYPE	CE	RT	STD			CE	RT	STD	CERT	STD	CER	Г	STD
SKMXF	R0106P2G		SOLINE- ER3 E10	0.0	09	0.20		*	*	•	*	*	*	*		*

CALIFORNIA

KIA CORPORATION

Executive Order: A-314-0464 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
SKMXR0106P2G	SKMXR0106P2G-NQP	0.00	0.02						

\*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2025 MODEL YEAR: VEHICLE MODELS INFORMATION

MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD			
1	KIA	SPORTAGE PLUG- IN HYBRID	LDT2	1.6	AMS6	SKMXR0106P2G	1	F			
ELECTRIC RANGE AND ZEV ALLOWANCE INFORMATION											

MODEL	PHEV TYPE	UDDS AER	UDDS EAER	US06 AER	HIGHW	ZEV	
NUMBER		(MILES)	(MILES)	(MILES)	ES) AER EAER		ALLOWANCE
1	TZEV	50.4	50.3	*	44.8	44.1	0.80