

# NISSAN MOTOR COMPANY, LTD.

Executive Order: A-015-0969-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	TEST GROUP INFORMATION													
MODE YEAR	- 1 т	EST GROUP		VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY		FUEL TYPE			
2025	sn	NSXT03.5AWA		LDT4				DEDICATED SINGLE FUEL VEHICLE			GASOLINE			
	USEFUL	LIFE (miles)		VEH	IICLE EMISS	ION C	CATEGORY INTERIM / INTERMEDIATE IN-USE S							
EXH	I/ORVR	EVAP			FTP		SF	TP	FTP		SFTP			
15	0000	150000	)	LEV3	ULEV50	LEV	3 CO	MPOSITE	*		*			
SPE	CIAL FE	ATURES & EX	HAUS STEMS		ON CONTRO	L		OBD S	TATUS	EN	IGINE DISPLACEMENT (L)			
1	2TWC (	2), 2HO2S, 2	2WR-H	02S, DF1	, CAC, 2TO	2		FULL	ALL MODELS					
*			*				Р	ARTIAL	*		3.5			
*	* *							TIAL WITH FINES	*					
		E/	/APO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMILY	/ INFORMATIO	N				
EVA	P / ORV	R FAMILY	EVA	PORATIVE	STD CATE	GORY	DRY EVAP EMISSION STD SPECIAL FEATURE CLASS			PECIAL FEATURES				
5	SNSXR01	76PFA	LE	V 3 OPTI	ON2 WITH I	H FEL LDT4			*					
				ı	EMISSION C	REDIT	INFO	RMATION						
	EDIT FO	X FLEET AVE. OR EXTENDED RRANTY			REDIT FOR NO ZERO-EVAP	ON-P	ZEV	NMOG C	REDIT FOR DO	<b>D</b>	OPTIONAL EXH. STD FOR WORK TRUCKS			
		N			N				N		N			
				NMOG	AND FLEET	AVE	RAGE	INFORMA	TION					
NMOG RAF	NMOG CH4 RAF NMOG/NMHC RATIO HCHO/NMHC RATIO NMOG+NOX FL PC+LDT (0-37 (g/mi)			0-375		V) LDT	+NOX FLEET S (3751 LVW-8500 R) + MDPV (g/m	)	NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)					
*	*	1.10		*	0	.030			0.030		*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



NISSAN MOTOR COMPANY, LTD.

Executive Order: A-015-0969-1

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

#### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-015-0969 dated March 7, 2024.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this \_25th \_ day of July 2024.

fin Jacoulian for Robin U. Lang, Chief

Emissions Certification and Compliance Division



# **ATTACHMENT**

### **EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS**

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°I	F)
---	----

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

		NMOG+NOx (g/mi)				NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*	*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- LEV3 E10	0.022	0.050	0.1	1.7	*	*	*	4	0.0004	0.003
50°F @4K	GASOLINE- LEV3 E10	0.066	0.100	0.2	1.7	*	*	*	16		

	FUEL TYPE	NMOG+N	Ox (g/mi)	CO (g/mi)		
	FUELTIFE	CERT	STD	CERT	STD	
HWFET @ 50K	*	*	*			
HWFET @ UL	GASOLINE-LEV3 E10	0.003	0.050			
20°F @ 50K	COLD CO E10 REGULAR GASOLINE (TIER3)			0.7	12.5	

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

				US06		SC03	3	COMPOSITE		
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	*		*	*			
		STD	*	*		*	*			
		CERT	*	*	2	*	*	0.024	0.5	*
@ UL	GASOLINE- LEV3 E10	STD	*	*	6	*	*	0.050	4.2	*
		BIN						0.080		

#### WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EVAPORATIVE FAMILY		FUEL TYPE		WHOLE \						
			3DHS (g/test) @ UL			2DI	HS (g/test) (	RL (g/mi) @ UL		
			CERT	STD	FEL	CERT	STD	FEL	CERT	STD
	SNSXR0176PFA	GASOLINE- LEV3 E10 PREM	0.246	0.500	0.500	0.280	0.500	0.500	0.000	0.05

#### ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

				FUEL ONLY EVAP & CANISTER BLEED								
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K			
	<b>FUEL TYPE</b>	CERT	STD		CERT	STD	CERT	STD	CERT	STD		
SNSXR0176PFA	GASOLINE- TIER3 E10 PREM	0.12	0.20	GASOLINE- LEV3 E10 PREM	*	*	*	*	0.012	0.020		



NISSAN MOTOR COMPANY, LTD.

Executive Order: A-015-0969-1

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)							
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD				
SNSXR0176PFA	SNSXR0176PFA-001	*	0.02				

\*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV; medium-duty vehicle; MDV4; MDV 8501-10000#GVWR; MDV5; MDV 10001-14000#GVWR; MDPV; mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIŔ/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2025 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
INFINITI	QX80 2WD	LDT4	3.5	SA9	SNSXR0176PFA	1	F
INFINITI	QX80 4WD	LDT4	3.5	SA9	SNSXR0176PFA	1	F
NISSAN	ARMADA 2WD	LDT4	3.5	SA9	SNSXR0176PFA	1	F
NISSAN	ARMADA 4WD	LDT4	3.5	SA9	SNSXR0176PFA	1	F
NISSAN	ARMADA 4WD PRO4X	LDT4	3.5	SA9	SNSXR0176PFA	1	F