Pursuant to the authority vested in the Air Resources Board by Health and Safety Code Sections 43013, 43018, 43101, 43102 and 43104; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following new spark-ignition marine engine and emission control systems (ECS) produced by the manufacturer are certified as described below. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	FUEL TYPE DISPLACEMENT (cc)		LEVEL OF CLEANLINESS		
2017	HM9XM04.5CAT	Gasoline	4500	Super Ultra Low Emissi ("Four Stars")		
EQUIPMENT APPLICATION Sterndrive		ECS & SPE	ENGINE TYPE			
		Heated O Dual Three-way On-Board Diagno Low Perme	tiport Fuel Injection, xygen Sensor, Catalytic Converter, ostics-Marine System, eation Fuel Hose	4-Stroke		
ENGINE MODELS (rated power in kilowatts, kW)		See Attac	hment			

BE IT ORDERED AND RESOLVED: That the listed engines are certified to a hydrocarbon plus oxides of nitrogen (HC+NOx) family emission limit (FEL) and carbon monoxide (CO) direct standard in accordance with a plan submitted by the manufacturer to, and approved by, the Executive Officer for compliance with the exhaust emission standards on a corporate average basis pursuant to Title 13, California Code of Regulations, (13 CCR) Section 2442(b). The HC+NOx FEL and the CO standard shall be the applicable emission standards for this engine family for determining compliance of any engine within this engine family pursuant to 13 CCR Sections 2444.1 (in-use compliance). The standards and certification emission levels in grams per kilowatt-hour (g/kW-hr) for this engine family are as follows. Engines in this engine family shall discharge no crankcase emissions into the ambient atmosphere in conformance with 13 CCR Section 2442(b).

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)		
STANDARD	5.0	75.0		
FAMILY EMISSION LEVEL	4.5	*		
CERTIFICATION LEVEL	2.7	45.6		

Compliance with the emission standards on a corporate average basis shall be determined pursuant to 13 CCR Section 2442(b) based on the sales-weighted average of all engines produced for sale in California that are included in the approved corporate average compliance plan for the model-year.

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Sections 2443.1, 2443.2 and 2443.3 (emission control, consumer, and environmental labels), Section 2444.2 (onboard engine malfunction detection system), and Sections 2445.1 and 2445.2 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this _____ day of December 2016.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

Model Year: 201	7	Page:3
Manufacturer Name:	Mercury Marine	Issued: _10/19/2016_
Engine Family:	HM9XM04.5CAT	Revised
SI MARINE ENGINE	SUPPLEMENT INFORMATION	F.O. #: U-W-001-045

S11. MODEL SUMMARY (Use asterisk to identify worst-case engine model used for certification testing)

S12	S13	Sales Codes (Check all appropriate codes)			S15	S16	S17	S18	S19
Engine Model	Engin e Code				Eng. Disp. (cc)	Rated Power (kW)	Rated Speed (RPM)	Peak Torque (N-m)	Peak Torque Speed
		Cal if.	49 State	50 State					(RPM)
4.5L 250Hp Alpha DTM ECT (g2)				X	4500	184	5200	407	3751
4.5L 250Hp Bravo DTM ECT (g2)				X	4500	184	5200	407	3751
4.5L 250Hp Bravo DTS ECT (g2)				X	4500	184	5200	407	3751
4.5L 200Hp Alpha DTM ECT* (g2)				X	4500	150	4800	363	3500
4.5L 200Hp Bravo DTM ECT (g2)				Х	4500	150	4800	363	3500
4.5L 200Hp Bravo DTS ECT (g2)				Х	4500	150	4800	363	3500