## MERCURY MARINE

**EXECUTIVE ORDER U-W-001-0503** New Spark-Ignition Marine Engines

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code Sections 43013, 43018, 43101, 43102 and 43104; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following new spark-ignition marine engine and emission control systems (ECS) produced by the manufacturer are certified as described below. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	FUEL TYPE	DISPLACEMENT (cc)	LEVEL OF CLEANLINESS		
2019	KM9XM03.02GB	Gasoline	2980	Ultra Low Emission ("Three Stars")		
EQUIPMENT APPLICATION		ECS & SPECIAL FEATURES		ENGINE TYPE		
Outboard		Multiport	Fuel Injection	4-Stroke		
ENGINE MODELS (rated power in kilowatts, kW)  See Attachment						

BE IT ORDERED AND RESOLVED: That the listed engines are certified to a hydrocarbon plus oxides of nitrogen (HC+NOx) family emission limit (FEL) and a carbon monoxide (CO) direct standard in accordance with a plan submitted by the manufacturer to, and approved by, the Executive Officer for accordance with a pian submitted by the manufacturer to, and approved by, the Executive Officer for compliance with the exhaust emission standards on a corporate average basis pursuant to Title 13, California Code of Regulations, (13 CCR) Section 2442(a). The HC+NOx FEL and the CO standard shall be the applicable emission standards for this engine family for determining compliance of any engine within this engine family pursuant to 13 CCR Sections 2444.1 (in-use compliance) and 2446 (audit testing). The standards and certification emission levels in grams per kilowatt-hour (g/kW-hr) for this engine family are as follows. Engines in this engine family shall have closed crankcases in conformance with Part I, Section 18(h) of the "California Exhaust Emission Standards and Test Procedures for 2001 Model-Year and Later Spark-Ignition Marine Engines."

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)		
STANDARD	*	300.0		
FAMILY EMISSION LEVEL	15.00	*		
CERTIFICATION LEVEL	13.79	136.5		

Compliance with the emission standards on a corporate average basis shall be determined pursuant to 13 CCR Section 2442(a) based on the sales-weighted average power of all engines produced for sale in California that are included in the approved corporate average compliance plan for the model-year.

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Sections 2443.1, 2443.2 and 2443.3 (emission control, consumer, and environmental labels), and Sections 2445.1 and 2445.2 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter pursuant to 13 CCR Sections 2442(a)(2)(B) and 2446.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this day of December 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

RC-01 Z-07-Z019
ATTREAMENT

	,	MACAMENT
Model Year:2019	Page:3	Plor 1
Manufacturer Name:Mercury Marine	Issued:12/26/2018	_ / /
Engine Family: KM9XM03.02GB	Revised:01/24/2019	
SI MADINE ENCINE SUPPLEMENT INFORMATION	F O # 11-W-001-0503	

S10. MODEL SUMMARY (Use asterisk to identify worst-case engine model used for certification testing)

S11 Model Designation	S12 Engine Code	S13 Sales Codes (Check all appropriate codes)			S15 Rated Power	S16 Rated Speed	S17 Peak Torque	S18 Peak Torque	
		Calif. Only	49 State	50- State	(cc)	(kW)	(RPM)	(N-m)	Speed (RPM)
*1150F13HD				X	3000	120	5400	244	3000
1150F23HD				X	3000	120	5400	244	3000
1150F24HD				X	3000	120	5400	244	3000
7150F23ZD				X	3000	120	5400	244	3000
7150F13ZD				X	3000	120	5400	244	3000
7150F24ZD				X	3000	120	5400	244	3000
1151F171D				Х	3000	105	5250	218	4250
1151F271D				X	3000	105	5250	218	4250
1151F281D				X	3000	105	5250	218	4250
1152F131D				Х	3000	120	5500	244	3000
1152F231D				X	3000	120	5500	244	3000
1135F13HD				Х	3000	105	5250	218	4250
1135F23HD				Х	3000	105	5250	218	4250
1135F24HD				Х	3000	105	5250	218	4250
1150F13ED				X	3000	120	5400	244	3000
1150F23ED				X	3000	120	5400	244	3000
1150F24ED				X	3000	120	5400	244	3000
1135F13ED				X	3000	105	5250	218	4250
1135F23ED				X	3000	105	5250	218	4250
1135F24ED				X	3000	105	5250	218.	4250