Pursuant to the authority vested in California Air Resources Board by Health and Safety Code Sections 43013. 43018, 43101, 43102 and 43104; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012:

IT IS ORDERED AND RESOLVED: That the following new spark-ignition marine engine and emission control systems (ECS) produced by the manufacturer are certified as described below. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	FUEL TYPE DISPLACEMENT (cc)		LEVEL OF CLEANLINESS		
2019	KM9XM08.2AS2	Gasoline 8200		Super Ultra Low Emission ("Four Stars")		
EQUIPME	NT APPLICATION	ECS & SPEC	CIAL FEATURES	ENGINE TYPE		
Inboard & Sterndrive		Heated O Dual Three-way	tiport Fuel Injection, xygen Sensor, Catalytic Converter, ostics-Marine System,	4-Stroke		
ENGINE MODELS (rated power in kilowatts, kW)						

BE IT ORDERED AND RESOLVED: That the listed engines are certified to a hydrocarbon plus oxides of nitrogen (HC+NOx) family emission limit (FEL) and carbon monoxide (CO) direct standard in accordance with a plan submitted by the manufacturer to, and approved by, the Executive Officer for compliance with the exhaust emission standards on a corporate average basis pursuant to Title 13, California Code of Regulations, (13 CCR) Section 2442(b). The HC+NOx FEL and the CO standard shall be the applicable emission standards for this engine family for determining compliance of any engine within this engine family pursuant to 13 CCR Sections 2444.1 (in-use compliance). This engine family shall comply with the evaporative requirements of 13 CCR Section 2442(b). The standards and certification emission levels in grams per kilowatt-hour (g/kW-hr) for this engine family are as follows. Engines in this engine family shall discharge no crankcase emissions into the ambient atmosphere in conformance with 13 CCR Section 2442(b).

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)		
STANDARD	5.0	75.0		
FAMILY EMISSION LEVEL	2.0	*		
CERTIFICATION LEVEL	1.2	54.1		

Compliance with the emission standards on a corporate average basis shall be determined pursuant to 13 CCR Section 2442(b) based on the sales-weighted average of all engines produced for sale in California that are included in the approved corporate average compliance plan for the model-year.

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Sections 2443.1, 2443.2 and 2443.3 (emission control, consumer, and environmental labels), Section 2444.2 (on-board engine malfunction detection system), and Sections 2445.1 and 2445.2 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

day of January 2019.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

ATTACHMENT. PLOFI

Model Year: ____2019____ Manufacturer Name: ____ Mercury Marine_ Engine Family: ____ KM9XM08.2AS2____ SI MARINE ENGINE SUPPLEMENTAL INFORMATION.

Page: 3 Issued: 10/05/2018 Revised: E.O.#: 1-00-001-0508

S11. MODEL SUMMARY (Use asterisk to identify worst-case engine model used for certification testing)

S12 Model Designation	S13 Engine Code	S14 Sales Codes (Check all appropriate codes)		S15 Eng. Disp. (cc)	S16 Rated Power (kW)	S17 Rated Speed (RPM)	S18 Peak Torque (N-m)	S19 Peak Torque Speed (RPM)	
		CA. Only	49 State	50- State					
8.2 MAG H.O. ECT mech				X	8200	313	5000	669	3500
8.2 MAG H.O. ECT DTS				Х	8200	316	5000	674	4000
* 8.2 H.O. ECT (inboard)				Х	8200	313	4800	665	4000
8.2 MAG ECT mech (5000RPM)				Х	8200	280	5000	627	3250
8.2 ECT (inboard) 8.2 MAG ECT DTS (5000RPM)				X X	8200 8200	276 276	4800 5000	666 666	3500 3500