YANCHENG JIANGDONG GASOLINE ENGINE MANUFACTURING CO., LTD

EXECUTIVE ORDER U-U-129-0019-2 New Off-Road Small Spark-Ignition Equipment

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

			1			
MANUFACTURER		ENGINE FAMILY (E.O. NUMBER)		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)		
NCHENG JIANGDONG GASOLINE IGINE MANUFACTURING CO., LTD 8YJGS.		/C (U-U-129-0018-1)	196	Gasoline		
ertified	EQUIPMEN	IT DESCRIPTION				
VAPORATIVE FAMILY	FUEL TANK SIZE (liters)	EQUIPMENT APPLICATION				
СМ	3.6, 15	Compressor, Pump, Pressure Washer, Generator Set, Snow Blower, Leaf Blower/Vacuum, Tiller				
NTROL SYSTEMS (ECS)	EQUIPMENT MODEL					
anister/Metal	JF200, JF200N					
1	NUFACTURING CO., LTD ortified VAPORATIVE FAMILY CM NTROL SYSTEMS (ECS)	NUFACTURING CO., LTD RYJGS.1961 EQUIPMEN VAPORATIVE FAMILY CM 3.6, 15 NTROL SYSTEMS (ECS)	NUFACTURING CO., LTD SYJGS.1961YC (U-U-129-0018-1) FUTIFIED FUND TO STREET TO STREE	NUFACTURING CO., LTD 8YJGS.1961YC (U-U-129-0018-1) EQUIPMENT DESCRIPTION VAPORATIVE FAMILY CM 3.6, 15 Compressor, Pump, Pressur Snow Blower, Leaf Blown Research Company		

A. ECS TYPE (Verking Control Type/Tank Barrier Type): 1. <u>Venting Control Type and Code</u>:- Canister=C Sealed Tank=S Other=O 2. <u>Tank Barrier Type and Code</u>:- Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. <u>EVAPORATIVE FAMILY 2-Letter CODE</u> (Venting Control Codes = C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). <u>Note</u>: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

DESIGN BASED									
FUEL HOSE PERMEATION (grams ROG/m²/day)		FUEL TANK PERMEATION (grams ROG/m²/day)		CARBON CANISTER BUTANE WORKING CAPACITY (grams HC/liter)					
STANDARD	OR EXCUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER				
15	C-U-05-012, G-05-017 Q-08-005	2.5	•	1.0, 1.4	C-U-06-003, C-U-06-007 C-U-07-008, C-U-07-009				

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

This Executive Order hereby supersedes Executive Order U-U-129-0019-1 dated March 27, 2008.

Executed at El Monte, California on this day of October 2008.

Annette Hebert, Chief

Mobile Source Operations Division