ECI FUEL SYSTEMS

EXECUTIVE ORDER U-U-140-0006 New Off-Road Small Spark-Ignition Equipment

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE DI	ESCRIPTION				
	MANUFACTURER	ENGINE FAMIL	Y (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas) Gasoline		
GE	NERAC POWER SYSTEMS	8GNXS.2161G	C (U-U-027-0170)	216			
TBC = To	Be Certified	EQUIPMENT	DESCRIPTION	'			
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)					
2008	СМ	See Attachments	Generator Set and Refueling Pump				
EMISSION	N CONTROL SYSTEMS (ECS)		EQUIPM	ENT MODEL			
Car	bon Canister/Metal Tank	See Attachments					
A. ECS TYPI	E (Venting Control Type/Tank Barrier Ty	e): 1. Venting Control Type :	and Code:- Canister=C S	Sealed Tank=S O	Mher≂O 2. Tank Barrier Type and Code		
Metal≈M Tr	eated HDPE or PE=P Co-extruded=C S	Selar=L Nylon=N Acetal=A Of	her=O B. EVAPORATIVE	FAMILY 2-Lette	r CODE (Venting Control Codes =C, S, of Do not use abbreviations for ECS types		

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable	PERFORMANCE BASED (grams HC/day)					
STANDARD	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	CERTIFICATION LEVEL			
1.20+0.056*tank vol. (liters)	N/A	N/A	2.7			

BE IT FURTHER RESOLVED: That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.

BE IT FURTHER RESOLVED: That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model and it's for use in the averaging and banking program. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1(e).

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

	1 /	1
Executed at El Monte, California on this	<u> </u>	_ day of April 2008

Annette Hebert, Chief

Mobile Source Operations Division

AttActMでして 配 しゃもこ Small Off-Road Evaporative Certification Database Form (Supplementary Information)

MODEL SUMMARY

1 5	Control Executiv e Order	1 ,,	. 10		. <u>.</u>		
S14. Carbon Canister or Other	Q-07-016	Q-07-016	Q-07-017	Q-07-016	Q-07-016	Q-07-016	
S13. Fuel Line	Order	C-U-07-017 C-U-06-011 C-U-06-010 Q-08-013	C-U-07-017 C-U-06-011 C-U-06-010 Q-08-013	C-U-07-017 C-U-06-011 C-U-06-010 Q-08-013	C-U-07-017 C-U-06-011 C-U-06-010 Q-08-013	C-U-07-017 C-U-06-011 C-U-06-010 Q-08-013	C-U-07-017 C-U-06-011 C-U-06-010 Q-08-013
S12. Fuel Tank Exec	utive Orde r	Exem pt Metal	Exem pt Metal	Exem pt Metal	Exem pt Metal	Exem pt Metal	Exem pt Metal
S11.	Lying 1 September 1	8GNXS.2161GC	8GNXS.2161GC	8GNXS.2161GC	8GNXS.2161GC	8GNXS.2161GC	8GNXS.2161GC
S10. Fuel Line Inside	Diamet er (mm)	6.35	6.35	6.35	6.35	6.35	6.35
S9. Nominal Fuel	Length ⁽ ¹⁾ (mm)	10058.4	10058.4	10058.4	10058.4	10058.4	10058.4
S8. Fuel	Туре	Multi- Layer	Multi- Layer	Multi- Layer	Multi- Layer	Multi- Layer	Multi- Layer
S7. Fuel Tank Intern	Surfac e Area (m²)	1.348	1.316	2.430	1.744	2.282	2.200
S6. Fuel Tank	(Liters	64.33	68.11	137.98	91.36	124.91	127.41
S5. Fuel System	(FI or CARB)	CARB	CARB	CARB	CARB	CARB	CARB
S4. Engi	(I or	П	II	П	11	п	ιП
odes all iate)	Stat e	×	×	×	×	×	×
S3. Sales Codes (check all appropriate)	\$ 9 \$ • # # •						
S2. Engine or	AL17GN47	ELC18GN47	ELC36GN47	FLW20GN47	FLW30BGN47	FLW30AGN47	
S1. Worst Case	(Cirec None)						

よった
~
كن
ALKIZYEDII

	Q-07-016	Q-07-016	Q-07-016	Q-07-016	9-07-016	Q-07-016	0-07-016	Q-07-017	Q-07-016	Q-07-016
	C-U-07-017 C-U-06-011 C-U-06-010 Q-08-013	C-U-07-017 C-U-06-011 C-U-06-010								
	Exempt Metal	Exempt Metal								
	8GNXS.2161GC	8GNXS,2161GC	8GNXS.2161GC	8GNXS.2161GC						
)	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35
) (10058.4	10058,4	10058.4	10058.4	10058.4	10058.4	10058.4	10058.4	10058.4	10058.4
	Multi- Layer	Multi- Layer								
- () ()	1.583	2.023	2.067	2.567	1.477	1.918	1.991	2.592	2.125	1.63
	77.71	66.83	129.73	127.676	63.89	118.71	121.13	161.48	117.92	76.63
	CARB	CARB								
	11	11	П	п	п	п	П	п	П	ш
	×	×	×	×	×	×	×	×	×	×
	FLW20GN47	FR18GN47	FR34GN47	TH30GN47	TH18 GN47	WW30SGN47	WW30GN47	WW40GN47	FRIN30GN47	FRIN18GN47
								×		

(Bold)= Indicates worst case across chart