California Environmental Protection Agency		EXECUTIVE ORDER U-U-118-0068
California Environmental Protection Agency AIR RESOURCES BOARD	SHANDONG HUASHENG ZHONGTIAN	New Off-Road Small Spark-Ignition
	MACHINERY GROUP CO., LTD	Equipment

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION		
MANUFACTURER SHANDONG HUASHENG ZHONGTIAN MACHINERY GROUP CO., LTD		ENGINE FAN	ENGINE FAMILY (E.O. NUMBER) BSHSS.1631GA (U-U-118-0062)		FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas) Gasoline
		BSHSS.163			
	Attachment Be Certified	EQUIPMEN		·····	
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	EQUIPMENT APPLICATION		
2011	CM2	3.6, 15.0	Compressor, Pump, Generator Set, Snowblower, Pressure Washer, Leaf Blower/Vacuum		
EMISSION CONTROL SYSTEMS (ECS)		EQUIPMENT MODEL			
Canister / Metal		168F			
	E (Venting Control Type/Tank Barrier Ty eated HDPE or PE=P_Co-extruded≖C_S				

Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes =C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). Note: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

DESIGN BASED									
FUEL HOSE PERMEATION (grams ROG/m <sup>2</sup> /day)		FUEL TANK PERMEATION (grams ROG/m <sup>2</sup> /day)		CARBON CANISTER BUTANE WORKING CAPACITY (grams HC/liter)					
STANDARD	CERTIFICATION LEVEL OR EXCUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER				
15	C-U-05-012, G-05-018 Q-08-004	2.5	*	1.0, 1.4	C-U-06-003, C-U-06-008, C-U-07-008, C-U-07-009 Q-07-020, Q-07-021				

**BE IT FURTHER RESOLVED:** That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this 2774

day of December 2010. FOR AGM

Ments Annette Hebert, Chief Mobile Source Operations Division