

TRANSFER FLOW INC.

EXECUTIVE ORDER U-U-123-0008 New Off-Road Small Spark-Ignition Equipment

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION							
	MANUFACTURER	ENGINE FAM	IILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas) Gasoline					
GENE	RAC POWER SYSTEMS, INC.	AGNXS.21610	GC (U-U-027-0195-1)	216						
CUM	MINS POWER GENERATION		AN5XS.1971GG (U-U-008-0191) BN5XS.1971GG (U-U-008-0204)							
TBC = To B	e Certified	EQUIPMEN	IT DESCRIPTION							
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	. E	PPLICATION						
2011	CM100.111AA	See Attachment	Generator Set with Optional Refueling Pump Kit							
EMISSION	CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL								
	Canister/Metal	See Attachment								
L ECS TYPE	(Venting Control Type/Tank Barrier Ty	pe): 1. <u>Venting</u> Control Ty	pe and Code:- Canister=C	Sealed Tank=S (Other=O 2, Tank Barrier Type and Cod					

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

(Tank Barrier Codes = M, P, C, L, N, A, O). Note: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types

*=not applicable	PERFORMANCE BASED (grams HC/day)								
STANDARD	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL						
1.20 + 0.056*Tank Vol. (L)	•	= (STANDARD) - (EFELD)	2.2						

BE IT FURTHER RESOLVED: That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.

BE IT FURTHER RESOLVED: That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1.

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this _

<u>/7</u> day of February 2011.

Annette Hebert, Chief
Mobile Source Operations Division

AGNXS.2161GC

AGNXS.2161GC

U-U-123-0008

TANK

METAL

TANK

METAL

TANK

G-05-016

C-U-06-030

G-05-016

C-U-06-030

G-05-016

O-07-015

O-07-015

Attachment

84.1

63.1

CARB

CARB

75.7

56.8

4.0 CGKW06

4.0CGKW20R

4.0CGKW15R

X

X

Small Off-Road Evaporative Certification Database Form (Supplementary Information)

GENERAC EQUIPMENT **MODEL SUMMARY** S14. S11. S12. S13. S10. S6. S8. S9. <u>S4</u>. S5. **S**3. S2. S1. Fuel Line Carbon **Exhaust Family** Fuel Fuel Fuel Fuel Tank Fuel Fuel Nom. Engine Sales Codes (check Worst Engine or Canister Tank EO Line Vol. Tank Line Fuel Class System all appropriate) Case Equipment or Other EO Inside (I or II) (FI or (Liters) Intern Type Line (Check Model Venting Diamet CARB) al Length One) 50-49-CAControl (mm) er (mm) Max. Surfa Sta Stat Only EO Nom. ce te . е Area (m²)METAL C-U-06-030 **MULTI** O-07-015 4.0CGKW20 X AGNXS.2161GC 1.500 21133 7.9 to 38.1 84.1 75.7 CARB G-05-016 TANK LAYER C-U-06-030 **METAL** MULTI O-07-015 AGNXS.2161GC 21133 7.9 to 38.1 56.8 1.272 CARB 63.1 G-05-016 4.0CGKW15 TANK LAYER Х **METAL** C-U-06-030 **MULTI** O-07-015 AGNXS.2161GC 21133 7.9 to 38.1 33.7 30.2 0.547 X CARB G-05-016 4.0CGKW08 TANK LAYER C-U-06-030 **METAL MULTI** O-07-015 21133 7.9 to 38.1 AGNXS.2161GC 25.2 CARB 22.7 0.611

1.500

1.272

LAYER

MULTI

LAYER

MULTI

LAYER

21133

21133

7.9 to 38.1

7.9 to 38.1

Attachment 2 of 2

Small Off-Road Evaporative Certification Database Form (Supplementary Information) ONAN EQUIPMENT

MODEL SUMMARY

S1.	S2.	S3.		S4.	S5.	S	6.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case (Check One)	Engine or Equipment Model	Codes (control of the control of the		Engine Class (I or II)	Fuel System (FI or CARB)	ystem Vol. FI or (Liters)		Fuel Tank Internal Surface Area (m²)	Fuel Line Type	Nominal Fuel Line Length ⁽¹⁾ (mm)	Fuel Line Inside Diameter (mm)	Exhaust Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister or Other Venting Control Executive Order
	2.8CKW20 2.8CKW20 2.8CKW15 2.8CKW15)	X X X	I	CARB CARB CARB	84.1 84.1 63.1 63.1	75.7 75.7 56.8 56.8	1.500 1.500 1.272 1.272	MULTI LAYER	21133 21133 21133 21133	7.9 to 38.1 7.9 to 38.1 7.9 to 38.1 7.9 to 38.1	BN5XS.1971GG AN5XS.1971GG BN5XS.1971GG AN5XS.1971GG	METAL TANK	C-U-06-030 G-05-016	Q-07-015 Q-07-015 Q-07-015 Q-07-015
	2.8CKW08 2.8CKW08 2.8CKW06 2.8CKW06		X X X X	I I I	CARB CARB CARB CARB	33.7 33.7 25.2 25.2	30.2 30.2 22.7 22.7	0.547 0.547 0.611 0.611	MULTI LAYER	21133 21133 21133 2133	7.9 to 38.1 7.9 to 38.1 7.9 to 38.1 7.9 to 38.1	BN5XS.1971GG AN5XS.1971GG BN5XS.1971GG AN5XS.1971GG	METAL TANK	C-U-06-030 G-05-016	Q-07-015 Q-07-015 Q-07-015 Q-07-015
х	2.8CKW20R 2.8CKW20R 2.8CKW20R 2.8CKW15R 2.8CKW15R		X X X X	I I I I	CARB CARB CARB CARB	84.I 84.I 63.1 63.1	75.7 75.7 56.8 56.8	1.500 1.500 1.272 1.272	MULTI LAYER	21133 21133 21133 21133	7.9 to 38.1 7.9 to 38.1 7.9 to 38.1 7.9 to 38.1	BN5XS.1971GG AN5XS.1971GG BN5XS.1971GG AN5XS.1971GG	METAL TANK	C-U-06-030 G-05-016	Q-07-015 Q-07-015 Q-07-015 Q-07-015

⁽¹⁾ The nominal fuel line lengths can be grouped into increment of ± 3 inches (76 mm)