

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003:

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION		
	MANUFACTURER	ENGINE FAM	IILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)
GENE	RAC POWER SYSTEMS, INC	BGNXS.2161	IGC (U-U-027-0205)	216	Gasoline
TBC = To B	e Certified	EQUIPMEN	IT DESCRIPTION	1	1
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	E	QUIPMENT A	PPLICATION
2011	CM14	See Attachments	Generato	or Set and Refe	ueling/Transfer Pump
EMISSION	CONTROL SYSTEMS (ECS)		ENGINE and/or	EQUIPMENT I	MODEL
Cart	oon Canister, Metal Tank		See A	ttachments	
Metal=M Tn	eated HDPE or PE=P Co-extruded=C !	Selar=L Nylon=N Acetal=A	Other=O B. EVAPORATIVI	FAMILY 2-Lette	Other=O 2. <u>Tank Barrier Type and Code</u> or CODE (Venting Control Codes =C, S, o Do not use abbreviations for ECS types

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable		PERFORMANCE BASED (grams HC/day)	
STANDARD	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL
1.20 + 0.056*Tank Vol. (L)	5.50	= (STANDARD) - (EFELD)	2.6

BE IT FURTHER RESOLVED: That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.

BE IT FURTHER RESOLVED: That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1.

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this day of January 2011

_ uay or January 2011

Annette Hebert, Chief

Mobile Source Operations Division

Small Off-Road Evaporative Certification Database Form (Supplementary Information)

MODEL SUMMARY

							1		\	One)	Worst Case (Check	S1.	
MP18GN47	MP30GN47	FR17GN47	FR34GN47	FW30BGN47	FW30AGN47	FLW20GN47	FW18BGN47	FW18AGN47	ELC36GN47		Engine or Equipment Model	S2.	
			`							CA Only	Sales all a		
					,		· 1			49- State	Sales Codes (check all appropriate)	S3.	
`	•	•	`	`	`	`	`	٠,	`	50- State	check ate)		
П	11	П	II	II	П	П	II	11	=	Ę	Engine Class (I or	S4.	
CARB	CARB	CARB	CARB	CARB	CARB	CARB	CARB	CARB	CARB	CARD)	Fuel System (FI or	S5.	
63.89	127.79	66.85	129.76	127.42	124.94	83.4	73.5	77.74	138.02	Total	Fuel T (L)		
60.49	121.01	57.34	122.95	120.75	118.37	79	69.66	73.58	130.74	Nominal	Fuel Tank Vol. (Liters)	S6.	
1.47	2.56	1.36	2.06	2.20	2.28	1.59	1.49	1.37	2.43	Area (m²)	Fuel Tank Internal	S7.	
Multi- layer	Multi- layer	Multi- layer	Multi- layer	Multi- layer	Multi- layer	Multi- layer	Multi- layer	Multi- layer	Multi- layer		Fuel Line Type	S8.	
10058.4	10058.4	10058.4	10058.4	10058.4	10058.4	10058.4	10058.4	10058.4	10058.4	(mm)	Nominal Fuel Line	S9.	
6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	(mm)	Fuel Line Inside	S10.	
BGNXS.2161GC	BGNXS.2161GC	BGNXS.2161GC	BGNXS.2161GC	BGNXS.2161GC	BGNXS.2161GC	BGNXS.2161GC	BGNXS.2161GC	BGNXS.2161GC	BGNXS.2161GC		Exhaust Family	S11.	11-1
Exempt Metal	Exempt Metal	Exempt Metal	Exempt Metal	Exempt Metal	Exempt Metal	Exempt Metal	Exempt Metal	Exempt Metal	Exempt Metal	Class	Fuel Tank Executive	\$12.	-040-1
Q-09-019 Q-09-022 G-05-018	Q-09-019 Q-09-022 G-05-018	Q-09-019 Q-09-022 G-05-018	Q-09-019 Q-09-022 G-05-018	Q-09-019 Q-09-022 G-05-018	Q-09-019 Q-09-022 G-05-018	Q-09-019 Q-09-022 G-05-018	Q-09-019 Q-09-022 G-05-018	Q-09-019 Q-09-022 G-05-018	Q-09-019 Q-09-022 G-05-018		Fuel Line Executive Order	S13.	2200
Q-0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0	Q-Q-Q-	၀ ၀ ၀ ၀ ၀ ၀	0 0	ဝုဝ ဝုဝ	0 0	Q Q Q Q Q Q Q Q Q	0 0 0 0 0 0	Q-Q-Q-Q-Q-Q-Q-Q-Q-Q-Q-Q-Q-Q-Q-Q-Q-Q-Q-	Q-0′	Coi Exec	Can Can or (κż	

~	0-0,	0-0,	Q-0, Q-0,	0.0	6,6,6	Q-6.	650	0 0 0	0-0.	0-0	0 0 0 0 0 0	553	000	555	Q-01
الد	Q-09-019 Q-09-022 G-05-018	Q-09-019 Q-09-022 G-05-018	Q-09-019 Q-09-022 G-05-018												
2-12-12	Exempt Metal	Exempt Metal	Exempt Metal												
	BGNXS.2161GC	BGNXS.2161GC	BGNXS.2161GC												
3	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35
2 of	10058.4	10058.4	10058.4	10058.4	10058.4	10058.4	10058.4	10058.4	10058.4	10058.4	10058.4	10058.4	10058.4	10058.4	10058.4
£ 00	Multi- layer	Multi- layer	Multi- layer												
AMACHAEN	1.99	1.91	2.59	2.12	1.57	1.73	1.21	1.21	2.43	1.96	1.52	1.29	.83	96	.55
£ ,	114.77	112.46	153.03	108.98	72.56.	91.15	81.93	73.91	149.31	104.28	71.91	70.58	43.14	43.69	25.20
	121.13	118.72	161.52	115.03	76.69	96.23	86.5	78.01	157.57	109.77	75.70	74.30	45.42	45.99	26.53
	CARB	CARB	CARB												
	п	11	ıı ı	п	=	E	Ш	ı	II	=		II	п	11	Ħ
	`	`	`	`	`	`	`	`	`	`	`	`	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	`	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
												-			
									-				47	47	
	WW30GN47	WW30SGN47	WW40GN47	IND30GN47	IND18GN47	VIN25GN47	NM22GN47	NM20GN47	MR40GN47	KS30GN47	FR20GN47	SF20GN47	MM12AGN47	MM12BGN47	ON7GN47

ON14GN47	`	E	CARB	55.72	52.93	1/4/E/7 /	Multi	52.93 .94 Multi- 10058.4	6.35	BGNXS.2161GC	Exempt Metal	Exempt 0-09-019 0-07	2.5
	. ,	=	CARB	76.95	73.10	1.21	Multi-	10058.4	6.35	BGNXS.2161GC	Exempt Metal	G-05-018 Q-09-019 Q-09-022 G-05-018	0-07
	`	11	CARB	38.98	37.03	0.70	Multi- layer	10058.4	6.35	BGNXS.2161GC	Exempt Metal	Q-09-019 Q-09-022 G-05-018	0-07
	`	п	CARB	57.34	54.47	26.	Multi- layer	10058.4	6.35	BGNXS.2161GC	Exempt Metal	Q-09-019 Q-09-022 G-05-018	0-07
ON20bGN47	`	111	CARB	75.7	16.17	1.20	Multi- layer	10058.4	6.35	BGNXS.2161GC	Exempt Metal	Q-09-019 Q-09-022 G-05-018	Q-07