

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION						
	MANUFACTURER	ENGINE FAN	TILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleugas)				
F	HONDA MOTOR CO., LTD.	CBHNXS.270	02AB (U-U-001-0573) 02AC (U-U-001-0574) 02SA (U-U-001-0575)	270 270 270	Gasoline				
TBC = To B	e Certified	EQUIPMEN	NT DESCRIPTION						
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE EQUIPMENT APPLICATION							
2012	CMHNX21A	4.2, 4.4, 5.3	erator Set, Snowblower, -Cart, Other OEM Product						
EMISSION	N CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL							
	Canister, Metal	See Attachment							

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

(Tank Barrier Codes = M, P, C, L, N, A, O). Note: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.

*=not applicable	PERFORMANCE BASED (grams HC/day)							
STANDARD	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL					
1.20 + 0.056*Tank Vol. (L)	0.31	= (STANDARD) (EFELD)	0.96					

BE IT FURTHER RESOLVED: That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.

**BE IT FURTHER RESOLVED:** That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model and it's for use in the averaging and banking program. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1(e).

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this

day of December 2011

Annette Hebert, Chief

Mobile Source Operations Division

Issued: 08/10/11

Revised:

Executive Order:

EQUIPMENT FUELED BY ON-ROAD VEHICLE/MARINE VESSEL FUEL TANK (Section 2766(c)) Small Off-Road Evaporative Certification Summary Sheet

## Small Off-Road Evaporative Certification Database Form (Supplementary Information)

## MODEL SUMMARY

	MODEL SUMMARY														
S1.	S2.	S3.		S4.	S5.	S6.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.	
Worst	Engine or	Sales Codes (check			Engine	Fuel	Fuel	Fuel	Fuel	Nominal	Fuel		Fuel	Fuel Line	Carbon
Case	Equipment	all appropriate)		Class	System	Tank	Tank	Line	Fuel	Line	Exhaust	Tank	Executive	Canister	
(Check	Model			(I or II)	(Flor	Vol.	Internal	Туре	Line	Inside	Family	Executive	Order	or Other	
One)				` ′	CARB)	(Liters)	Surface Area	"	Length (mm)	Diameter (mm)	,	Order		Venting Control	
,															
		CA	49-	50-				(m <sup>2</sup> )		(	( , , ,				Executive
		Only	State	State				()							Order
х	B2AH02A1-C (FRC800) *1	х			H	CARB	4.2	*2	FKM	222	4.5	BHNXS.2701AA	N/A	N/A	N/A
	CSDJ01A3-C (GX270HS)			Х	11	CARB	5.3	*2	FKM	210	4.5	CHNXS.2702SA	N/A	N/A	N/A
	C2JH01A1-C C2JH02A1-C C2JH04A1-C C2JH06A1-C (GX240)			Х	II	CARB	5.3	*2	FKM	210	4.5	CHNXS.2702AC	N/A	N/A	N/A
	C2JH07A1-C (FRC800K1)			×	II	CARB	4.4	*2	FKM	210	4.5	CHNXS.2702AC	N/A	N/A	N/A
	C2KH01A2-C C2KH02A2-C C2KH02A2RC C2KH03A2-C C2KH04A2-C C2KH09A2-C C2KH10A2-C (GX270)		·	Х	11	CARB	5.3	*2	FKM	210	4.5	CHNXS.2702AB	N/A	N/A	N/A

Note \*1: Worst case configuration which was carried-over from previous model year

Note \*2: According to CARB Small Off-Road Engine Evaporative Emission Control System Certification Procedure CP-902, these models are tested by Evaporative Emission Test Procedure TP-902 (Diurnal Evaporative Emission Test).