## CHONGQING ZONGSHEN GENERAL POWER MACHINE CO., LTD

EXECUTIVE ORDER U-U-082-0074 New Off-Road Small Spark-Ignition Equipment

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION						
	MANUFACTURER	ENGINE FAI	MILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)				
	IGQING ZONGSHEN GENERAL OWER MACHINE CO., LTD.	CCZHS.208 CCZHS.208 CCZHS.208	CCZHS.2081HC (U-U-082-0071) 179, 208 CCZHS.2081HU (U-U-082-0062) 179, <b>208</b> CCZHS.2081HA (U-U-082-0073) 179, 208 Ga CCZHS.2081H1 (U-U-082-0072) 208 CCZHS.1231HC (U-U-082-0070) 123						
	Attachment Be Certified	EQUIPME	NT DESCRIPTION		<b>)</b> .				
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	EQUIPMENT APPLICATION						
2012	CMH1	1.3, 1.45, 12	Compressor, Pump, Stump Beater, Generator Set, Non-Backpack Blower, Pressure Washer, Tiller, Edger, Brushcutter, Other Industrial Equipment						
EMISSIO	N CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL							
	Canister/Metal	See Attachment							
Metal≃M T	E (Venting Control Type/Tank Barrier Tyl reated HDPE or PE=P Co-extruded=C S or Codes = M, P, C, L, N, A, O). Note: Al	Selar=L Nylon=N Acetal=/	A Other=O B. EVAPORATIVE	E FAMILY 2-Letter CO	DE (Venting Control Codes =C, S, C				

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable		DESIGN BASED					
	OSE PERMEATION ams ROG/m²/day)		ANK PERMEATION ams ROG/m²/day)	CARBON CANISTER BUTANE WORKING CAPACITY (grams HC/liter)			
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER		
15	G-05-018, Q-08-005, Q-08-017, C-U-05-013	*	*	1.0, 1.4	C-U-06-003, C-U-06-007 C-U-07-008, C-U-07-009, Q-09-005		

**BE IT FURTHER RESOLVED:** That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this

auy or coptember 2011

Annette Hebert, Chief

Mobile Source Operations Division



重庆宗申通用动力机械有限公司 CHONGQING ZONGSHEN GENERAL POWER MACHINE CO., LTD. Zongshen Industry Zone, Banan District, Chongqing 400054, China

## Small Off-Road Evaporative Certification Database Form (Supplementary Information)

## MODEL SUMMARY

S1.	S2.		S3.		S4.	S5.	S6.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst	Engine or	Sales Codes (check all		Engine	Fuel	Fuel	Fuel Tank	Fuel Line	Nominal	Fuel Line	Exhaust Family	Fuel Tank	Fuel Line	Carbon Canister	
Case	Equipment	appropriate)		Class (I	System	Tank	Internal	Type	Fuel Line	Inside		Executive	Executive Order	or Other Venting	
(Check	Model			or II)	(F1 or	Vol.	Surface		Length <sup>(1)</sup>	Diameter		Order		Control	
One)		CA Only	49-State	50-State		CARB)	(Liters)	Area (m <sup>2</sup> )		(mm)	(mm)				Executive Order
X	165F_ 170F_ ZH180_ ZH210_ 170-TU_ 170-VU_ 270-TU_ 270-VU_ 170-LU			х		CARB	1.45	0.12	multilayer	140	6.3	CCZHS.2081HU CCZHS.2081HC CCZHS.2081HA CCZHS.2081H1	N/A	G-05-018 or Q-08-005 or Q-08-017 or C-U-05-013	C-U-06-003 or C-U-07-008 or Q-09-005
	165F_ 170F_ ZH180_ ZH210_			х	ı	CARB	12	0.476	multilayer	126	6.3 or 4.0	CCZHS.2081HU CCZHS.2081HC CCZHS.2081H1	N/A	G-05-018 or Q-08-005 or Q-08-017 or C-U-05-013	C-U-06-007 or C-U-07-009
	161F_ ZH125_			Х	K	CARB	1.3	0.11	multilayer	230	6.3	CCZHS.1231HC	N/A	G-05-018	C-U-06-003 or C-U-07-008 or Q-09-005

<sup>(1)</sup> The nominal fuel line lengths can be grouped into increment of ± 3 inches (76 mm)

