Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012:

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

ENGINE DESCRIPTION											
	MANUFACTURER	ENGINE F (E.O. NUI		ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)						
	Chongqing Rato Power Manufacturing Corporation	See Attach	nment A	See Attachment A	Gasoline						
TBC = To E	TBC = To Be Certified  EQUIPMENT DESCRIPTION										
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)		EQUIPMENT APPLICATION							
2015	CP1V	0.75, 0.95, 1.1, Walk-Behind Lawnmower, Line Trimmer, Pressure Washer, Tiller, Other Industrial Equipment									
EMISSIO	EMISSION CONTROL SYSTEMS (ECS) ENGINE and/or EQUIPMENT MODEL										
	CP	See Attachment B									
A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. Venting Control Type and Code:- Canister=C Sealed Tank=S Other=O 2. Tank Barrier Type and Code:- Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes = C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). Note: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.											

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable	PERFORMANCE BASED (grams HC/day)							
STANDARD	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL					
1.0 (Walk-Behind Mowers), 0.95 + 0.056*Tank Vol. (L) (All Other Models)	*	= (STANDARD) - (EFELD)	0.73					

BE IT FURTHER RESOLVED: That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.

BE IT FURTHER RESOLVED: That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1.

**BE IT FURTHER RESOLVED:** That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

This Executive Order hereby cancels and replaces Executive Order U-U-169-0142 dated December 22, 2014.

Executed at El Monte, California on this \_\_\_\_\_ day of April 2015.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

#### Attachment A

ENGINE DESCRIPTION										
MANUFACTURER	ENGINE FAMILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)							
Chongqing Rato Power Manufacturing Corporation	FCRPS.1131GB (U-U-169-0123) FCRPS.1391GB (U-U-169-0124) FCRPS.1501GB (U-U-169-0125-1) FCRPS.1731GB (U-U-169-0126) FCRPS.1741GD (U-U-169-0128) FCRPS.1891GB (U-U-169-0129-1) FCRPS.2231GB (U-U-169-0132) FCRPS.1501GD (U-U-169-0145)	113 139 150 163, 173 173, 174 174, 189 223 150	Gasoline							

## Attachment B, 1 of 1

### DRAFT

# Small Off-Road Evaporative Certification Database Form (Supplementary Information)

#### **MODEL SUMMARY**

S1.	S2.	\$3.		S4.	S5.	S6.		S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.	
Worst Case (Check One)	Engine or Equipment Model	Sales Codes (check all appropriate)			Engine Class (I or	Fuel System (FI or	Fuel Tank Vol. (Liters)		Fuel Tank Internal Surface	Fuel Line Type	Nominal Fuel Line	Fuel Line Inside Diameter	Exhaust Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister or Other Venting
		CA Only	49- State	50- State	II)	CARB)	Total	Nominal	Area (m²)	Length <sup>(1)</sup> (mm)	(mm)		Order		Control Executive Order	
	EA190, EA175, RV140-III RV170III RV175 RV170-III RV160-III RVM110-III RV150-III RV225 RV150III						1.0	0.95	0.07		118	4				
											196	3				
											293	4.5				
						1.5	1.45	0.09		305	4.5	FCRPS. 1891GB				
						CARB				Multi- layer	122	4	FCRPS. 1391GB FCRPS. 1731GB FCRPS. 1741GD FCRPS. 1131GB FCRPS. 1501GB FCRPS. 2231GB FCRPS. 1501GD	N/A	Q-10-003 Q-08-005 Q-08-017 Q-15-010 Q-15-011	N/A
							0.8	0.75	0.06		216	3				
X				X	I						85	4				
											110	4				
							1.2	1.1	0.085		245	4				
											187	4				
											175	4				
											80	4				
											168	4				
											280	6				
		-							280	4						

<sup>(1)</sup> The nominal fuel line lengths can be grouped into increment of ± 3 inches (76 mm)