EXECUTIVE ORDER U-U-001-0767 New Off-Road Small Spark-Ignition Equipment

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

MANUFACTURER HONDA MOTOR CO., LTD. TBC = To Be Certified MODEL YEAR EVAPORATIVE FAMILY FU 2016 CMHNX27A	GHNXS.270 GHNXS.389 EQUIPMEI	MILY (E.O. NUMBER) 2AB (U-U-001-0743) 2AB (U-U-001-0746) NT DESCRIPTION	ENGINE SIZE (cc) 270 389	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas) Gasoline
TBC = To Be Certified MODEL EVAPORATIVE FAMILY FU	GHNXS.389 EQUIPMENT JEL TANK SIZE	NT DESCRIPTION	389	Gasoline
MODEL EVAPORATIVE FAMILY FU	JEL TANK SIZE			
YEAR EVAPORATIVE FAMILY				
2016 CMHNX27A	UEL TANK SIZE EQUIPMENT APPLICATION			
2010	23.5, 24.0	Generator Set		
EMISSION CONTROL SYSTEMS (ECS) ENGINE and/or EQUIPMENT MODEL			MODEL	
Canister, Metal	G2KH05G1-C (EG4000CL), G2KH06G1-C (EM4000X, EM4000SX), G2MH03G2-C (EG5000CL, EG6500CL), G2MH04G2-C (EM6500SXK2, EM5000SXK3, EB6500X1, EB5000XK3)			

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

(Tank Barrier Codes = M, P, C, L, N, A, O). Note: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.

*=not applicable	PERFORMANCE BASED (grams HC/day)				
STANDARD	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL		
1.20 + 0.056*Tank Vol. (L)	-1.56	= (STANDARD) - (EFELD)	3.47		

BE IT FURTHER RESOLVED: That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.

BE IT FURTHER RESOLVED: That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model and it's for use in the averaging and banking program. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1(e).

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this

_ day of July 2015.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division