California Environmental Protection Agency		EXECUTIVE ORDER U-U-017-0245
Air Resources Board	YAMAHA MOTOR CO., LTD.	New Off-Road Small Spark-Ignition Equipment

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION							
	MANUFACTURER	ENGINE FAM	ILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)					
Y	AMAHA MOTOR CO., LTD.	GYMXS.1711EH (U-U-017-0241) GYMXS.1921EH (U-U-017-0244) 171, 192 Gasoline								
* TBC = To	Be Certified	EQUIPMEN	T DESCRIPTION		· · · · · · · · · · · · · · · · · · ·					
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	EQUIPMENT APPLICATION							
2016	CMYMX13F	4.0	4.0 Compressor, Pump, Stump Beater, Generator, Backpack Blower and Pressure Washer							
EMISSIO	N CONTROL SYSTEMS (ECS)		EQUIPM	ENT MODEL						
Ca	bon Canister/Metal Tank	See Attachments								
Code:- Met	E (Venting Control Type/Tank Barrier Ty al=M Treated HDPE or PE=P Co-extrud Fank Barrier Codes = M, P, C, L, N, A, O)	ed=C Selar=L Nylon=N Ad	cetal=A Other=O B. EVAPO	RATIVE FAMILY	2-Letter CODE (Venting Control Codes					

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable	PERFORMANCE BASED (grams HC/day)									
STANDARD	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL							
0.95 + 0.056*tank vol. (Liter)	*	*	0.5							

BE IT FURTHER RESOLVED: That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.

BE IT FURTHER RESOLVED: That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model and is for use in the averaging and banking program. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1(e).

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this $\underline{\rightarrow \cup}$ day of December 2015.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

ATTACHMENT BISTL Small Off-Road Evaporative Certification Database Form (Supplementary Information)

MODEL SUMMARY

U-u-017-0245

S1.	S2.		S3.		S4.	S5.		S6.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Case Equ	Engine or Equipment Model	Equipment	Sales Codes (check all appropriate)		Engine Class (I or		Fuel Tank Vol. (Liters)		Fuel Tank Internal Surface	k Line nal Type	e Fuel e Line	Fuel Line Inside	Exhaust Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister or Other Venting
Oney		CA Only	49- State	50- State	II)	CARD)	Total	Nominal	Area (m ²)		Length ⁽¹⁾ (mm)	Diameter (mm)		Order		Control Executive Order
*	7DHJ-050			x	I	CARB	4.2	4.0	(Metal Tank	Multi layer	60	5	GYMXS.1921EH	(Mctal Tank)	C-U-05-003 C-U-05-012 C-U-06-017 G-05-018 Q-13-013	
	7DHJ-060			x	I	CARB	4.2	4.0	(Metal Tank	Multi layer	60	5	GYMXS.1921EH	(Metal Tank)	C-U-05-003 C-U-05-012 C-U-06-017 G-05-018 Q-13-013	
	YP20GJ			x	I	CARB	4.2	4.0	(Metal Tank	Multi layer	60	5	GYMXS.1711EH	(Metal Tank)	C-U-05-003 C-U-05-012 C-U-06-017 G-05-018 Q-13-013	
	YP30GJ			x	I	CARB	4.2	4.0	(Metal Tank	Multi layer	60	5	GYMXS.1711EH	(Metal Tank)	C-U-05-003 C-U-05-012 C-U-06-017 G-05-018 Q-13-013	
	7CPK-030			x	I	CARB	4.2	4.0	(Metal Tank	Multi layer	60	5	GYMXS.1711EH	(Metal Tank)	C-U-05-003 C-U-05-012 C-U-06-017 G-05-018 Q-13-013	
	7CN1-080			x	I	CARB	4.2	4.0	(Metal Tank	Multi layer	60	5	GYMXS.1711EH	(Metal Tank)	C-U-05-003 C-U-05-012 C-U-06-017 G-05-018 Q-13-013	
	YP20TX			x	I	CARB	4.2	4.0	(Metal Tank	Multi layer	60	5	GYMXS.1711EH	(Metal Tank)	C-U-05-003 C-U-05-012 C-U-06-017 G-05-018 Q-13-013	

AMACHMENT R 20FZ

:

										1) 2011			u-1	1-017-0	245
7DHJ-070			х	I	CARB	4.2	4.0	(Metal Tank	Multi layer	60	5	GYMXS.1921EH	(Metal Tank)	C-U-05-003 C-U-05-012 C-U-06-017 G-05-018	
7DHJ-080			x	I	CARB	4.2	4.0	(Metal Tank	Multi layer	60	5	GYMXS.1921EH	(Metal Tank)	C-U-05-003 C-U-05-012 C-U-06-017 G-05-018	
7CN1-090		-	х	I	CARB	4.2	4.0	(Metal Tank	Multi layer	60	5	GYMXS.1711EH	(Metal Tank)	C-U-05-003 C-U-05-012 C-U-06-017 G-05-018 Q-13-013	
	7DHJ-080	7DHJ-080	7DHJ-080	7DHJ-080 X	7DHJ-080 X I	7DHJ-080 X I CARB	7DHJ-080 X I CARB 4.2	7DHJ-070 X I CARB 4.2 4.0 7DHJ-080 X I CARB 4.2 4.0	7DHJ-070XICARB4.24.0(Metal Tank7DHJ-080XICARB4.24.0(Metal Tank7CNI 090XICARB4.24.0(Metal Tank	7DHJ-070 X I CARB 4.2 4.0 (Metal Tank Multi layer 7DHJ-080 X I CARB 4.2 4.0 (Metal Tank Multi layer 7DHJ-080 X I CARB 4.2 4.0 (Metal Tank Multi layer 7CNI 090 X I CARB 4.2 4.0 (Metal Tank Multi layer	7DHJ-070 X I CARB 4.2 4.0 (Metal Tank Multi layer 60 7DHJ-080 X I CARB 4.2 4.0 (Metal Tank Multi layer 60 7DHJ-080 X I CARB 4.2 4.0 (Metal Tank Multi layer 60 7CNL090 X I CARB 4.2 4.0 (Metal Multi layer 60	7DHJ-070 X I CARB 4.2 4.0 Tank layer 60 5 7DHJ-080 X I CARB 4.2 4.0 (Metal Tank Multi layer 60 5	7DHJ-070 X I CARB 4.2 4.0 (Metal Tank Multi layer 60 5 GYMXS.1921EH 7DHJ-080 X I CARB 4.2 4.0 (Metal Tank Multi layer 60 5 GYMXS.1921EH 7DHJ-080 X I CARB 4.2 4.0 (Metal Tank Multi layer 60 5 GYMXS.1921EH	7DHJ-070 X I CARB 4.2 4.0 (Metal Tank Multi layer 60 5 GYMXS.1921EH (Metal Tank) 7DHJ-080 X I CARB 4.2 4.0 (Metal Tank) Multi layer 60 5 GYMXS.1921EH (Metal Tank) 7DHJ-080 X I CARB 4.2 4.0 (Metal Tank) 60 5 GYMXS.1921EH (Metal Tank) 7DHJ-080 X I CARB 4.2 4.0 (Metal Tank) 60 5 GYMXS.1921EH (Metal Tank)	7DHJ-070 X I CARB 4.2 4.0 $(Metal Tank)$ Multi layer 60 5 GYMXS.1921EH $(Metal Tank)$ $(Metal $

(1) The nominal fuel line lengths can be grouped into increment of \pm 3 inches (76 mm)