Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION							
	MANUFACTURER	ENGINE FAI	MILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)					
	GQING ZONGSHEN GENERAL WER MACHINE CO., LTD.	GCZHS.196	GCZHS.1591V1 (U-U-082-0185) 141,159 GCZHS.1961V1 (U-U-082-0192) 196 Gaso GCZHS.1951V1 (U-U-082-0193) 195							
TBC = To Be Certified EQUIPMENT DESCRIPTION										
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE EQUIPMENT APPLICATION								
2016	CPMX2	1.0 Compressor, Pump, Stump Beater, Non-Backpack Blower, Pressure Washer, Tiller, Edger, Brushcutter, Other Industrial Equipmen								
EMISSION	CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL								
	Canister/HDPE		See Attachment							
A. ECS TYPE	E (Venting Control Type/Tank Barrier Ty	be): 1. Venting Control Ty	vpe and Code:- Canister=C	Sealed Tank=S C	ther=O 2. Tank Barrier Type and Code:-					

A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. <u>Venting Control Type and Code</u>:- Canister=C Sealed Tank=S Other=O 2. <u>Tank Barrier Type and Code</u>:-Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes = C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). <u>Note</u>: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable	PERFORMANCE BASED (grams HC/day)						
STANDARD	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL				
0.95 + 0.056*Tank Vol. (L)		= (STANDARD) – (EFELD)	0.82				

**BE IT FURTHER RESOLVED:** That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.

**BE IT FURTHER RESOLVED:** That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1.

**BE IT FURTHER RESOLVED:** That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte,	California on this	3	day of Nove	ember 2015.
	~	-	71 1	/

t Heli

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

Attachment, 1 of 1



重庆宗申通用动力机械有限公司 CHONGQING ZONGSHEN GENERAL POWER MACHINE CO., LTD. Zongshen Industry Zone, Banan District, Chongqing 400054, China

## Small Off-Road Evaporative Certification Database Form (Supplementary Information)

## MODEL SUMMARY

S1.	S2.	S3.		S4.	S5.		S6.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.	
Worst	J N N		Engine	Fuel	Fuel	Tank Vol.	Fuel Tank	Fuel Line	Nominal	Fuel Line	Exhaust Family	Fuel Tank	Fuel Line	Carbon Canister or		
Case	Equipment	appropriate)		Class	System	(Liters)		Internal	Туре	Fuel Line			Executive	Executive	Other Venting	
(Check	Model	CA Only	10 State	50 State	(I or II)	(Fl or			Surface		Length <sup>(1)</sup>	Diameter		Order	Order	Control Executive
One)		CA Omy	49-5tate	50-State		CARB)	Total	Nominal	Area (m <sup>2</sup> )		(mm)	(mm)				Order
	XP160_ 1X65CU_ 1X65CH_ 1X65LU_ 1X65LH_ 1X65TU_ 1X65TH_ 1X65VU_ 1X65VU_ 1X65VH_ 5X65VU_ 5X65VH_			×	ł	CARB	1.2	1.0	Ċ	Muttilayer	330	6.3	GCZHS.1591V1	N/A	G-05-018 or Q-14-008	N/A
	XP200_ 1X70MT_ 1X70ST_ 1X70TY_ 5X70VU_ 5X70VH_			x	Ċ	CARB	1.2	1.0	0.068	Multilayer	330	6.3	GCZHS.1961V1	N/A	G-05-018 or Q-14-008	N/A
	7P71JU_ 7P71JH_			×	ł	CARB	1.2	1.0	0.068	Multilayer	230	6.3	GCZHS.1951V1	N/A	G-05-018 or Q-14-008	N/A

X: 5P71MU is the worst case model carried over from evap family CP195 (2015 MY).

(1) The postfix "\_" is the designator for future non-emission related revision change.

(2) The nominal fuel line lengths can be grouped into increment of  $\pm$  3 inches (76 mm)