CHONGQING AM PRIDE POWER&MACHINERY CO.,LTD

EXECUTIVE ORDER U-U-164-0061-2 New Off-Road Small Spark-Ignition Equipment

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012:

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION							
	MANUFACTURER	ENGINE FAM	ILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleur gas)					
	CHONGQING AM PRIDE WER&MACHINERY CO.,LTD	FCPPS.09810 FCPPS.22310 GCPPS.2231	GC (U-U-164-0043) GA (U-U-164-0042) GA (U-U-164-0045) GA (U-U-164-0055) GA (U-U-164-0060)	196, 208 98 196, 208, 223 196, 208, 223 98	Gasoline					
	Attachment Be Certified	EQUIPME	NT DESCRIPTION							
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)		EQUIPMENT APPLICATION						
2016	CM2081	3.6, 3.8, 6, 15 Compressor, Pump, Pressure Washer, Generator								
EMISSIO	N CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL								
	Canister/Metal		See Attachment							
Metal=M T	Canister/Metal E (Venting Control Type/Tank Barrier Tylereated HDPE or PE=P Co-extruded=C Str Codes = M, P, C, L, N, A, O). Note: All	Selar=L Nylon=N Acetal=A	/pe and Code:- Canister=C A Other=O B. EVAPORATI	Sealed Tank=S Oth	CODE (Venting Control Codes =C, S,					

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable	DESIGN BASED										
	OSE PERMEATION ams ROG/m²/day)		ANK PERMEATION ams ROG/m²/day)	CARBON CANISTER BUTANE WORKING CAPACITY (grams HC/liter)							
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER						
15	Q-08-005, G-05-018, Q-14-008, Q-12-016A, Q-15-011	1.5	*	1.0, 1.4	C-U-06-003, Q-07-020, C-U-07-008, C-U-06-005, C-U-06-007, C-U-06-007A, C-U-06-008, Q-07-021, C-U-07-009, Q-08-031, Q-08-035, C-U-07-021						

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

This Executive Order hereby supersedes Executive Order U-U-164-0061-1 dated December 31, 2015.

Executed at El Monte, California on this

_ day of April 2016

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

DRAFT

Small Off-Road Evaporative Certification Database Form (Supplementary Information)

MODEL SUMMARY

S1.	S2.		S3.		S4.	S5.	S6.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case (Check	Engine or Equipment Model	Sales Codes (check all appropriate)		Class (I or	Fuel System (FI or	Fuel Tank Vol.	Fuel Tank Internal Surface	Fuel Line Type	Nominal Fuel Line	Fuel Line Inside Diameter	Exhaust Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister or Other Venting	
One)		CA Only	49- State	50- State	II)	CARB)	(Liters)	Area (m²)		Length (mm)	(mm)		Older		Control Executive Order
	AP156F, AP156FD, AP168FB,AP170F, AP170FB SU1500C, AP1500C AP2500C, SU2500C, SUA2500C, SUA4000C, SU4000C, AP4000C, AP4000C, SU4500C,SUA4500C, AP4500C,SUA4500C, AP45250C SU5250C, AP5250C SC3250-1, SC3250-11,SC3500-1, SC3500-11,SC4000-1, SC4000-11,GP3250, AP3250, AG3250 RTPG-4500C SUA5000C SUPW50,SUPW80 APW2700, APW3200 SU5000C,AP5000C, SUA5000EC,SU5000EC, AP5000EC,SU5000EC, AP5000EC,SU500EC, AP5000EC,SU500EC, AP5000EC,SU500EC, AP500DEC,SU500EC, AP500EC,SU50EC, AP5			x	I	CARB	3.6	0.15	Multi- layer	125			N/A		C-U-06-003 or Q-07-020 or C-U-07-008
				X	I	CARB	3.8	0.15	Multi- layer	125			N/A		C-U-06- 005
				CARR	15	0.52	Multi-	105		FCPPS.2081GC	N/A	Q-08-005 or G-05-018	C-U-06-007 or C-U-06-007A or		
				X	1	CARB	13	0.53	layer	180	4.5 or 6.35	or FCPPS.2231GA	17/1		Q-07-021 or C-U-07-009
				X	I	CARB	6	0.31	Multi- layer	125			N/A		Q-08-035 or C-U-07-021 or C-U-06-008 or Q-08-031