Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012:

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION			
	MANUFACTURER	ENGINE FAI	MILY (E.O. NUMBER)	FUEL TYPE (CNG/LNG=compressed/liquefled natural gas LPG=liquefled petroleum gas)		
	GQING ZONGSHEN GENERAL DWER MACHINE CO., LTD.	HCZHS.196	S.1591V2 (TBC) S1V2 (U-U-082-0228) S.1491V1 (TBC) S.1491H1 (TBC)	159, 141 196 132, 149 132, 149	Gasoline	
TBC = To B	e Certified	EQUIPME	NT DESCRIPTION			
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	PPLICATION			
2017	CPXP2	1.3, 1.1, 0.8, 0.75, 1.2	Compressor, Pu Pressure Washer, Tille	imp, Stump Be er, Edger, Brus	ater, Non-Backpack Blower, hcutter, Other Industrial Equipment	
EMISSION	CONTROL SYSTEMS (ECS)		ENGINE and/or	EQUIPMENT I	MODEL	
	Canister/HDPE		See A	Attachment		

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes =C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). Note: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.

*=not applicable	PERFORMANCE BASED (grams HC/day)								
STANDARD	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL						
0.95 + 0.056*Tank Vol. (L)	*	= (STANDARD) - (EFELD)	0.62						

BE IT FURTHER RESOLVED: That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.

BE IT FURTHER RESOLVED: That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1.

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this day of December 2016.

10 grun

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

Attachment, 1 of Z



重庆宗申通用动力机械有限公司 CHONGQING ZONGSHEN GENERAL POWER MACHINE CO., LTD. Zongshen Industry Zone, Banan District, Chongqing 400054, China

Small Off-Road Evaporative Certification Database Form (Supplementary Information)

MODEL SUMMARY

S1. Worst Case	forst Engine or Equipment			S4. Engine Class	S5. Fuel System	tem Fuel Tank Vol. (Liters)		S7. Fuel Tank Internal	S8. Fuel Line Type	Fuel	Inside	S11. Exhaust Family	S12. Fuel Tank Executive		S14. Carbon Canister or Other Venting	
(Check One)	Model	CA Only	49-State	50-State	(I or II)	(FI or CARB)	Total	Nominal	Surface Area (m²)		Line Length ⁽¹⁾ (mm)	Diameter (mm)		Order	Order	Control Executive Order
	XP200_ XP200-01_ XP200-02_ XP200-03_ XP200-04_ XP200-05_ XP200-06_ XP200-08_ XP200-09_ XP200-10_ VP2800_ VP3000_			X	1	CARB	1.4	1.3	0.082	Multilayer	322	6.3	HCZHS.1961V2	N/A	G-05-018 or Q-14-008	N/A
	XP200-07_ XP200-11_			х	ı	CARB	1.3	1.1	0.073	Multilayer	300	6.3	HCZHS.1961V2	N/A	G-05-018 or Q-14-008	N/A
×	XP140_ XP140-01_ XP140-02_ XP140-03_ XP140-04_ XP140-05_			x	ı	CARB	0.9	0.8	0.068	Multilayer	260 or 200	6.3	HCZHS.1591V2	N/A	G-05-018 or Q-14-008	N/A

Attachment, 2 of 2



重庆宗申通用动力机械有限公司 CHONGQING ZONGSHEN GENERAL POWER MACHINE CO., LTD. Zongshen Industry Zone, Banan District, Chongqing 400054, China

XP160_ XP160-01_ XP160-02_ XP160-03_ XP160-04_ XP160-05_ XP160-06_ XP160-07_ GQ7.5/15.5 WP2500_ VP2500_	х	1	CARB	1.4	1.3	0.082	Multilayer	300 or 290	6.3	HCZHS.1591V2	N/A	G-05-018 or Q-14-008	N/A
NP150_ NP130_ 1P65F_ 1P61F_ MINI2000 GQ7.5/15.5 WP2500_ VP2500_	x	L	CARB	0.85	0.75	0.050	Multilayer	75	6.3	HCZHS.1491V1	N/A	G-05-018 or Q-14-008	N/A
NH150_ NH130_ 165F_ 161F_ SG20_	x	ı	CARB	1.25	1.20	0.069	Multilayer	88	6.3 or 4.0	HCZHS.1491H1	N/A	G-05-018 or Q-14-008 or Q-08-005 or C-U-05-013 or Q-10-003	N/A

⁽¹⁾ The nominal fuel line lengths can be grouped into increment of ± 3 inches (76 mm)

⁽²⁾ Postfix "_" is the designator(s) for future non-emission related revision change, may appears as other number or letter.