EXECUTIVE ORDER U-U-099-0077 New Off-Road Small Spark-Ignition Equipment

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

ENGINE DESCRIPTION											
	MANUFACTURER	ENGINE FAI	MILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)						
Kav	wasaki Heavy Industries, LTD.		GKAXS.6032CC (U-U-004-0672) 603 Gasoline GKAXS.7262CB (U-U-004-0661)								
	Kohler Company	GKHXS.725	GKHXS.7252CB (U-U-005-0486) 725,747								
S.A. = See TBC = To E	Attachment Be Certified	EQUIPMENT DESCRIPTION									
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	EQUIPMENT APPLICATION								
2017	CPRSDTR	11.55		Riding N	lower						
EMISSIO	N CONTROL SYSTEMS (ECS)		ENGINE and/or EQUIPMENT MODEL								
	СР		See Attachment								
A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. Venting Control Type and Code:- Canister=C Sealed Tank=S Other=O 2. Tank Barrier Type and Code:- Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes = C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). Note: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.											

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable		DESIGN BASED						
	OSE PERMEATION ams ROG/m²/day)		ANK PERMEATION ams ROG/m²/day)	CARBON CANISTER BUTANE WORKING CAPACITY (grams HC/liter)				
STANDARD	ANDARD CERTIFICATION LEVEL OR EXECUTIVE ORDER		CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	OR EXECUTIVE ORDER			
15	Q-08-013	1.5	C-U-06-014	1.4	Q-09-021			

**BE IT FURTHER RESOLVED:** That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_ day of September 2016.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

ATTACHMENT (page 10F1)

## Small Off-Road Evaporative Certification Database Form (Supplementary Information)

## MODEL SUMMARY

S1.	S2.	S3.		S4.	S5.		S6.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.	
Worst Case (Check One)	Engine or Equipment Model	Sales Codes (check all appropriate)		Engine Class (I or	Fuel System (FI or CARB)	Fuel Tank Vol. (Liters)		Fuel Tank Internal Surface	Fuel Line Type	Nominal Fuel Line Length <sup>(1)</sup>	Fuel Line Inside Diameter	Exhaust Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister or Other Venting	
		CA Only	49- State	50- State	11)	() () () () () () () () () () () () () (	Total	Nominal	Area (m²)		(mm)			01401		Control Executive Order
	931998US			Х	II	CARB	14.9	11.55	0.44	SINGLE LAYER	31	6.35	GKAXS.7262CB	C-U-06-014	Q-08-013	Q-09-021
	932004US			X	II	CARB	14.9	11.55	0.44	SINGLE LAYER	31	6.35	GKAXS.7262CB	C-U-06-014	Q-08-013	Q-09-021
	933408US			Х	П	CARB	14.9	11.55	0.44	SINGLE LAYER	31	6.35	GKAXS.6032CC	C-U-06-014	Q-08-013	Q-09-021
	934505US			Х	11	CARB	14.9	11.55	0.44	SINGLE LAYER	31	6.35	GKHXS.7252GB	C-U-06-014	Q-08-013	Q-09-021
	934513US			Х	II	CARB	14.9	11.53	0,44	SINGLE LAYER	31	6.35	GKHXS.7252GB	C-U-06-014	Q-08-013	Q-09-021
	934539US			Х	II	CARB	14.9	11.55	0.44	SINGLE LAYER	31	6.35	GKHXS.7252GB	C-U-06-014	Q-08-013	Q-09-021
	934547US	~		Х	11	CARB	14,9	11.55	0.44	SINGLE LAYER	31	6.35	GKHXS.7252GB	C-U-06-014	Q-08-013	Q-09-021
	934554US			Х	II	CARB	14.9	11.55	0.44	SINGLE LAYER	31	6.35	GKHXS.7252GB	C-U-06-014	Q-08-013	Q-09-021
	934562US			Х	I1	CARB	14.9	11.55	0.44	SINGLE LAYER	31	6.35	GKHXS.7252GB	C-U-06-014	Q-08-013	Q-09-021
	935767US			Х	11	CARB	14.9	11.55	0.44	SINGLE LAYER	31	6.35	GKHXS.7252GB	C-U-06-014	Q-08-013	Q-09-021

<sup>(1)</sup> The nominal fuel line lengths can be grouped into increment of  $\pm 3$  inches (76 mm)