CHONGQING MAIFENG POWER MACHINERY CO., LTD

EXECUTIVE ORDER U-U-165-0071 New Off-Road Small Spark-Ignition Equipment

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

ENGINE DESCRIPTION											
	MANUFACTURER	ENGINE FAMI	LY (E.O. NUMBER)	ENGINE SIZE	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)						
CHO	ONGQING MAIFENG POWER MACHINERY CO., LTD	HCMGS.2121	GL (U-U-165-0067)	196, 208, 212	Gasoline or LPG or Gasoline-LPG Dual-Fuel						
S.A. = See Attachment TBC = To Be Certified EQUIPMENT DESCRIPTION											
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	EQUIPMENT APPLICATION								
2017	CM212GL	See Attachment	Rump, Generator Set, Tiller								
EMISSIO	N CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL									
	Canister/Metal	See Attachment									
A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. Venting Control Type and Code:- Canister=C Sealed Tank=S Other=O 2. Tank Barrier Type and Code:- Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O 8. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes = C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). Note: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.											

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not	applicable		DESIGN BASED												
		OSE PERMEATION	FUEL T	ANK PERMEATION	CARBON CANISTER BUTANE WORKING CAPACITY (grams HC/liter)										
	(gra	ms ROG/m²/day)	0 00 4	□⊓ 🤟 ∏⊓ARBO											
STA	NDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER									
	15	Q-10-003, Q-08-005, Q-12-016A	1.5	Q-17-009, Q-17-025, Q-17-017	1.0, 1.4	Q-07-020, Q-08-035, Q-07-021, Q-13-005, Q-08-036, Q-11-02 4									

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this ____ day of June 2017.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

Attachment, 1 of 1

Small Off-Road Evaporative Certification Database Form (Supplementary Information)

MODEL SUMMARY

S1.	S2.		S3.		S4.	S5.	S6.		S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case (Check One)	Engine or Equipment Model	CA			Engine Class (I or II)	Fuel System (FI or CARB)	Fuel Tank Vol. (Liters)		Fuel Tank Internal Surface Area	Fuel Line Type	Nominal Fuel Line Line Inside Length ⁽¹⁾ Diameter (mm)	Exhaust Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister or Other Venting Control	
		Only State	State	State			Total	Nominal	(m ²)							Executive Order
	168FB YK650 170F YK700 170FA						1.6	1.45	0.08							Q-07-020
							3.6	3.5	0.14							
						6.5	6.25	0.19					Q-17-009		Q-08-035	
							17	16.7	0.5							Q-07-021
							28	27.6	0.7							Q-13-005 Q-08-036
							1.7	1.6	0.08688							Q-07-020
						3.6	3.5	0.126803	Multi-					Q-10-003	0.00.005	
×				*	II	CARB	6.6	6.5	0.25001	layer	150-500 4.5	4.5	5 HCMGS.2121GL	Q-17-025	Q-08-005 Q-12-016A	Q-08-035
							16.5	16	0.52958							Q-07-021 Q-13-005
							29.5	29	1.13221							Q-08-036
							3.7	3.59	0.151574					Q-17-017		Q-07-020
							6.3	6.16	0.193386							Q-08-035
							15	14.62	0.463512							Q-07-021
							29	28.5	0.693327							Q-13-005 Q-08-036
								31.8	31.49	0.741375						

⁽¹⁾ The nominal fuel line lengths can be grouped into increment of ± 3 inches (76 mm)