

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

ENGINE DESCRIPTION			
MANUFACTURER	ENGINE FAMILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)
KAWASAKI HEAVY INDUSTRIES, LTD.	HKAXS.6032CA (U-U-004-0715) HKAXS.7262CA (U-U-004-0709) HKAXS.7262CB (U-U-004-0708)	603, 726	Gasoline
	HKAXS.7262CC (U-U-004-0707) HKAXS.7262IB (U-U-004-0720)		
BRIGGS & STRATTON CORPORATION	HBSXS.8102VS (U-U-002-0996)	724, 810	
KOHLER COMPANY	HKHXS.7472GB (TBC) HKHXS.7472GD (U-U-005-0531) HKHXS.7472PE (U-U-005-532)	725, 747	
S.A. = See Attachment TBC = To Be Certified			
EQUIPMENT DESCRIPTION			
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	EQUIPMENT APPLICATION
2017	CC	18.64, 28.22, 14.11, 24.87, 26.5	Walk-Behind Lawnmower, Riding Mower, Commercial Turf
EMISSION CONTROL SYSTEMS (ECS)		ENGINE and/or EQUIPMENT MODEL	
Canister/Co-extruded		See Attachment	
A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. <u>Venting Control Type and Code</u> : Canister=C Sealed Tank=S Other=O 2. <u>Tank Barrier Type and Code</u> : Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. <u>EVAPORATIVE FAMILY 2-Letter CODE</u> (Venting Control Codes =C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). Note: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.			

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.


*not applicable		DESIGN BASED			
FUEL HOSE PERMEATION (grams ROG/m ² /day)		FUEL TANK PERMEATION (grams ROG/m ² /day)		CARBON CANISTER BUTANE WORKING CAPACITY (grams HC/liter)	
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER
15	G-05-018	1.5	C-U-07-012, Q-15-003	1.4	Q-08-031

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this 17th day of February 2017.


 Annette Hebert, Chief
 Emissions Compliance, Automotive Regulations and Science Division

**Small Off-Road Evaporative Certification Database Form
(Supplementary Information)**

MODEL SUMMARY

S1. Worst Case (Check One)	S2. Engine or Equipment Model	S3. Sales Codes (check all appropriate)			S4. Engine Class (I or II)	S5. Fuel System (FI or CARB)	S6. Fuel Tank Vol. (Liters)		S7. Fuel Tank Internal Surface Area (m ²)	S8. Fuel Line Type	S9. Nominal Fuel Line Length ⁽¹⁾ (mm)	S10. Fuel Line Inside Diameter (mm)	S11. Exhaust Family	S12. Fuel Tank Executive Order	S13. Fuel Line Executive Order	S14. Carbon Canister or Other Venting Control Executive Order
		CA Only	49-State	50-State			Total	Nominal								
	PS1532KWCA			X	II	CARB	19.27	18.64	0.444	Low Permeation	787 (wet)	6.35	N/A	C-U-07-012	G-05-018	Q-08-031
	PS1536KWCA			X	II	CARB	19.27	18.64	0.444	Low Permeation	787 (wet)	6.35	N/A	C-U-07-012	G-05-018	Q-08-031
	PD1536KwCA			X	II	CARB	19.27	18.64	0.444	Low Permeation	787 (wet)	6.35	N/A	C-U-07-012	G-05-018	Q-08-031
	PD1544KWCA			X	II	CARB	19.27	18.64	0.444	Low Permeation	787 (wet)	6.35	N/A	C-U-07-012	G-05-018	Q-08-031
	ZT90030			X	II	CARB	19.27	18.64	0.444	Low Permeation	787 (wet)	6.35	N/A	C-U-07-012	G-05-018	Q-08-031
	ZT90031			X	II	CARB	19.27	18.64	0.444	Low Permeation	787 (wet)	6.35	N/A	C-U-07-012	G-05-018	Q-08-031
	ZT90032			X	II	CARB	19.27	18.64	0.444	Low Permeation	787 (wet)	6.35	N/A	C-U-07-012	G-05-018	Q-08-031
	MH2244KWCA			X	II	CARB	31.04	28.22	0.764	Low Permeation	1397 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	MH2250KWCA			X	II	CARB	31.04	28.22	0.764	Low Permeation	1397 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	MH2460KWCA			X	II	CARB	31.04	28.22	0.764	Low Permeation	1397 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	MR2250KWCA			X	II	CARB	31.04	28.22	0.764	Low Permeation	1397 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	MR2550KOCA			X	II	CARB	31.04	28.22	0.764	Low Permeation	1092 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031

	MR2460KWCA		X	II	CARB	31.04	28.22	0.764	Low Permeation	1397 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	MR2560KOCA		X	II	CARB	31.04	28.22	0.764	Low Permeation	1092 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	Z22342KOCA		X	II	CARB	15.52	14.11	0.382	Low Permeation	635 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	Z22348KWCA		X	II	CARB	15.52	14.11	0.382	Low Permeation	229 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	Z22348BRCA		X	II	CARB	15.52	14.11	0.382	Low Permeation	635 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	Z22348KOCA		X	II	CARB	15.52	14.11	0.382	Low Permeation	635 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	Z22354KWCA		X	II	CARB	15.52	14.11	0.382	Low Permeation	229 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	Z22354BRCA		X	II	CARB	15.52	14.11	0.382	Low Permeation	635 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	Z22354KOCA		X	II	CARB	15.52	14.11	0.382	Low Permeation	635 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	ST2548KWECA		X	II	CARB	28.01	24.87	0.561	Low Permeation	927 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	ST2554KWECA		X	II	CARB	28.01	24.87	0.561	Low Permeation	927 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	ZT90028		X	II	CARB	28.01	24.87	0.561	Low Permeation	927 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	ZT90029		X	II	CARB	28.01	24.87	0.561	Low Permeation	927 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	099099-Z6KW2248		X	II	CARB	31.8	26.5	1.253	Low Permeation	889 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	099099-Z6KW2454		X	II	CARB	31.8	26.5	1.253	Low Permeation	889 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	099099-Z6KW2460		X	II	CARB	31.8	26.5	1.253	Low Permeation	889 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	099099-Z6KOE2548CA		X	II	CARB	31.8	26.5	1.253	Low Permeation	889 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
	099099-Z6KOE2554CA		X	II	CARB	31.8	26.5	1.253	Low Permeation	889 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031

099099- Z6KOE2560CA			X	II	CARB	31.8	26.5	1.253	Low Permeation	889 (wet)	6.35	N/A	Q-15-003	G-05-018	Q-08-031
------------------------	--	--	---	----	------	------	------	-------	-------------------	--------------	------	-----	----------	----------	----------

(1) The nominal fuel line lengths can be grouped into increment of ± 3 inches (76 mm)