EXECUTIVE ORDER U-U-017-0297 New Off-Road Small Spark-Ignition Equipment

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION								
	MANUFACTURER	ENGINE FAM	MILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)						
Y	AMAHA MOTOR CO., LTD.	JYMXS.171	1EH (U-U-017-0283)	171	Gasoline						
S.A. = See Attachment TBC = To Be Certified EQUIPMENT DESCRIPTION											
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	EQUIPMENT APPLICATION								
2018	CPYMX23A	6	6 Generator								
EMISSIO	N CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL									
Carbon	Canister, Treated HDPE Tank	See Attachment									
Code:- Met	E (Venting Control Type/Tank Barrier Ty al=M Treated HDPE or PE=P Co-extruc Fank Barrier Codes = M, P, C, L, N, A, O	led=C Selar=L Nylon=N /	Acetal=A Other=O B. EVAPO	RATIVE FAMILY	2-Letter CODE (Venting Control Codes						

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable		DESIGN BASED										
	OSE PERMEATION Ims ROG/m²/day)		ANK PERMEATION ams ROG/m²/day)	CARBON CANISTER BUTANE WORKING CAPACITY (grams HC/liter)								
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER							
15	C-U-05-003, C-U-05-012, C-U-06-017, G-05-018, Q-07-018	1.5	C-U-06-023	1.4	C-U-06-008							

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this day of December 2017.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

ATTACHHENT B (04)

Small Off-Road Evaporative Certification Database Form (Supplementary Information)

u-u-017-0297

MODEL SUMMARY

S1.	S2.	S3.		S4.	S5.	S5. S6.		S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.	
Worst Engine or Equipment (Check One)				ate)	Engine Class (I or II)	Fuel System (FI or CARB)	Fuel Tank Vol. (Liters)		Fuel Tank Internal Surface	Fuel Line Type	Nominal Fuel Line Length ⁽¹⁾	Fuel Line Inside Diameter	Exhaust Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister or Other Venting
Olicy		CA Only	49- State	50- State	11)	ii) CARB)	Total	Nominal	Area (m²)		(mm)	(mm)		Oluci		Control Executive Order
*	EF24iSHX			х	ı	CARB	6.12	6	0.239	multilayer	250	5	JYMXS.1711EH	C-U-06- 023	C-U-05-003 C-U-05-012 C-U-06-017 G-05-018 Q-07-018	C-U-06-008
	EF24iSX			x		CARB	6.12	6	0.239	multilayer	250	. 5	JYMXS.1711EH	C-U-06- 023	C-U-05-003 C-U-05-012 C-U-06-017 G-05-018 Q-07-018	C-U-06-008
	EF24iS			х	ı	CARB	6.12	6	0.239	multilayer	250	5	JYMXS.1711EH	C-U-06- 023	C-U-05-003 C-U-05-012 C-U-06-017 G-05-018 Q-07-018	C-U-06-008

The nominal fuel line lengths can be grouped into increment of ± 3 inches (76 mm)