

## CHONGQING ZONGSHEN GENERAL POWER MACHINE CO., LTD.

EXECUTIVE ORDER U-U-082-0319
New Off-Road Small Spark-Ignition
Equipment

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION						
	MANUFACTURER	ENGINE FAM	MILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)				
	GQING ZONGSHEN GENERAL OWER MACHINE CO., LTD.	JCZHS.196	1V1 (U-U-082-0274) 1V1 (U-U-082-0275) 1V1 (U-U-082-0277)	Gasoline					
TBC = To B	e Certified		NT DESCRIPTION						
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	EQUIPMENT APPLICATION						
2018	CNMX1	1.3, 0.75	Walk-Behind Lawnmower, Compressor, Pump, Stump Beater, 1.3, 0.75 Non-Backpack Blower, Pressure Washer, Tiller, Edger, Other Industrial Equipment						
EMISSION	CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL							
	Canister/Nylon	See Attachment							
Metal=M Tr	eated HDPE or PE=P_Co-extruded=C_S	Selar=L Nylon=N Acetal=A	A Other=O B. EVAPORATIVE	FAMILY 2-Lette	ther=O 2. Tank Barrier Type and Code: r CODE (Venting Control Codes =C, S, O); Do not use abbreviations for ECS types.				

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable	PERFORMANCE BASED (grams HC/day)							
STANDARD	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL					
1.0		= (STANDARD) - (EFELD)	0.53					

BE IT FURTHER RESOLVED: That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.

BE IT FURTHER RESOLVED: That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1.

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_ day of March 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

## Atlachment, 1 & 1

## Small Off-Road Evaporative Certification Database Form (Supplementary Information)

## MODEL SUMMARY

S1.	S2.	<u> </u>	<b>S</b> 3.		S4.	S5.	-	S6.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case (Check One)	Engine or Equipment Model	pment all appropriate) Class System (Liters) odel (Fl or CARB)			Fuel Tank Internal Surface	Fuel Line Type	Nominal Fuel Line Length <sup>(1)</sup> (mm)	Fuel Line Inside Diameter (mm)	Exhaust Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister or Other Venting				
		CA Only	49- State	50- State			Total	Nominal	Area (m²)							Control Executive Order
	1X65CU_, 1X65TU_, 1X65LU_, 1X65MU_, 5X65MU_, 6X65MU_, 6X65QU_, 6X65QU_			x	ı	CAŖB	1.4	1.3	0.08	Multilayer	90	6,3	JCZHS.1591V1	N/A	G-05-018 or Q-14-008 or Q-15-010	N/A
	5X70MU_, 6X70MU_, 5X70QU_, 6X70QU_, 7X70JW_, 7X70JU_			x	ı	CARB	1.4	1.3	0.08	Multilayer	110	6.3	JCZHS.1961V1	N/A	G-05-018 or Q-14-008 or Q-15-010	N/A
x	1R61NU_ <sup>(#)</sup> , 1R61RU <sup>_(#)</sup> , 1R65NU <sup>_(#)</sup> , 1R65RU <sup>_(#)</sup>			x	ı	CARB	0.8	0.75	0.05	Multilayer	75	6.3	JCZHS.1491V1	N/A	G-05-018 or Q-14-008 or Q-15-010	N/A

<sup>[#]</sup> Walk-behind application only.

(1) The nominal fuel line lengths can be grouped into increment of ± 3 inches (76 mm)
 (2) Postfix \_ of the model name is the designator(s) for future non-emission related revision change, may appears as other number or letter.