Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION							
	MANUFACTURER	ENGINE FAN	ILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas) Gasoline					
BRIGG	S & STRATTON CORPORATION	HBSXS.6272 HBSXS.305 JBSXS.4792 JBSXS.6272	2HH (U-U-002-0974) HN (U-U-002-0976-1) 2HB (U-U-002-0973) 2HH (U-U-002-1042) 2HN (U-U-002-1040) 2HB (U-U-002-1032)	479, 570, 627, 305						
	Attachment Be Certified									
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	E	PLICATION						
2018	CC	9.45, 17.0, 20.1, 30.3, 55.0	Riding Mower, Commercial Turf, Other Utility Vehicles							
EMISSIO	N CONTROL SYSTEMS (ECS)		ENGINE and/or EQUIPMENT MODEL							
	Canister/Co-extruded		See Attachment							
Code:- Meta	E (Venting Control Type/Tank Barrier Ty al=M Treated HDPE or PE=P Co-extruc ank Barrier Codes = M, P, C, L, N, A, O	ed=C Selar=L Nylon=N A	Acetal=A Other=O B. EVAPO	RATIVE FAMILY	2-Letter CODE (Venting Control Codes					

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable						
	OSE PERMEATION ms ROG/m²/day)		ANK PERMEATION ams ROG/m <sup>2</sup> /day)	CARBON CANISTER BUTANE WORKING CAPACITY (grams HC/lin		
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	
15	Q-10-004, C-U-05-002, C-U-05-009, Q-08-020, G-05-018, Q-08-013, Q-09-019A	1.5	Q-08-027A	1.4	Q-08-031, C-U-07-010, C-U-06-008, C-U-07-016A, Q-07-013A	

**BE IT FURTHER RESOLVED:** That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

This Executive Order hereby supersedes Executive Order U-U-100-0017 dated February 05, 2018.

Executed at El Monte, California on this \_\_\_\_\_ day of November 2018.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

Attachment 1 of 2

1-1-100-0017-

## Small Off-Road Evaporative Certification Database Form (Supplementary Information)

## MODEL SUMMARY

S1.	S2.	S3.		\$3.		S3.		S3.		S3.		\$3.		S3.		S3.		S3.		S3.		S3.		S3.		S3.		S3.		S3.		S5.		S6.	S7.	S8.	S9.	S10.	<b>S11</b> .	S12.	S13.	S14.
Worst Engine or Case Equipment (Check Model One)				Codes (check ppropriate)		Fuel System (Fl or CARB)	1 1		Fuel Fuel Line Tank Type Internal Surface	Nominal Fuel Line Length <sup>(1)</sup> (mm)	Fuel Line Inside Diameter (mm)	Exhaust Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister or Other Venting Control																											
		CA Only	49- State	50- State			Total	Nominal	Area (m²)							Executive Order																										
	Eclipse 322 062802 062803			x	11	CARB	20.5	20.1	0.526	<del>Low</del> <del>Permeation</del> Multi-Layer	711.2 (total combined hose lengths)	6.35	HBSXS.4792HH (U-U-002-0974), JBSXS.4792HH (U-U-002-1042)	Q-08-27A	Q-10-004, C-U-05-002, C-U-05-009, Q-08-020, G-05-018, Q-08-013, Q-09-19A	C-U-07-016A																										
	Greens King IV 062305 062306			x	II	CARB	39.1	30.3	0.944	<del>Low</del> <del>Permeation</del> Multi-Layer	635 (total combined hose lengths)	6.35	HBSXS.4792HH (U-U-002-0974), JBSXS.4792HH (U-U-002-1042), HBSXS.6272HN (U-U-002-0976), JBSXS.6272HN (U-U-002-1040)	Q-08-27A	Q-10-004, C-U-05-002, C-U-05-009, Q-08-020, G-05-018, Q-08-013, Q-09-19A	Q-08-031																										
x	GP-400 062706			x	11	CARB	59.0	55.0	1.518	Low Permeation Multi-Layer	850 (total combined hose lengths)	7.9	HBSXS.6272HN (U-U-002-0976), JBSXS.6272HN (U-U-002-1040)	Q-08-27A	Q-10-004, C-U-05-002, C-U-05-009, Q-08-020, G-05-018, Q-08-013, Q-09-19A	Q-07-013A																										
	Groomsmaster 088010			x	11	CARB	20.6	17.0	0.494	Low Permeation Multi-Layer	312.4 (total combined hose lengths)	6.35, 7.9	HBSXS.6272HN (U-U-002-0976), JBSXS.6272HN (U-U-002-1040)	Q-08-27A	Q-10-004, C-U-05-002, C-U-05-009, Q-08-020, G-05-018, Q-08-013, Q-09-19A	C-U-07-010																										

Attachment Lot 2

V-V-100-0017-1

	GA-24 058234			x	11	CARB	11.0	9.45	0.276	<del>Low</del> <del>Permeation</del> Multi-Layer	514.5 (total combined hose lengths)	6.35, 7.9	HBSXS.3052HB (U-U-002-0973), JBSXS.3052HB (U-U-002-1032)	Q-08-27A	Q-10-004, C-U-05-002, C-U-05-009, Q-08-020, G-05-018, Q-08-013, Q-09-19A	C-U-06-008	
--	-----------------	--	--	---	----	------	------	------	-------	--	---	-----------	---	----------	--	------------	--

(1) The nominal fuel line lengths can be grouped into increment of  $\pm 3$  inches (76 mm)