

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION								
	MANUFACTURER		LY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)						
CHC	NGQING MAIFENG POWER MACHINERY CO., LTD	JCMGS.21210	GL (U-U-165-0079)	196, 208, 212	Gasoline or LPG or Gasoline-LPG Dual-Fuel						
S.A. = See Attachment TBC = To Be Certified EQUIPMENT DESCRIPTION											
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	EQUIPMENT APPLICATION								
2018	CM212GL	See Attachment	Pump, Generator Set, Tiller								
EMISSION	N CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL									
	Canister/Metal	See Attachment									
A. ECS TYPE	E (Venting Control Type/Tank Barrier Ty	pe): 1. <u>Venting Control Ty</u>	pe and Code:- Canister=(C Sealed Tank=S Oth	her=0 2. Tank Barrier Type and Code: CODE (Venting Control Codes =C. S. O						

Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes =C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). Note: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable		DESIGN BASED										
	OSE PERMEATION ams ROG/m ² /day)		ANK PERMEATION ams ROG/m ² /day)	CARBON CANISTER BUTANE WORKING CAPACITY (grams HC/liter)								
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER							
15	Q-10-003, Q-08-005, Q-12-016A	1.5	Q-17-009A, Q-17-025, Q-17-017	Q-07-020, Q-08-035, 1.0, 1.4 Q-07-021, Q-13-005, Q-08-036, C-U-07-022								

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this <u>31</u> day of January 2018.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

Altachinent, 1 of 1

Small Off-Road Evaporative Certification Database Form (Supplementary Information)

MODEL SUMMARY																	
S1.	S2 .		S3.	3. 5		S5.		S6.	6. S7.	S8 .	S9.	S10.	S11.	S12.	S13.	S14.	
Worst Case (Chec k One)	Engine or Equipme nt Model	Sales Codes (check all appropriate)		(check all		Fuel Syste m (Fl	Fuel Tank Vol. (Liters)		Fuel Tank Internal	Fuel Line Type	Nomin al Fuel Line	Fuel Line Inside	Exhaust Family	Fuel Tank Executiv	Fuel Line Executiv	Carbon Canister or Other Venting	
		CA Onl y	49- Stat e	50- Stat e	- (tor II)	or CARB)	Tota I	Nomina I	Surface Area (m²)		Length ⁽ ¹⁾ (mm)	Diame ter (mm)		e Order	e Order	Control Executiv e Order	
-	170FA MF170FA 170F MF170F 168FB MF168FB	FA DF B					1.6	1.45	0.08					Q-17-009A		Q-07-020	
							3.6	3.5	0.14							Q-07-020	
							6.5	6.25	0.19				-			Q-08-035	
							17	16.7	0.5							Q-07-021	
								28	27.6	0.7							Q-13-005 Q-08-036
							31	30	0.6961		-					C-U-07-022	
						1.7	1.6	0.08688							Q-07-020		
X				*	11	CARB	3.6	3.5	0.126803	Multi- layer	150-500	4.5	JCMGS.2121GL	Q-17-025	Q-10-003 Q-08-005 Q-12-016A		
							6.6	6.5	0.25001	layer						Q-08-035	
							16.5	16	0.52958							Q-07-021	
							29.5	29	1.13221							Q-13-005 Q-08-036	
							3.7	3.59	0.151574							Q-07-020	
						6.3	6.16	0.193386				· · ·			Q-08-035		
							15.	14.62	0.463512					Q-17-017		Q-07-021	
							29	28.5	0.693327							Q-13-005 Q-08-036	
							31	29.83	0.720791							C-U-07-022	

(1) The nominal fuel line lengths can be grouped into increment of \pm 3 inches (76 mm)

48