

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE DE	SCRIPTION						
	MANUFACTURER	ENGINE FAMILY	(E.O. NUMBER)	ENGINE SIZE	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas) Gasoline				
Chong	iqing Rato Technology Co., Ltd.	JCRPS.2121GC JCRPS.2231GA JCRPS.0991GA	(U-U-169-0248) (U-U-169-0243) (U-U-169-0240) (U-U-169-0235) (U-U-169-0239)	179 212 223 99 212					
TBC = To B	e Certified	FOUIPMENT	DESCRIPTION						
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	EQUIPMENT APPLICATION						
2018	CM1H	3.4, 2.5, 3.1, 1.75	Compressor, Pump, Pressure Washer, Tiller, Other Industrial Equipment						
EMISSION	CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL							
	Canister/Metal	. See Attachment							
Metal=M Tr	Canister/Metal E (Venting Control Type/Tank Barrier Ty eated HDPE or PE=P Co-extruded=C Codes = M. P. C. L. N. A. O). Note: A	Selar=L Nylon=N Acetal=A O	and Code:- Canister=C ther=O B. EVAPORATIV	Sealed Tank=S Othe	ODE (Venting Control Codes =C,				

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable		PERFORMANCE BASED (grams HC/day)	
STANDARD	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL
0.95 + 0.056*Tank Vol. (L)		= (STANDARD) - (EFELD)	0.83

BE IT FURTHER RESOLVED: That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.

BE IT FURTHER RESOLVED: That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1.

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this 2

day of December 2017.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

Attachment, 1 of 1

Small Off-Road Evaporative Certification Database Form (Supplementary Information)

MODEL SUMMARY

S1.	S2.		S3.		S4.	S5.		S6.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case (Check One)	Case Model Check		s Codes appropr	*	Engin e Class (I or	Fuel System (FI or CARB)	ł	Tank Vol. Liters)	Fuel Tank Intern al	Fuel Line Typ e	Nomi nal Fuel Line	Fuel Line Inside Diameter (mm)	Exhaust Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister or Other Venting
		CA Onl y	49- Stat e	50- State	11)		Total	Nominal	Surfac e Area (m²)		Lengt h (mm)					Control Executive Order
X	R180-3III, K180III R210III, K210III, R225 R210-V, RG3.6-60Q-D RT50ZB26-3.6Q RT80ZB26-3.6Q RT50YB50-3.8Q RT50HB35-3.8Q RT80WB26-3.8Q WP3070S RT80ZB28-3.8Q					3.6	3.4	0.15		160	4 4	JCRPS. 1791GC JCRPS. 2121GC				
					CARR	2.8	2.5	0.13	13	160	4.5					
				1 CARB	3.6	3.1	0.139 Mul ti- laye	53	4.5	JCRPS. 2231GA JCRPS. 2121GV	N/A	Q-10-003 Q-08-005 Q-15-010 Q-15-011	N/A			
	R100-III, K100-III, R100-V DR RapidFire Log Splitter			X	I	CARB	2.0	1.75	0.094		200	4.5	JCRPS. 0991GA		Q-17-043	
	DA Rapidi ne Log Spiller										140	4.5				

⁽¹⁾ The nominal fuel line lengths can be grouped into increment of ± 3 inches (76 mm)