

CHONGQING HEYA TECHNOLOGY CO., LTD.

EXECUTIVE ORDER U-U-224-0018
New Off-Road Small Spark-Ignition
Equipment

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

	9	ENGINE	DESCRIPTION						
	MANUFACTURER	ENGINE FAM	MILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)				
	GQING ZONGSHEN GENERAL OWER MACHINE CO., LTD.		2HE (U-U-082-0271) .4202HE (TBC)	420	Gasoline				
	Attachment Be Certified	EQUIPME	NT DESCRIPTION						
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	E	PPLICATION					
2018	CM3	25 Compressor, Pump, Generator and Pressure Washer							
EMISSIO	N CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL							
Car	bon Canister/Metal Tank	See Attachment							
Code:- Met	E (Venting Control Type/Tank Barrier Ty al=M Treated HDPE or PE=P Co-extruc ank Barrier Codes = M, P, C, L, N, A, O	led=C Selar=L Nylon=N A	Acetal=A Other=O B. EVAPO	RATIVE FAMILY	2-Letter CODE (Venting Control Codes				

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable		DE	SIGN BASED			
	OSE PERMEATION ams ROG/m²/day)		ANK PERMEATION ams ROG/m²/day)	CARBON CANISTER BUTANE WORKING CAPACITY (grams HC/liter)		
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	
15	Q-08-005, Q-12-016A, C-U-07-003, Q-10-003	1.5	Q-16-027, Q-16-027A	1.4	Q-15-007, Q-12-011	

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this

day of November 2017

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

ATTACHHENT PS loft

Small Off-Road Evaporative Certification Database Form (Supplementary Information)

MODEL SUMMARY

U-U-224-0018

S1.	S2.		S3.		S4.	S5.	5	66.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case (Check One)	Engine or Equipment Model	Sales Codes (check all appropriate)		Engine Fuel Class System (I or (FI or II) CARB)		Fuel Tank Vol. (Liters)		Fuel Tank Internal Surface	Fuel Line Type	Nomina I Fuel Line Length ⁽¹	Fuel Line Inside Diamete	Exhaust Family	Fuel Tank Executi ve	Fuel Line Executive Order	Carbon Canister or Other Venting	
		C A On ly	49- State	50- State			Total Nom (m ²)) (mm)) (mm) r (mm)		Order		Control Executive Order		
	190F_(EFI) ZS190F_(EFI) 190F-2(EFI) 190F-2(EFI) HY7500EFI IG7800EFI HY7000EFI EZV8000EFI ST8000EFI TI8000EFI RY18000EFI/ EZV7500 EFI/ HY7500 EFI/ HY7500P/ HY7500P/ XP7000S/ SG7000/			X	II	CARB	25	25	0.654	multila yer	320	7	HCZHS.4202HE JCZHS.4202HE	Q-16- 027 Q-16- 027A	Q-08-005 Q-12-016A C-U-07- 003 Q-10-003	Q-15-007 Q-12-011
															·	
												-				

⁽¹⁾ The nominal fuel line lengths can be grouped into increment of ± 3 inches (76 mm)