

KOHLER COMPANY

EXECUTIVE ORDER U-U-005-0634 New Off-Road Small Spark-Ignition Equipment

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012:

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION						
	MANUFACTURER	ENGINE FAI	MILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleu gas)				
	KOHLER COMPANY	KKHXS.277 JKHXS.429	2GA (U-U-005-0579) 2GA (U-U-005-0600) 2GA (U-U-005-0580) 2GA (U-U-005-0601)	277, 429	Gasoline				
TBC = To E	Be Certified	EQUIPME	NT DESCRIPTION						
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	E	PPLICATION					
2019	CM12	6.8	Compressor Plump Generator Pressure Washer and						
EMISSIO	N CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL							
	Canister/Metal Tank	See Attachment							
Code:- Met	E (Venting Control Type/Tank Barrier Ty al=M Treated HDPE or PE=P Co-extruc ank Barrier Codes = M, P, C, L, N, A, O)	ed=C Selar=L Nylon=N	Acetal=A Other=O B. EVAPO	RATIVE FAMILY	2-Letter CODE (Venting Control Codes				

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable	PERFORMANCE BASED (grams HC/day)								
STANDARD	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL						
1.20 + 0.056*Tank Vol. (L)	0.47	= (STANDARD) - (EFELD)	1.05						

BE IT FURTHER RESOLVED: That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.

BE IT FURTHER RESOLVED: That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model and it's for use in the averaging and banking program. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1(e).

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.



KOHLER COMPANY

EXECUTIVE ORDER U-U-005-0634 New Off-Road Small Spark-Ignition Equipment

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

ATTACHHENT BIOGI

Small Off-Road Evaporative Certification Database Form (Supplementary Information)

MODEL SUMMARY

11-11-005-0634

S1.	S2.		S3.		S4.	S5.		S6.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case (Check One)	Engine or Equipment Model	Sales Codes (check all appropriate)		Engine Class (I or II)	Fuel System (FI or CARB)	Fuel Tank Vol. (Liters)		Fuel Tank Internal Surface	Fuel Line Type	Nominal Fuel Line Length ⁽¹⁾	Fuel Line Inside Diameter	Exhaust Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister or Other Venting	
		CA Only	49- State	50- State	11)	CAID)	Total	Nominal	Area (m²)		(mm)	(mm)		Oruci		Control Executive Order
	CH395			X	11	CARB	7.0	6.8	0.201	Multi	195	4.5	KKHXS.2772GA JKHXS.2772GA	N/A	Q-08-005 Q-14-008	N/A
х	CH440			x	11	CARB	7.0	6.8	0.201	Multi	221	4.5	KKHXS.4292GA JKHXS.4292GA	N/A	G-05-018 Q-08-005 Q-14-008	N/A
														,		

⁽¹⁾ The nominal fuel line lengths can be grouped into increment of \pm 3 inches (76 mm)