Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION									
	MANUFACTURER	ENGINE FAI	MILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)							
L	ONCIN MOTOR CO., LTD.	JCGPS.420 KCGPS.420	2GR (U-U-145-0328) 2GR (U-U-145-0356)	389, 420								
ŀ	HONDA MOTOR CO., LTD.	JHNXS.270 JHNXS.389 JHNXS.389 JHNXS.688	Gasoline									
* TBC = To	* TBC = To Be Certified EQUIPMENT DESCRIPTION											
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	EQUIPMENT APPLICATION									
2019	СМЗ	27.3, 28.39, 29.9, 37.48		Generat	or Set							
EMISSIO	N CONTROL SYSTEMS (ECS)	EQUIPMENT MODEL										
	Canister/Metal Tank	See Attachment										
A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. <u>Venting Control Type and Code</u> :- Canister=C Sealed Tank=S Other=O 2. <u>Tank Barrier Type and</u> <u>Code</u> :- Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes =C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). <u>Note</u> : Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.												

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

DESIGN BASED											
FUEL H	IOSE PERMEATION ams ROG/m ² /day)	FUEL T (gra	ANK PERMEATION ams ROG/m ² /day)	CARBON CANISTER BUTANE WORKING CAPACITY (grams HC/liter)							
STANDARD	ANDARD CERTIFICATION LEVEL OR EXCUTIVE ORDER		CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER						
15	C-U-06-010, C-U-05-012, Q-14-008	1.5	Q-16-019	1.4	C-U-07-022, C-U-07-011, C-U-07-023						

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

274 Executed at El Monte, California on this day of October 2018.

Ficile

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

ATTACHMENT B 1.41

Small Off-Road Evaporative Certification Database Form (Supplementary Information)

MODEL SUMMARY

u-u-027-0267

S 1.	S2.	S3.		S4.	S5.		S6.	S7.	S8.	S9 .	S10 .	S11.	S12.	S13.	S14.	
Worst Case (Check	Engine or Equipment Model	Sales Codes (check all appropriate)		Engine Class (I or	Fuel System (FI or	Fuel Tank Vol. (Liters)		Fuel Tank Internal	Fuel Line Type	Nominal Fuel Line	Fuel Line Inside	Exhaust Family	Fuel Tank Executive	Fuel Line Executive Order	Carbon Canister or Other	
One)		CA Only	49- State	50- State	- 11)	CARB)	Total	Nominal	Surface Area (m ²)		(mm)	(mm)		Order		Venting Control Executive Order
	GSH420VGC1	x			п	CARB	30.28	28.39	0.731	MULTI LAYER	140	6	JCGPS.4202GR KCGPS.4202GR	Q-16-019	C-U-05-012 C-U-06-010 Q-14-008	C-U-07-022
	HSH270PGE1			x	Ш	CARB	31.0	27.3	0.71	MULTI LAYER	559	6.4	JHNXS.2702AB	Q-16-019	C-U-05-012 C-U-06-010 Q-14-008	C-U-07-011 C-U-07-022
	HSH389PGE1			x	П	CARB	31.0	29.9	0.77	MULTI LAYER	571	6.4	JHNXS.3892AB	Q-16-019	C-U-05-012 C-U-06-010 Q-14-008	C-U-07-011 C-U-07-022
	HSH389PGE2			x	Ш	CARB	31.0	29.9	0.77	MULTI LAYER	571	6.4	JHNXS.3892AC	Q-16-019	C-U-05-012 C-U-06-010 Q-14-008	C-U-07-011 C-U-07-022
	HSH688PGE1			x	п	CARB	43.8	37.48	0.93	MULTI LAYER	432	6.4	JHNXS.6882AA	Q-16-019	C-U-05-012 C-U-06-010 Q-14-008	C-U-07-011 C-U-07-023
								·								

(1) The nominal fuel line lengths can be grouped into increment of ± 3 inches (76 mm)