Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION							
	MANUFACTURER	ENGINE FAM	MILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)					
Liquid	Combustion Technology, LLC	KLCTS.179	1EX (U-U-063-0167)	179	Gasoline					
TBC = To B	e Certified	EQUIPMEI	NT DESCRIPTION							
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	EQUIPMENT APPLICATION							
2019	KLCTE1OM179L	2.0 Pump, Generator Set, Pressure Washer								
EMISSION	CONTROL SYSTEMS (ECS)		ENGINE and/or EQUIPMENT MODEL							
	Other / Metal		See Attachment							
					Other=O 2. Tank Barrier Type and Code					

A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. <u>Venting Control Type and Code</u>:- Canister=C Sealed Tank=S Other=O 2. <u>Tank Barrier Type and Code</u>:- Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes = C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). <u>Note</u>: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable	PERFORMANCE BASED (grams HC/day)							
STANDARD	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL					
0.95 + 0.056*Tank Vol. (L)	* .	*	0.70					

BE IT FURTHER RESOLVED: That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.

BE IT FURTHER RESOLVED: That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model and it's for use in the averaging and banking program. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1(e).

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this day of January 2019.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

ATTACHMENT P(OF) E0#U-V-063-0185

Small Off-Road Evaporative Certification Database Form (Supplementary Information)

MODEL SUMMARY

S1.	S2.		S3.		S4.	S5.	S	86.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case Equipment (Check Model		Sales Codes (check all appropriate)		Class S	System (FI or		ank Vol. ters)	Tank Line	Fuel Line Type	Fuel Line	Fuel Line Inside	Exhaust Family	Fuel Tank Executive	Fuel Line Executive Order	Carbon Canister or Other	
One)		CA Only	49- State	50- State	11)	CARB)	Total	Nominal	Surface Area (m ²)		Length ⁽¹⁾ (mm)	Diameter (mm)		Order		Venting Control Executive Order
x	PLMHK- E1B 179			×	ı	Carb	2.25L	2.0L	0.103m2	Multi	165.1	6.35	KLCTS.1791EX	Q-17-028 (metal tank)	C-U-06- 030A	Carbon fuel cap
							1									
		,, , , , ,												VIII		

⁽¹⁾ The nominal fuel line lengths can be grouped into increment of ± 3 inches (76 mm)