

CHONGQING ZONGSHEN GENERAL POWER MACHINE CO., LTD.

EXECUTIVE ORDER U-U-082-0353 New Off-Road Small Spark-Ignition Equipment

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012:

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION			
	MANUFACTURER	ENGINE FAMILY (E.O. NUMBER)		ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)	
	IGQING ZONGSHEN GENERAL OWER MACHINE CO., LTD.	KCZH:	KCZHS.1491H1 (TBC) KCZHS.1491V2 (TBC) KCZHS.1591V2 (TBC) KCZHS.2241V2 (TBC)		Gasoline	
TBC = To E	Be Certified	EQUIPME	NT DESCRIPTION			
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	EQUIPMENT APPLICATION			
2019	CPXP2	See Attachment Compressor, Pump, Stump Beater, Non-Beater, Pressure Washer, Tiller, Edger, Other Indu				
EMISSIO	N CONTROL SYSTEMS (ECS)		ENGINE and/or	QUIPMENT N	MODEL	
	Canister/HDPE	See Attachment				
Metal=M Ti	E (Venting Control Type/Tank Barrier Ty reated HDPE or PE=P Co-extruded=C : r Codes = M. P. C. I. N. A. O). Note: A	Selar=L Nylon=N Acetal=/	A Other=O B. EVAPORATIVE	FAMILY 2-Lette		

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable	PERFORMANCE BASED (grams HC/day)			
STANDARD	EVAPORATIVE FAMILY EMISSION LIMIT DIFFERENTIAL (EFELD)	EVAPORATIVE MODEL EMISSION LIMIT (EMEL)	CERTIFICATION LEVEL	
0.95 + 0.056*Tank Vol. (L)	*	= (STANDARD) - (EFELD)	0.41	

BE IT FURTHER RESOLVED: That the evaporative model emission limit (EMEL), as applicable, is the diurnal emissions level declared by the manufacturer based on diurnal test results for a worst-case engine or equipment model within an evaporative family. No engine or equipment emissions within the evaporative family could be closer to its respective standard than the evaporative family emission limit differential (EFELD) calculated from the declared EMEL for the worst-case engine or equipment.

BE IT FURTHER RESOLVED: That the evaporative family emission limit differential (EFELD), as applicable, is an emission level differential between the effective standard level for a specific model representing the entire evaporative family and the EMEL declared for the specific model. It serves as the applicable evaporative emission standard for determining compliance on a corporate average basis of any equipment within this evaporative family under 13 CCR Sections 2754.1.

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this _____ day of December 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

Attachment, 1 of 2

Small Off-Road Evaporative Certification Database Form (Supplementary Information)

MODEL SUMMARY

S14.	Carbon Canister or Other Venting	Control Executive Order	A/S	Ϋ́	N/A	ΣΊΣ	N/A
S13.	Fuel Line Executive Order		G-05-018 or Q-14-008 or Q-15-010 or Q-19-002	G-05-018 or Q-14-008 or Q-15-010 or Q-19-002	G-05-018 or Q-14-008 or Q-15-010 or Q-19-002	G-05-018 or Q-14-008 or Q-15-010 or Q-19-002	G-05-018 or Q-14-008 or Q-15-010 or Q-19-002
S12.	Fuel Tank Executive Order		N/A	N/A	A/N	N/A	N/A
S11.	Exhaust Family		KCZHS.1491H1	KCZHS.1491V2	KCZHS.1591V2	KGZHS.2241V2	KCZHS.2241V2
S10.	Fuel Line Inside Diameter (mm)	ź	6.3	6.3	6.3	დ	6.3
.89.	Nominal Fuel Line Length ⁽¹⁾ (mm)		88	75	200 or 260	322	Multilayer 300 or 322
S8.	Fuel Line Type		Multilayer	Multilayer	Multilayer	Multilayer	Multilayer
S7.	Fuel Tank Internal Surface	Area (m²)	0.07	0.05	0.068	0.08	0.073
S6.	l Tank Vol. (Liters)	Nominal	1.1	0.75	0.8	6.	1.7
	Fuel T (Li	Total	1.2	0.85	0.9	4.	1.3
S5.	Fuel System (Fl or CARB)		CARB	CARB	CARB	CARB	CARB
S4.	Engine Class (I or II)		_	_	_	_	_
S3.	Sales Codes (check all appropriate)	50- State	×	×	×	×	×
		CA 49- Only State					
S2.	Engine or Equipment Model	0	NH130-01- NH130-01- NH150-01- NH150-03- NH150-04- NH150-05	NP130-01- NP130-01- NP150-01- NP150-02- NP150-03- NP150-04- NP150-05-	XP140_ XP140-01_ XP140-02_ XP140-03_ XP140-04_ XP140-05_	XP200-02 XP200-03 XP200-05 XP200-06 XP200-09 XP200-09 XP200-10 XP225 XP225 XP225	XP200XP200XP200-01XP200-04XP200-08XP200-09XP200-09XP200-09XP200-09XP200-09XP200-09XP200-09XP200-09XP200-09XP200-09XP200-09XP200-09
S1.	Worst Case (Check One)				×		

IN	5
S	0
W	2
0	
1	L
N	S
8	1
9	0
125	V .
7	-
1	U
2	De

N/A
G-05-018 or Q-14-008 or Q-15-010 or Q-19-002
Y Y
KCZHS.1591V2
6.3
300
Multilayer
0.08
. 23
4.1
CARB
_
×
XP160-01 XP160-01 XP160-03 XP160-04 XP160-05 XP160-06 XP160-06 XP160-08

(1) The nominal fuel line lengths can be grouped into increment of \pm 3 inches (76 mm) (2) Postfix _ of the model name is the designator(s) for future non-emission related revision change, may appears as other number or letter.