LONCIN MOTOR CO., LTD.

EXECUTIVE ORDER U-U-145-0357 New Off-Road Small Spark-Ignition Equipment

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION							
	MANUFACTURER	ENGINE FAM	ILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas) Gasoline					
L	ONCIN MOTOR CO., LTD.	KCGPS.4202	GR (U-U-145-0356)	389, 420						
S.A. = See TBC = To B	Attachment le Certified	EQUIPMEN	T DESCRIPTION	1						
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	EQUIPMENT APPLICATION							
2019	CMKCGPS.420R	See Attachment Compressor, Pump, Pressure Washer, Stump Beater, Generator Set, Tiller, Brushcutter, Other Industrial Equipme								
EMISSIO	N CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL								
	Canister/Metal	See Attachment								
Metal=M Tr	eated HDPE or PE=P Co-extruded=C	Selar=L Nylon=N Acetal=A	Other=O B. EVAPORATIVE	FAMILY 2-Lette	other=O 2. <u>Tank Barrier Type and Code</u> or CODE (Venting Control Codes =C, S, O Do not use abbreviations for ECS types.					

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable		DE	SIGN BASED				
	OSE PERMEATION ams ROG/m²/day)		ANK PERMEATION ams ROG/m²/day)	CARBON CANISTER BUTANE WORKING CAPACITY (grams HC/liter)			
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER		
15	See Attachment	1.5	See Attachment	1.4	See Attachment		

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this day of August 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

Attachment

Small Off-Road Evaporative Certification Database Form (Supplementary Information)

U-U-145.0357

MODEL SUMMARY

SI.	S2.		S3.		S4.	S5.		S6.	S7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case (Check One)	Engine or Equipment Model			Sales Codes (check all appropriate)		Fuel System (FI or	Fuel Tank Vol. (Liters)		Fuel Tank Internal	Fuel Line Type	Fuel Line	Fuel Line Inside	Exhaust Family	Fuel Tank Executive	Fuel Line Executive Order	Carbon Canister or Other
		CA Only	49- State	50- State	11)	II) CARB)	Total	Nominal	Surface Area (m²)		Length ⁽¹⁾ (mm)	Diameter (mm)		Order		Venting Control Executive Order
	G390FA, G420FA G390FDA, G420FDA			x	- 11	CARB	6.8L	6.5L	0.26	multilayer	<=300	≽ 4	KCGPS.4202GR	Q-16-015 Q-16-015A Q-16-015B Q-16-017 Q-16-017A Q-16-019 Q-16-019A Q-16-019B Q-16-019C	C-U-05-012 G-05-018, Q-13-013	C-U-07-021 Q-08-035 Q-11-002 C-U-06- 031A Q-15-004
	G390FA, G420FA G390FDA, G420FDA			x	II	CARB	22.2L	22L	0.7	multilayer	<=300	≥4	KCGPS.4202GR	Q-16-015 Q-16-015A Q-16-015B Q-16-017 Q-16-017A Q-16-019C Q-16-019 Q-16-019A Q-16-019B Q-16-019C	C-U-05-012 G-05-018, Q-13-013	C-U-07- 016B C-U-07- 016A C-U-07- 022, Q-08-036 Q-11-023 Q-15-008
	G390FA, G420FA G390FDA, G420FDA			x	II	CARB	32L	26.5L	0.75	multilayer	<=300	≥ 4	KCGPS.4202GR,	Q-16-019 Q-16-019A Q-16-019B Q-16-019C	C-U-05-012 G-05-018, Q-13-013	C-U-07- 022 , Q-08-036 Q-11-023 Q-15-008
	G390FA, G420FA G390FDA, G420FDA			x	11	CARB	30.5L	30.3L	0.78	multilayer	<=300	≽ 4	KCGPS.4202GR,	Q-16-019 Q-16-019A Q-16-019B Q-16-019C	C-U-05-012 G-05-018, Q-13-013	C-U-07-022 Q-15-008

	G390FA, G420FA G390FDA, G420FDA		x	11	CARB	27L	22L	0.7	multilayer	<=300	≽ 4	KCGPS.4202GR	Q-16-015 Q-16-015A Q-16-015B Q-16-017 Q-16-017A Q-16-019 Q-16-019A Q-16-019B Q-16-019C	C-U-05-012 G-05-018, Q-13-013	C-U-07- 016B C-U-07- 016A C-U-07- 022, Q-08-036 Q-11-023 Q-15-008
	G390FA, G420FA G390FDA, G420FDA		x	II	CARB	25.5L	22L	0.7	multilayer	<=300	≽ 4	KCGPS.4202GR	Q-16-015 Q-16-015B Q-16-017 Q-16-017A Q-16-019 Q-16-019A Q-16-019B Q-16-019C	C-U-05-012 G-05-018, Q-13-013	C-U-07- 016B C-U-07- 016A C-U-07- 022, Q-08-036 Q-11-023 Q-15-008
×	G390FA, G420FA G390FDA, G420FDA		х	II	CARB	35L	30.3L	0.78	multilayer	<=300	≥4	KCGPS.4202GR,	Q-16-019 Q-16-019A Q-16-019B Q-16-019C	C-U-05-012 G-05-018, Q-13-013	C-U-07-022 Q-15-008
	G390FA, G420FA G390FDA, G420FDA		х	11	CARB	8.8L	8.5L	0.26	multilayer	<=300	≥4	KCGPS.4202GR	Q-16-015 Q-16-015A Q-16-015B	C-U-05-012 G-05-018, Q-13-013	C-U- 06-008
	G390FA, G420FA G390FDA, G420FDA	 -	х	II	CARB	35L	30L	0.71	multilayer	<=300	≥4	KCGPS.4202GR,	Q-16-015 Q-16-015A Q-16-015B	C-U-05-012 G-05-018, Q-13-013	C-U-07-022 Q-15-008 C-U-07- 016B
	G390FA, G420FA G390FDA, G420FDA	,	X.	II	CARB	33L	30L	0.719	multilayer	<=300	.≥4	KCGPS.4202GR,	Q-16-019C	C-U-05-012 G-05-018, Q-13-013	Q-15-008

⁽¹⁾ The nominal fuel line lengths can be grouped into increment of ± 3 inches (76 mm)