

## CHONGQING SHINERAY AGRICULTURAL MACHINERY CO., LTD.

EXECUTIVE ORDER U-U-200-0065 New Off-Road Small Spark-Ignition Equipment

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012:

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION					
	MANUFACTURER	ENGINE FAN	IILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)  Gasoline			
CHONGO	ING SHINERAY AGRICULTURA MACHINERY CO., LTD.	KCSPS.223	1XA (U-U-200-0064)	208, 212, 223				
S.A. = See / TBC = To B	Attachment e Certified	EQUIPMEN	IT DESCRIPTION					
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	EQUIPMENT APPLICATION					
2019	CM2231XA	See Attachment	Compressor, Pump, Pressure Washer, Generator Set, Tiller, Other Industrial Equipment					
EMISSION	CONTROL SYSTEMS (ECS)		ENGINE and/or	EQUIPMENT I	MODEL			
	Canister/Metal		See A	Attachment				
Metal=M Tr	eated HDPE or PE=P Co-extruded=C S	elar=L Nylon=N Acetal=A	Other=O B. EVAPORATIV	E FAMILY 2-Lette	Other=O 2. <u>Tank Barrier Type and Code</u> or CODE (Venting Control Codes =C, S, C Do not use abbreviations for ECS types			

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable	able DESIGN BASED											
	OSE PERMEATION ams ROG/m²/day)		ANK PERMEATION ams ROG/m²/day)	CARBON CANISTER BUTANE WORKING CAPACITY (grams HC/liter)								
STANDARD	ANDARD CERTIFICATION LEVEL OR EXECUTIVE ORDER		CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER							
15	See Attachment	1.5	See Attachment	1.0, 1.4	See Attachment							

**BE IT FURTHER RESOLVED:** That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_ day of August 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

U-U-200-0065

RC#1

## Small Off-Road Evaporative Certification Database Form (Supplementary Information)

**MODEL SUMMARY** 

(page 1 of z)

05-08-19

S1.	S2.		S3.		S4.	S5.	S	66.	<b>S</b> 7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case (Check One)	Engine or Equipment Model	(c app	es Cod heck a propriat	II te) 50-	Engine Class (I or II)	Fuel System (Fl or CARB)	Vol. (	Tank Liters)	Fuel Tank Internal Surface Area (m²)	Fuel Line Type	Nominal Fuel Line Length (mm)	Fuel Line Inside Diameter (mm)	Exhaust Family	Fuel Tank Executiv e Order	Fuel Line Executive Order	Carbon Canister or Other Venting Control Executive Order
х	SR170FE/P	Only	State	State X	ı	CARB	4.0	3.6	0.15	Multilayer	145±10	4	KCSPS.2231XA	Q-16-027	Q-10-003 Q-08-005 Q-18-031 Q-18-031A	Q-07-020, C-U-07-008,
	SR170FE/P			х	_	CARB	4.8	4.5	0.17	Multilayer	145±10	4	KCSPS.2231XA	Q-16-027	Q-10-003 Q-08-005 Q-18-031	Q-08-035 C-U-07-021
	SR170FE/P			х	. 1	CARB	16.5	16	0.46	Multilayer	145±10	4	KCSPS.2231XA	Q-16-027	Q-10-003 Q-08-005 Q-18-031 Q-18-031A	C-U-07-009, Q-07-021
	SR170FA/P SR170FB/P			×	_	CARB	4.0	3.8	0.15	Multilayer	200±3	4	KCSPS.2231XA	Q-16-019 Q-16-027	Q-10-003 Q-08-017 Q-12-016A Q-18-031 Q-18-031A	C-U-07-021 Q-08-035 Q-11-014
	SR170FA/P SR170FB/P			х	-	CARB	17	15	0.62	Multilayer	200±3	4	KCSPS.2231XA	Q-16-019 Q-16-027	Q-10-003 Q-08-017 Q-12-016A Q-18-031 Q-18-031A	C-U-07-009, Q-07-021
	SR170FA/P SR170FB/P			х	-	CARB	4.8	4.5	0.17	Multilayer	200±3	4	KCSPS.2231XA	Q-16-019 Q-16-027	Q-10-003 Q-08-017 Q-12-016A Q-18-031 Q-18-031A	C-U-07-021 Q-08-035 Q-11-014
	SR170FA/P SR170FB/P			x	l	CARB	4.0	3.6	0.14	Multilayer	200±3	4	KCSPS.2231XA	Q-16-019 Q-16-027	Q-10-003 Q-08-017 Q-12-016A Q-18-031 Q-18-031A	C-U-07-008, Q-07-020

Attachment (page 2 of 2)

U-U-200-0065 RC#1.05-08-19

SR170FA/P SR170FB/P		x	1	CARB	4.0	3.6	0.15	Multilayer	200±3	4	KCSPS.2231XA		Q-10-003 Q-08-017 Q-12-016A Q-18-031 Q-18-031A	C-U-07-008, Q-07-020
SR170FA/P SR170FB/P		x	_	CARB	16.5	16	0.46	Multilayer	200±3	4	KCSPS.2231XA	u 10 02.	Q-10-003 Q-08-017 Q-12-016A Q-18-031 Q-18-031A	C-U-07-009, Q-07-021

<sup>(1)</sup> The nominal fuel line lengths can be grouped into increment of  $\pm 3$  inches (76 mm)