

CHONGQING DINKING POWER MACHINERY CO., LTD

EXECUTIVE ORDER U-U-210-0097 New Off-Road Small Spark-Ignition Equipment

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

		ENGINE	DESCRIPTION								
	MANUFACTURER	ENGINE FAM	ILY (E.O. NUMBER)	ENGINE SIZE	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)						
CHO	ONGQING DINKING POWER MACHINERY CO., LTD	KCHDS.2231	EM (U-U-210-0093)	196, 212, 223	Gasoline						
S.A. = See Attachment TBC = To Be Certified EQUIPMENT DESCRIPTION											
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK SIZE (liters)	EQUIPMENT APPLICATION								
2019	CM2231	See Attachment	Compressor, Pump, Pressure Washer, Generator Set, Tiller, Other Industrial Equipment								
EMISSION	CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL									
	Canister/Metal	See Attachment									
Metal=M Tr	eated HDPE or PE=P Co-extruded=C	Selar=L Nylon=N Acetal=A	A Other=O B. EVAPORAT	IVE FAMILY 2-Letter	ner=O 2. <u>Tank Barrier Type and Code</u> : CODE (Venting Control Codes =C, S, O) Do not use abbreviations for ECS types.						

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754(a) or 2754(b), as applicable), and certification levels in grams per day (g/day) or grams per square meter per day (g/m²/day) or grams per liter (g/l) for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

*=not applicable DESIGN BASED											
	OSE PERMEATION ams ROG/m²/day)		ANK PERMEATION ams ROG/m²/day)	CARBON CANISTER BUTANE WORKING CAPACITY (grams HC/liter)							
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER						
15	See Attachment	1.5	See Attachment	1.0, 1.4	See Attachment						

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

Executed at El Monte, California on this

_ day of December 2018.

Annette Hebert, Chief

*Emissions Compliance, Automotive Regulations and Science Division

Altachnesit, 1 of 1

Small Off-Road Evaporative Certification Database Form (Supplementary Information)

MODEL SUMMARY

S1.	SZ.		S 3.		S4.	S5.		S6.	S 7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case (Check One)	Engine or Equipment Model		Codes (appropri		Engine Class System (I or II) (FI or CARB)			Tank Vol. .iters)	s) Tank Internal Surface		Nominal Fuel Line Length ⁽¹⁾	Fuel Line Inside Diameter	Exhaust Family	Fuel Tank Executive Order	Fuel Line Executi ve	Carbon Canister or Other Venting
		CA Only	49- State	50- State			Total	Nominal	Area (m²)		(mm)	(mm)			Order	Control Executive Order
	DK170F/P DK170F/P-2 YK700						15	13.5	0.53							Q-07-021 C-U-06-007A
	CMT212 DK168F/P-1	İ					10	9.5	0.29							C-0-00-007A
	YK650 YK550															
	CMT200 T7															
	T6 170F/P					¢.	3.6	3.45	0.17						Q-08-005	Q-07-020
	170F/P-2 168F/P-1				1	CARB	3.0	3.43	0.17	Multi- layer	250	4	KCHDS.2231EM	Q-17-024	Q-05-005 Q-15-012 Q-13-013	C-U-06-003
	170F/P-1 DK170FD/P-														Q-15-010	
	2 170FD/P-2						X									
x	DK170F/P-1			•			15	13.5	0.53							Q-07-021
	DK170F/P-1			*		X	10	9.5	0.29							C-U-06-007A
	DK170F/P-1						3.6	3.45	0.17							Q-07-020 C-U-06-003

⁽¹⁾ The nominal fuel line lengths can be grouped into increment of 3 inches (76 mm)