



Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

**IT IS ORDERED AND RESOLVED:** That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

| ENGINE DESCRIPTION       |                             |                                     |   |
|--------------------------|-----------------------------|-------------------------------------|---|
| MANUFACTURER             | ENGINE FAMILY (E.O. NUMBER) | ENGINE SIZE (cc)                    | FUEL TYPE<br>(CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)                     |
| MTD Southwest Inc.       | LMTDS.0304EF (U-U-020-0376) | 30                                  | Gasoline  |
| TBC = To Be Certified    |                             |                                     |   |
| EQUIPMENT DESCRIPTION    |                             |                                     |   |
| MODEL YEAR               | EVAPORATIVE FAMILY          | FUEL TANK NOMINAL CAPACITY (liters) | EQUIPMENT APPLICATION   |
| 2020                     | LMTDS.0304EF                | 0.444                               | Brushcutter, Edger, Hedge Trimmer, Leaf Blower/Vacuum, Line Trimmer, Non-Backpack Blower, Tiller, Other |
| EMISSION CONTROL SYSTEMS |                             | ENGINE and/or EQUIPMENT MODEL(S)    |   |
| P                        |                             | See Attachment                      |   |

TANK TYPE: S=sealed M=metal P=treated HDPE or PE C=coextruded L=selar N=nylon A=acetal O=other (specify)

The following are the evaporative emission standard (Title 13, California Code of Regulations, 13 CCR Section 2755 or 2757, as applicable), and certification level in g ROG·m<sup>-2</sup>·day<sup>-1</sup> for this evaporative family or the component Executive Order, as applicable.

| PERMEATION EMISSION STANDARDS                                       |  |   |  |
|---|--|---|--|
| FUEL LINE PERMEATION<br>(g ROG·m <sup>-2</sup> ·day <sup>-1</sup> ) |  | FUEL TANK PERMEATION<br>(g ROG·m <sup>-2</sup> ·day <sup>-1</sup> ) |  |
| STANDARD  | CERTIFICATION LEVEL OR EXECUTIVE ORDER     | STANDARD  | CERTIFICATION LEVEL OR EXECUTIVE ORDER |
| 15  | Q-19-067 (Q-14-003)<br>Q-19-145 (Q-08-021) | 2.0   | Q-19-059 (Q-17-058A)                   |

**BE IT FURTHER RESOLVED:** That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

**This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.**

This Executive Order hereby supersedes Executive Order U-U-020-0377 dated November 25, 2019.

Executed at El Monte, California on this 29<sup>th</sup> day of January 2020.

  
Allen Lyons, Chief  
Emissions Certification and Compliance Division

### Model Summary Sheet

(In #11, identify the fuel tank model exhibiting the highest permeation rate relative to the applicable permeation emission standard.)

| 11.<br>Worst Case<br>(Check One) | 12.<br>Model  | 13.<br>Sales Codes<br>(Check all appropriate) |              | 14.<br>Fuel Tank<br>Volume (Liters) |         | 15.<br>Fuel Tank<br>Internal<br>Surface<br>Area<br>(m <sup>2</sup> ) | 16.<br>Fuel Line<br>Type<br>(e.g.<br>Single or<br>Multi-<br>Layer) | 17.<br>Fuel<br>Line<br>Length<br>(mm) | 18.<br>Fuel Line<br>Internal<br>Diameter<br>(mm) | 19.<br>Exhaust<br>Family | 20.<br>Fuel Tank<br>Component<br>Executive Order* | 21.<br>Fuel Line<br>Component<br>Executive Order* |
|----------------------------------|---------------|---|--------------|-------------------------------------|---------|--|--|---------------------------------------|--|--------------------------|---|---|
|                                  |               | Calif.<br>Only                                | 50-<br>State | Total                               | Nominal |  |  |                                       |  |                          |   |   |
|                                  |               |   |              |                                     |         |  |  |                                       |  |                          |   |   |
| X                                | AC3X          |   | X            | 0.455                               | 0.444   | 0.039  | Multi  | 273.05                                | 2.381  | LMTDS.0304EF             | Q-19-059 (Q-17-058A)                              | Q-19-067 (Q-14-003)<br>Q-19-145 (Q-08-021)        |
|                                  | Bolens        |   | X            | 0.455                               | 0.444   | 0.039  | Multi  | 273.05                                | 2.381  | LMTDS.0304EF             | Q-19-059 (Q-17-058A)                              | Q-19-067 (Q-14-003)<br>Q-19-145 (Q-08-021)        |
|                                  | Craftsman     |   | X            | 0.455                               | 0.444   | 0.039  | Multi  | 273.05                                | 2.381  | LMTDS.0304EF             | Q-19-059 (Q-17-058A)                              | Q-19-067 (Q-14-003)<br>Q-19-145 (Q-08-021)        |
|                                  | Craftsman Pro |   | X            | 0.455                               | 0.444   | 0.039  | Multi  | 273.05                                | 2.381  | LMTDS.0304EF             | Q-19-059 (Q-17-058A)                              | Q-19-067 (Q-14-003)<br>Q-19-145 (Q-08-021)        |
|                                  | CUB CADET     |   | X            | 0.455                               | 0.444   | 0.039  | Multi  | 273.05                                | 2.381  | LMTDS.0304EF             | Q-19-059 (Q-17-058A)                              | Q-19-067 (Q-14-003)<br>Q-19-145 (Q-08-021)        |
|                                  | Hyper Tough   |   | X            | 0.455                               | 0.444   | 0.039  | Multi  | 273.05                                | 2.381  | LMTDS.0304EF             | Q-19-059 (Q-17-058A)                              | Q-19-067 (Q-14-003)<br>Q-19-145 (Q-08-021)        |
|                                  | Murray        |   | X            | 0.455                               | 0.444   | 0.039  | Multi  | 273.05                                | 2.381  | LMTDS.0304EF             | Q-19-059 (Q-17-058A)                              | Q-19-067 (Q-14-003)<br>Q-19-145 (Q-08-021)        |
|                                  | Murray Select |   | X            | 0.455                               | 0.444   | 0.039  | Multi  | 273.05                                | 2.381  | LMTDS.0304EF             | Q-19-059 (Q-17-058A)                              | Q-19-067 (Q-14-003)<br>Q-19-145 (Q-08-021)        |
|                                  | Remington     |   | X            | 0.455                               | 0.444   | 0.039  | Multi  | 273.05                                | 2.381  | LMTDS.0304EF             | Q-19-059 (Q-17-058A)                              | Q-19-067 (Q-14-003)<br>Q-19-145 (Q-08-021)        |
|                                  | Rover         |   | X            | 0.455                               | 0.444   | 0.039  | Multi  | 273.05                                | 2.381  | LMTDS.0304EF             | Q-19-059 (Q-17-058A)                              | Q-19-067 (Q-14-003)<br>Q-19-145 (Q-08-021)        |
|                                  | Snapper       |   | X            | 0.455                               | 0.444   | 0.039  | Multi  | 273.05                                | 2.381  | LMTDS.0304EF             | Q-19-059 (Q-17-058A)                              | Q-19-067 (Q-14-003)<br>Q-19-145 (Q-08-021)        |
|                                  | Troy-Bilt     |   | X            | 0.455                               | 0.444   | 0.039  | Multi  | 273.05                                | 2.381  | LMTDS.0304EF             | Q-19-059 (Q-17-058A)                              | Q-19-067 (Q-14-003)<br>Q-19-145 (Q-08-021)        |
|                                  | Yard Machines |   | X            | 0.455                               | 0.444   | 0.039  | Multi  | 273.05                                | 2.381  | LMTDS.0304EF             | Q-19-059 (Q-17-058A)                              | Q-19-067 (Q-14-003)<br>Q-19-145 (Q-08-021)        |
|                                  | Yard-Man      |   | X            | 0.455                               | 0.444   | 0.039  | Multi  | 273.05                                | 2.381  | LMTDS.0304EF             | Q-19-059 (Q-17-058A)                              | Q-19-067 (Q-14-003)<br>Q-19-145 (Q-08-021)        |

\*If not using CARB Component EOs, fill out test data information in #26-31.