



Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

**IT IS ORDERED AND RESOLVED:** That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

ENGINE DESCRIPTION			
MANUFACTURER	ENGINE FAMILY (E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)
MTD Southwest Inc.	LMTDS.0254AO (U-U-020-0378)	25	Gasoline
TBC = To Be Certified			
EQUIPMENT DESCRIPTION			
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)	EQUIPMENT APPLICATION
2020	LMTDS.0254AO	0.251	Line Trimmer
EMISSION CONTROL SYSTEMS		ENGINE and/or EQUIPMENT MODEL(S)	
P		See Attachment	
TANK TYPE: S=sealed M=metal P=treated HDPE or PE C=coextruded L=selar N=nylon A=acetal O=other (specify)			

The following are the evaporative emission standard (Title 13, California Code of Regulations, 13 CCR Section 2755 or 2757, as applicable), and certification level in g ROG·m<sup>-2</sup>·day<sup>-1</sup> for this evaporative family or the component Executive Order, as applicable.

PERMEATION EMISSION STANDARDS			
FUEL LINE PERMEATION (g ROG·m <sup>-2</sup> ·day <sup>-1</sup> )		FUEL TANK PERMEATION (g ROG·m <sup>-2</sup> ·day <sup>-1</sup> )	
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER
15	Q-19-067 (Q-14-003) Q-19-145 (Q-08-021)	2.0	Q-19-059 (Q-17-058A)

**BE IT FURTHER RESOLVED:** That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

This Executive Order hereby supersedes Executive Order U-U-020-0379 dated December 4, 2019.

Executed at El Monte, California on this 29<sup>th</sup> day of January 2020.

Allen Lyons, Chief  
Emissions Certification and Compliance Division

### Model Summary Sheet

(In #11, identify the fuel tank model exhibiting the highest permeation rate relative to the applicable permeation emission standard.)

11. Worst Case (Check One)	12. Model	13. Sales Codes (Check all appropriate)		14. Fuel Tank Volume (Liters)		16. Fuel Tank Internal Surface Area (m <sup>2</sup> )	16. Fuel Line Type (e.g. Single or Multi- Layer)	17. Fuel Line Length (mm)	18. Fuel Line Internal Diameter (mm)	19. Exhaust Family	20. Fuel Tank Component Executive Order*	21. Fuel Line Component Executive Order*
		Calif. Only	50-State	Total	Nominal							
X	P25TR.2		X	0.267	0.251	0.026	Multi	184.15	2.381	LMTDS.0254AO	Q-19-059 (Q-17-058A)	Q-19-067 (Q-14-003) Q-19-145 (Q-08-021)
	Bolens		X	0.267	0.251	0.026	Multi	184.15	2.381	LMTDS.0254AO	Q-19-059 (Q-17-058A)	Q-19-067 (Q-14-003) Q-19-145 (Q-08-021)
	Craftsman		X	0.267	0.251	0.026	Multi	184.15	2.381	LMTDS.0254AO	Q-19-059 (Q-17-058A)	Q-19-067 (Q-14-003) Q-19-145 (Q-08-021)
	Craftsman Pro		X	0.267	0.251	0.026	Multi	184.15	2.381	LMTDS.0254AO	Q-19-059 (Q-17-058A)	Q-19-067 (Q-14-003) Q-19-145 (Q-08-021)
	CUB CADET		X	0.267	0.251	0.026	Multi	184.15	2.381	LMTDS.0254AO	Q-19-059 (Q-17-058A)	Q-19-067 (Q-14-003) Q-19-145 (Q-08-021)
	Hyper Tough		X	0.267	0.251	0.026	Multi	184.15	2.381	LMTDS.0254AO	Q-19-059 (Q-17-058A)	Q-19-067 (Q-14-003) Q-19-145 (Q-08-021)
	Murray		X	0.267	0.251	0.026	Multi	184.15	2.381	LMTDS.0254AO	Q-19-059 (Q-17-058A)	Q-19-067 (Q-14-003) Q-19-145 (Q-08-021)
	Murray Select		X	0.267	0.251	0.026	Multi	184.15	2.381	LMTDS.0254AO	Q-19-059 (Q-17-058A)	Q-19-067 (Q-14-003) Q-19-145 (Q-08-021)
	Remington		X	0.267	0.251	0.026	Multi	184.15	2.381	LMTDS.0254AO	Q-19-059 (Q-17-058A)	Q-19-067 (Q-14-003) Q-19-145 (Q-08-021)
	Rover		X	0.267	0.251	0.026	Multi	184.15	2.381	LMTDS.0254AO	Q-19-059 (Q-17-058A)	Q-19-067 (Q-14-003) Q-19-145 (Q-08-021)
	Snapper		X	0.267	0.251	0.026	Multi	184.15	2.381	LMTDS.0254AO	Q-19-059 (Q-17-058A)	Q-19-067 (Q-14-003) Q-19-145 (Q-08-021)
	Troy-Bilt		X	0.267	0.251	0.026	Multi	184.15	2.381	LMTDS.0254AO	Q-19-059 (Q-17-058A)	Q-19-067 (Q-14-003) Q-19-145 (Q-08-021)
	Yard Machines		X	0.267	0.251	0.026	Multi	184.15	2.381	LMTDS.0254AO	Q-19-059 (Q-17-058A)	Q-19-067 (Q-14-003) Q-19-145 (Q-08-021)
	Yard-Man		X	0.267	0.251	0.026	Multi	184.15	2.381	LMTDS.0254AO	Q-19-059 (Q-17-058A)	Q-19-067 (Q-14-003) Q-19-145 (Q-08-021)

\*If not using CARB Component EOs, fill out test data information in #26-31.