

GENERAC POWER SYSTEMS, INC.

EXECUTIVE ORDER U-U-027-0271-1 New Off-Road Small Spark-Ignition Equipment

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following equipment produced by the manufacturer is certified as described below. Production equipment shall be in all material respects the same as those for which certification is granted.

ENGINE DESCRIPTION										
	MANUFACTURER	ENGINE FAMILY	(E.O. NUMBER)	ENGINE SIZE (cc)	FUEL TYPE (CNG/LNG=compressed/liquefied natural gas LPG=liquefied petroleum gas)					
LC	DNCIN MOTOR CO., LTD.	KCGPS.4202GR LCGPS.4202GR LSEMS.4592EM	(U-U-145-0413)	389,420, 439, 459	Gasoline					
S.A. = See Attachment TBC = To Be Certified EQUIPMENT DESCRIPTION										
MODEL YEAR	EVAPORATIVE FAMILY	FUEL TANK NOMINAL CAPACITY (liters)	EQUIPMENT APPLICATION							
2020	GNXCM3	See Attachment	Generator Set							
EMISSION	CONTROL SYSTEMS (ECS)	ENGINE and/or EQUIPMENT MODEL								
Cart	oon Canister/Metal Tank	See Attachment								
A. ECS TYPE (Venting Control Type/Tank Barrier Type): 1. Venting Control Type and Code: Metal=M Treated HDPE or PE=P Co-extruded=C Selar=L Nylon=N Acetal=A Other=O B. EVAPORATIVE FAMILY 2-Letter CODE (Venting Control Codes = C, S, O); (Tank Barrier Codes = M, P, C, L, N, A, O). Note: Always list venting control type or code first before tank barrier type or code. Do not use abbreviations for ECS types.										

The following are the evaporative emission standards (Title 13, California Code of Regulations, 13 CCR Section 2754, as applicable), and certification levels in g organic material hydrocarbon equivalent day or g ROG·m²-day or grams per liter for this evaporative family or the component Executive Order, as applicable. The running loss emissions control has been demonstrated by the manufacturer.

DIURNAL EMISSION STANDARD (g organic material hydrocarbon equivalent·day¹)										
1.20 + 0.056 × Nominal Capacity (L)										
	INE PERMEATION ROG·m ⁻² ·day ⁻¹)		ANK PERMEATION ROG·m ⁻² ·day ⁻¹)	CARBON CANISTER BUTANE WORKING CAPACITY (grams per liter)						
STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER	STANDARD	CERTIFICATION LEVEL OR EXECUTIVE ORDER					
15	See Attachment	1.5	See Attachment	1.4	See Attachment					

BE IT FURTHER RESOLVED: That for the listed equipment, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2759 (labeling), Section 2774 (bond requirements) and 13 CCR Sections 2760 and 2764 (emission control system warranty).

Equipment certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the evaporative family and model-year listed above. Equipment in this family that is produced for any other model-year is not covered by this Executive Order.

This Executive Order hereby supersedes Executive Order U-U-027-0271 dated May 6, 2020.

Executed on this 8th_ day of October 2020.

Allen Lyons, Chief

Emissions Certification and Compliance Division

For CARB Use Only										
Executive Order: U-U-										
Attachment _	of									

Small Off-Road Evaporative Certification Database Form

MODEL SUMMARY

S1.	S2.	S	3.	S4.	S5.		S6.	S 7.	S8.	S9.	S10.	S11.	S12.	S13.	S14.
Worst Case (Check One)	Model	(check all appropriate) (Engine Class (I or II)	Fuel System (FI or CARB)		nk Volume iters)	Fuel Tank Internal Surface Area (m²)	Fuel Line Type (e.g. Single	Nominal Fuel Line Length ⁽¹⁾ (mm)	Fuel Line Inside Diameter (mm)	Engine Family	Fuel Tank Executive Order	Fuel Line Executive Order	Carbon Canister (or Working Capacity (g/L))/
		CA Only	50- State			Total	Nominal		or Multi- layer)	, ,					Other Venting Control Executive Order
	LSH420PGC1	х		II	CARB	34.00	32.00	0.645	MULTI LAYER	140	6	KCGPS.4202GR LCGPS.4202GR	Q-19-007B (Q-16-019)	Q-19-013 (C-U-05- 012) Q-19-002 (Q-14-008)	Q-19-099
	LSH420PGC2		х	II	CARB	34.00	32.00	0.802	MULTI LAYER	140	6	KCGPS.4202GR LCGPS.4202GR	Q-19-007B (Q-16-019)	Q-19-013 (C-U-05- 012) Q-19-002 (Q-14-008)	Q-19-099
х	ESH459PGE1		x	п	CARB	34.00	32.00	0.802	MULTI LAYER	175	6	LSEMS.4592EM	Q-19-007B (Q-16-019)	Q-18-024	Q-19-099